

	<p align="center">Руководство по производству полетов</p> <p align="center">Часть С Глава 3 Приложение</p> <p>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.O.34.002</p>
---	---	---

TRINIDAD / Jorge Henrich Intl.
Тринидад / Георг Ненрик

SLTR (B)

Bolivia
Боливия

LANDING MINIMUMS

RWY	A/c type	RNAV (GNSS) LNAV	VOR DME	VOR	NDB	CIRCLE-TO-LAND*		
						MDA (H)	CEIL	VIS
14	Falcon	95x2000 810'	110x1700 870'	150x2300 1000'	180x2700 1100'	1430' (280m)	(1250') (380m)	3700m
	B737/BBJ	95x2000 810'	110x1700 870'	150x2300 1000'	180x2700 1100'	1430' (280m)	(1250') (380m)	4600m
32	Falcon	-	-	-	-	1430' (280m)	(1250') (380m)	3700m
	B737/BBJ	-	-	-	-	1430' (280m)	(1250') (380m)	4600m

* - Circle-to-land for B737 (CAT D) not authorized after IAP RNAV (GNSS) and NDB to runway 14

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
14/32	Falcon	-	800m	800m	800m	-
14/32	B737/BBJ	-	1600m	1600m	1600m	-

RWY Heading

145/325

RWY Dimensions

2400x30m

ARP Coordinates

S 14 49.2

W 064 55.1

AD Elevation

509'/155m

	Дата введения в действие 11.05.2018	
--	--	--