(ASIIPOM

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

GUANGZHOU / Baiyun Гуанчжоу / Байюнь ZGGG (B)

China Китай

LANDING MINIMUMS

RWY	A/c	Missed apch	ILS			LOC (GS out)	
	type	climb grad mim	FULL	Limited	ALS out		ALS out
01	Falcon RRJ95 B737	3.0%	60x550 241'	60x750 241'	60x1200 241'	135x1700 480'	135x2000 480'
02L	Falcon RRJ95 B737	3.0%	60x550 245'	60x750 245'	60x1200 245'	130x1600 460'	130x1900 460'
02R	Falcon RRJ95 B737	3.2%	60x550 244'	60x750 244'	60x1200 244'	140x1800 500'	140x2100 500'
19	Falcon RRJ95 B737	2.5%	60x550 243'	60x750 243'	60x1200 243'	165x2200 580'	165x2400 580'
20L	Falcon RRJ95 B737	2.5%	60x550 244'	60x750 244'	60x1200 244'	125x1500 450'	125x1900 450'
20R	Falcon RRJ95 B737	2.5%	60x550 248'	60x750 248'	60x1200 248'	135x1600 480'	135x2000 480'

RWY	A/c	CIRCLI	NG
KW 1	type	MDA (H)	VIS
	Falcon	1200'	4400
	r alcon	(350m)	
All	RRJ95	1200'	4400
RWYs		(350m)	
	B737	1200'	5000
	D/3/	(350m)	

TAKE-OFF MINIMUMS

DWW	A/c type	With Runway Centerline Lights	Without Runway Centerline Lights (RCLL)		Runway Centerline Marking (RCLM)	
RWY		(RCLL) and Runway	with Runway Lights (RL)		without RCLL & RL	
		Lights (RL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
All RWYs	Falcon RRJ95 B737	RVR 400m VIS 800m		RVR 500m VIS 800m	-	

ГОРНЫЙ / MOUNTAINOUS TERRAIN

Дата расчета минимума аэродрома «11» 03. 2022 г.