

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
---	--	---

BRESCIA /Montichiari
Брешиа / Монтичьяри

LIPO (B)

Italy
Италия

LANDING MINIMUMS

RWY	A/c type	ILS CAT3A	ILS CAT 2		ILS CAT1					
		Missed approach climb gradient minimum								
		5.0%	5.0%	2.5%	5.0%			2.5%		
					FULL	TDZ or CL out	ALS out	FULL	TDZ or CL out	ALS out
32	Falcon	-	30xR300 433' RA106'	60xR450 533' RA211'	70xR550 VIS 800 565'	70xR750 VIS 800 565'	70x1200 565'	85xR600 VIS 800 613'	85xR750 VIS 800 613'	85x1300 613'
	RRJ95	DH 50'/15m RVR 200m	30xR300 433' RA106'	60xR450 533' RA211'	70xR550 VIS 800 565'	70xR750 VIS 800 565'	70x1200 565'	85xR600 VIS 800 613'	85xR750 VIS 800 613'	85x1300 613'
	B737	DH 50'/15m RVR 200m	30xR300 433' RA106'	60xR450 533' RA211'	70xR550 VIS 800 565'	70xR750 VIS 800 565'	70x1200 565'	85xR600 VIS 800 613'	85xR750 VIS 800 613'	85x1300 613'

RWY	A/c type	LOC (GS out)		VOR (+DME)	
			ALS out		ALS out
32	Falcon	130x1200 750'	130x1900 750'	130x1200 750'	130x1900 750'
	RRJ95	130x1200 750'	130x1900 750'	130x1500 750'	130x1900 750'
	B737	130x1200 750'	130x1900 750'	130x1200 750'	130x1900 750'

RWY	A/c type	CIRCLE-TO-LAND Not authorized Southwest of rwy		
		MDA (H)	CEIL	VIS
14/32	Falcon	1110' (230m)	(1080') (330m)	2400
	RRJ95	1110' (230m)	(1080') (330m)	3000
	B737	2000' (500m)	(1970') (600m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
13/34	Falcon RRJ95 B737	150	300	300	400	-

	Дата введения в действие 22.02.2019	
--	--	--