

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Пер. № 2.О.34.002</p>
--	---	--

KUOPIO
Куопио

EFKU (A)

Finland
Финляндия

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC (GS out)	RNAV (GNSS)		VOR	CIRCLE-TO-LAND		
					LNAV/VNAV	LNAV		MDA (H)	CEIL	VIS
15	F900	-	-	-	110xR1300 668'	135xR1700 750'	135xR1700 750'	1240' (280m)	(1250') (380m)	2400
	RRJ95	-	-	-	110xR1300 668'	135xR1700 750'	135xR1700 750'	1240' (280m)	(1250') (380m)	3000
	B737	-	-	-	110xR1300 668'	135xR1700 750'	135xR1700 750'	1240' (280m)	(1250') (380m)	3600
33	F900	60xR750 517'	60xR1200 517'	125xR1200 730'	135xR1400 660'	135xR1400 660'	-	1240' (280m)	(1250') (380m)	2400
	RRJ95	60xR800 517'	60xR1200 517'	125xR1200 730'	135xR1400 660'	135xR1400 660'	-	1240' (280m)	(1250') (380m)	3000
	B737	60xR750 517'	60xR1200 517'	125xR1200 730'	135xR1400 660'	135xR1400 660'	-	1240' (280m)	(1250') (380m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
15/33	F900 RRJ95 B737	-	250*	250*	400	-

* - LVP must be in force, otherwise take-off minimum is 400m

RWY Heading

147/327

RWY Dimensions

2800x60m

ARP Coordinates

N 63 00.5 E 027 47.7

AD Elevation

324'/ 99m

Дата утверждения	Дата введения в действие 13.05.2016	
------------------	--	--