

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Пер. № 2.О.34.002</p>
--	---	--

JYVASKYLA
Ювяскюля

EFJY (A)

Finland
Финляндия

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC (GS out)	RNAV (GNSS)		VOR	CIRCLE-TO-LAND		
					LNAV/VNAV	LNAV		MDA (H)	CEIL	VIS
12	F900	-	-	-	160xR1700 978'	180xR2000 1044'	185xC2100 1060'	1345' (270m)	(1215') (370m)	2400
	RRJ95	-	-	-	160xR1700 978'	180xR2000 1044'	185xC2100 1060'	1345' (270m)	(1215') (370m)	3000
	B737	-	-	-	160xR1700 978'	180xR2000 1044'	185xC2100 1060'	1510' (320m)	(1380') (420m)	3600
30	F900	60xR750 608'	60xR1200 608'	165xR1800 950'	130xR1300 835'	130xR1300 835'	160xR1700 930'	1345' (270m)	(1215') (370m)	2400
	RRJ95	60xR800 608'	60xR1200 608'	165xR1800 950'	130xR1500 835'	130xR1500 835'	160xR1700 930'	1345' (270m)	(1215') (370m)	3000
	B737	60xR750 608'	60xR1200 608'	165xR1800 950'	130xR1300 835'	130xR1300 835'	160xR1700 930'	1510' (320m)	(1380') (420m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
12/30	F900 RRJ95 B737	-	250*	250*	400	-

* - LVP must be in force, otherwise take-off minimum is 400m

RWY Heading

125/305

RWY Dimensions

2601x60m

ARP Coordinates

N 62 24.1 E 025 40.4

AD Elevation

460'/ 140m

Дата утверждения	Дата введения в действие 13.05.2016	
------------------	--	--