(ASIIPOM A B N A

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

TASHKENT / Islam Karimov Ташкент / Ислам Каримов UTTT (A)

Uzbekistan Узбекистан

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1			VOR DME CDFA	
			FULL	Limited	ALS out		ALS out
08L	Falcon RRJ95 B737	30x300 1469' RA 105'	60x550 1569'	60x750 1569'	60x1200 1569'	135x2200 1810'	
08R	Falcon RRJ95 B737	-	60x750 1569'		60x1200 1569'	230x4000 2120'	
26L	Falcon RRJ95 B737	1	-		-	175x3300 1990'	
26R	Falcon RRJ95 B737		60x750 1614'		60x1200 1614'	175x3000 1990'	

RWY	A/c type	CIRCLING NOT AUTHORIZED AT NIGHT		
		MDA (H)	VIS	
All RWYs	Falcon RRJ95 B737	2600' (360m)	5000	

TAKE-OFF MINIMUMS

		With Runway	Without Runway Centerline Lights		Runway Centerline Marking	
	A/c	Centerline Lights		(RCLL)	(RCLM)	
RWY	type	(RCLL) and Runway	with Runway Lights (RL)		without RCLL & RL	
		Lights (RL)		NIGHT (Runway End		
			DAY	Identifier Lights are	DAY	NIGHT
				Needed)		
	Falcon					
08L/26R	RRJ95	150	300	300	500	-
	B737					
	Falcon					
08R/26L	RRJ95	-	300	300	500	-
	B737					