

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
---	---	---

THESSALONIKI/ Makedonia
Салоники / Македония

LGTS (B)

Greece
Греция

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1			
		Missed apch climb grad mim 4.0%	Missed apch climb grad mim 4.0%		Missed apch climb grad mim 2.5%	
			FULL	ALS out	FULL	ALS out
16	Falcon RRJ95 B737	46xR450 164' RA164'	65xR750 VIS 800 214'	65x1200 V214'	110x1300 374'	110x1700 374'

RWY	A/c type	VOR DME or VOR (+DME)	CIRCLE-TO-LAND Not authorized in sector inbound 162° to 280° clockwise		
		ALS out	MDA (H)	CEIL	VIS
16	Falcon	200x2400 660'	1400' (420m)	(1710') (520m)	2400
	RRJ95	200x2400 660'	1400' (420m)	(1710') (520m)	3000
	B737	200x2400 660'	1800' (540m)	(2110') (640m)	3600
34	Falcon	390x5000 1300'	1400' (420m)	(1710') (520m)	2400
	RRJ95	390x5000 1300'	1400' (420m)	(1710') (520m)	3000
	B737	390x5000 1300'	1800' (540m)	(2110') (640m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
16/34	Falcon RRJ95 B737	150	300	300	400	-

	Дата введения в действие 28.05.2018	
--	--	--