## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

TEKIRDAG /Chorlu Intl. Текирдаг / Чорлу LBTU (B)

Turkey Турция

## **LANDING MINIMUMS**

RWY	A/c	ILS			LOC (GS out)		
IX VV I	type	FULL	Limited	ALS out		ALS out	
	Falcon	60xR550	60xR750	60x1200	105x900	105x1600	
04	RRJ95	VIS 800	VIS 800	708'	850'	850'	
	B737	708'	<i>708'</i>	708			

RWY	A/c	VOR Z (+DME)		VOR Z		NDB Z (+DME)		NDB Z (+DME)	
IX VV I	type	CDFA		non-CDFA		CDFA		non-CDFA	
			ALS out		ALS out		ALS out		ALS out
	Falcon	120x1100 900'	120x1800 900'	120x1500 900'	120x2200 900'	120x1100 900'	120x1800 900'	120x1500 900'	120x2200 900'
04	RRJ95	120x1500 900'	120x1800 900'	120x1500 900'	120x2200 900'	150x1800 1000'	150x1800 1000'	150x1800 1000'	150x2200 1000'
	B737	120x1100 900'	120x1800 900'	120x1500 900'	120x2200 900'	120x1100 900'	120x1800 900'	120x1500 900'	120x2200 900'
22	Falcon RRJ95 B737	135x1600 1000'	135x2000 1000'	135x2000 1000'	135x2400 1000'	150x1800 1050'	150x2200 1050'	150x2200 1050'	150x2600 1050'

RWY	A/c	CIRCLE-TO-LAND Including VOR-A&B: NDB-A&B			
	type	MDA (H)	CEIL	VIS	
	Falcon	1700'	(1480')	2400	
	Talcon	(350m)	(450m)		
04/22	RRJ95	1700'	(1480')	3000	
04/22		(350m)	(450m)		
	B737	1700'	(1480')	3600	
	D/3/	(350m)	(450m)		

## **TAKE-OFF MINIMUMS**

	With Runway A/c Centerline Lights			t Runway Centerline Lights L) with Runway Lights (RL)	Runway Centerline Marking (RCLM) without RCLL & RL	
RWY	type	(RCLL) and Runway Lights (RL)	DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
04/22	Falcon RRJ95 B737	150	300	300	400	-

Дата введения в действие	
14.04.2019	