



Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. №
2.О.34.002

KATOWICE / Pyrzowice
Катовице / Пыржовице

EPKT (A)

Poland
Польша

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS			LOC (GS out)		VOR (+DME)	
			FULL	TDZ or CL out	ALS out		ALS out		ALS out
09	Falcon RRJ95 B737/BBJ	-	-	-	-	-	-	115x1300* 1350'	115x1700 1350'
27	Falcon RRJ95 B737/BBJ	33xR300 1112' RA105'	65xR550 VIS 800 1208'	65xR750 VIS 800 1208'	65x1200 1208'	100x800 1330'	100x1500 1330'	130x1300* 1440'	130x2000 1440'

* - VIS 1500 for RRJ95

RWY	A/c type	RNAV (GNSS) LNAV/VNAV		RNAV (GNSS) LNAV		CIRCLE-TO-LAND		
			ALS out		ALS out	MDA (H)	CEIL	VIS
09	Falcon	85x900 1240'	85x1300 1240'	125x1500 1380'	125x1900 1380'	1820' (250m)	(1150') (350m)	2400
	RRJ95	100x1500 1300'	100x1500 1300'	125x1500 1380'	125x1900 1380'	1820' (250m)	(1150') (350m)	3000
	B737 BBJ	85x900 1240'	85x1300 1240'	125x1500 1380'	125x1900 1380'	1860' (260m)	(1180') (360m)	3600
27	Falcon	95xR750 VIS 800 1310'	95x1400 1310'	125x1200 1410'	125x1900 1410'	1820' (250m)	(1150') (350m)	2400
	RRJ95	100x1500 1330'	100x1500 1330'	125x1500 1410'	125x1900 1410'	1820' (250m)	(1150') (350m)	3000
	B737 BBJ	95xR750 VIS 800 1310'	95x1400 1310'	125x1200 1410'	125x1900 1410'	1860' (260m)	(1180') (360m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
09/27	Falcon RRJ95 B737	150	300	300	400	-

Дата утверждения

Дата введения в действие
01.11.2017