(ASIIPOM

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

RECIFE / Guararapes-Gilberto Freyre Intl. Pecuφu / Γγαραραπиς SBRF (B)

Brazil Бразилия

LANDING MINIMUMS

RWY	A/c	ILS		LOC (GS out)		VOR		NDB	
	type		ALS out		ALS out		ALS out		ALS out
18	Falcon	DA (H) - 223' (60m)		MDA (H) - 450' (130m)		MDA (H) - 700' (210m)		MDA (H) - 650' (190m)	
	B737	CEIL - 200' VIS - 1300m		CEIL - 500' VIS - 2500m		CEIL - 700' VIS - 3100m		CEIL - 700' VIS - 2900m	

RWY	A/c type	RNAV	CIRCLE-TO-LAND			
		LNAV/VNAV	LNAV	CIRCLE-TO-LAND		
		ALS out	ALS out	MDA (H)	CEIL	VIS
	Falcon	DA (H) - 467' (135m)	MDA (H) - 640' (190m)	72 0'	(1020')	2900
18		CEIL - 500' VIS - 2100m	CEIL - 700' VIS - 2800m	(210m)	(310m)	
10	B737	DA (H) - 467' (135m)	MDA (H) - 640' (190m)	7 60'	(1050')	3600
		CEIL - 500' VIS - 2100m	CEIL - 700' VIS - 2800m	(220m)	(320m)	
	Falcon	DA (H) - 585' (170m)	MDA (H) - 640' (185m)	<i>720'</i>	(1020')	2900
36		CEIL - 600' VIS - 2500m	CEIL - 700' VIS - 2800m	(210m)	(310m)	
30	B737	DA (H) - 585' (170m)	MDA (H) - 640' (185m)	760'	(1050')	3600
		CEIL - 600' VIS - 2500m	CEIL - 700' VIS - 2800m	(220m)	(320m)	

TAKE-OFF MINIMUMS

RWY	A/c type	Conditions		t Runway Centerline Lights ith Runway Lights (RL) and RCLM	RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
18/36	Falcon B737	Take-off Alternate Airport Filed	300'x600m		Available	-
18/36	Falcon B737	Take-off Alternate Airport not Filed	Available Landing Minimums		Landing Minimums	-

RWY Heading 184/004

RWY Dimensions 3007x45m

ARP Coordinates S 08 07.6 W 034 55.4

AD Elevation 33'/10m

Дата введения в действие	
21.05.2018	