

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

DAKHLA Дахла GMMH (B)

LANDING MINIMUMS

RWY	A/c type	ILS	LOC (GS out)	RNAV (GNSS) LNAV	VOR (+DME)	CIRCLE-TO-LAND		
						after VOR apch		
						MDA (H)	CEIL	VIS
	Falcon	65x1200	140x2100	135x2100	140x2100	690'	(990')	2400
		240'	490'	480'	490'	(200m)	(300m)	
03	RRJ95	65x1200	140x2100	135x2100	140x2100	690'	(990')	3000
03		<i>240'</i>	490'	480'	490'	(200m)	(300m)	
	B737	65x1200	140x2100	135x2100	140x2100	750'	(1050')	3600
		<i>240'</i>	490'	480'	490'	(220m)	(320m)	
21	Falcon	-	-	110x1600	-	690'	(990')	2400
				380'		(200m)	(300m)	
	RRJ95	-	-	110x1600		690'	(990')	3000
				380'		(200m)	(300m)	
	B737			110x1600	-	750'	(1050')	3600
			-	380'		(220m)	(320m)	

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (RCLL) and	Without Runway Centerline Lights (RCLL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without RCLL & RL	
		Runway Lights (RL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
03/21	Falcon RRJ95 B737	-	300*	300*	400	-

^{* -} LVP must be in force

RWY Heading 028/208

RWY Dimensions 3000x45m

ARP Coordinates N 23 43.1 W 015 55.9

AD Elevation 36'/11m

Дата введения в действие	
21.09.2019	