

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
---	---	---

MAASTRICHT / Maastrich-Aachen
Маастрихт / Маастрихт-Ахен

EHBK (B)

Netherlands
Нидерланды

LANDING MINIMUMS

RWY	A/c type	ILS CAT 3A	ILS CAT 2	ILS CAT 1			LOC (GS out)	
				FULL	TDZ or CL out	ALS out		ALS out
03	Falcon RRJ95 B737	-	-	60xR750 VIS 800 (60x800 for RRJ95) 566'			110x1200 720'	110x1600 720'
21	Falcon	-	30xR300 471' RA107'	60xR550 VIS 800 571'	60xR750 VIS 800 571'	60x1200 571'	105x800 710'	105x1500 710'
	RRJ95	DH 50'/15m RVR 200m	30xR300 471' RA107'	60xR550 VIS 800 571'	60xR750 VIS 800 571'	60x1200 571'	105x800 710'	105x1500 710'
	B737	DH 50'/15m RVR 200m	30xR300 471' RA107'	60xR550 VIS 800 571'	60xR750 VIS 800 571'	60x1200 571'	105x800 710'	105x1500 710'

RWY	A/c type	NDB CDFA		CIRCLE-TO-LAND		
			ALS out	MDA (H)	CEIL	VIS
03	Falcon	145x1800 830'	145x2200 830'	1200' (250m)	(1150') (350m)	2400
	RRJ95	150x1800 860'	150x2200 860'	1200' (250m)	(1150') (350m)	3000
	B737	145x1800 830'	145x2200 830'	1200' (250m)	(1150') (350m)	3600
21	Falcon	165x1700 900'	165x2400 900'	1200' (250m)	(1150') (350m)	2400
	RRJ95	165x1700 900'	165x2400 900'	1200' (250m)	(1150') (350m)	3000
	B737	165x1700 900'	165x2400 900'	1200' (250m)	(1150') (350m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
03/21	Falcon RRJ95 B737	150	300	300	400	-

	Дата введения в действие 27.07.2018	
--	--	--