



# Руководство по производству полетов

## Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Пер. №  
2.0.34.002

**LONDON / Luton**  
Лондон /Лутон

**EGGW (B)**

**United Kingdom**  
Великобритания

### LANDING MINIMUMS

RWY	A/c type	ILS CAT 3A	ILS CAT 2	ILS CAT1			LOC (GS out)	
				FULL	TDZ or CL out	ALS out		ALS out
08	Falcon	-	30xR300 615' RA127'	60xR750 VIS 800 715'		60x1200 715'	120x1400 910'	120x1800 910'
	RRJ95 B737/BBJ	DH 50'/15m RVR 200m						
26	Falcon	-	30xR300 608' RA132'	60xR550 VIS 800 708'	60xR750 VIS 800 708'	60x1200 708'	110x900 860'	110x1600 860'
	RRJ95 B737/BBJ	DH 50'/15m RVR 200m						

RWY	A/c type	NDB		SRA (обзорный РЛ)		CIRCLE-TO-LAND		
			ALS out		ALS out	MDA (H)	CEIL	VIS
08	Falcon	-	-	145x1800 990'	145x2200 990'	1300' (240m)	(1100') (340m)	2400
	RRJ95	-	-	145x1800 990'	145x2200 990'	1300' (240m)	(1100') (340m)	3000
	B737/BBJ	-	-	145x1800 990'	145x2200 990'	1300' (240m)	(1100') (340m)	3600
26	Falcon	130x1300 930'	130x2000 930'	135x1300 940'	135x2000 940'	1300' (240m)	(1100') (340m)	2400
	RRJ95	150x1800 1020'	150x2000 1020'	135x1300 940'	135x2000 940'	1300' (240m)	(1100') (340m)	3000
	B737/BBJ	130x1300 930'	130x2000 930'	135x1300 940'	135x2000 940'	1300' (240m)	(1100') (340m)	3600

### TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
08/26	Falcon RRJ95 B737/BBJ	150	300	300	400	-

Дата введения в действие  
26.01.2018