



BELFAST / Aldergrove
Белфаст

EGAA (B)

United Kingdom
Великобритания

LANDING MINIMUMS

RWY	A/c type	ILS CAT 3A	ILS CAT 2	ILS CAT 1	ILS ALS out	LOC+DM E (GS out) CDFA	LOC+DME (GS out) ALS out CDFA	LOC (GS out) non-CDFA	LOC (GS out) ALS out non-CDFA
17	Falcon	-	-	60x750 406'	60x1200 406'	120x1100 600'	120x1800 600'	-	-
	RRJ95	-	-	60x800 406'	60x1200 406'	120x1100 600'	120x1800 600'	-	-
	B737	-	-	60x750 406'	60x1200 406'	120x1100 600'	120x1800 600'	-	-
25	Falcon	-	30x300 368' RA108'	60x550 468'	60x1200 468'	125x1200 680'	125x1900 680'	150x1900 760'	150x2700 760'
	RRJ95	DH 50'/15m RVR 200m	30x300 368' RA108'	60x550 468'	60x1200 468'	125x1200 680'	125x1900 680'	150x1900 760'	150x2700 760'
	B737	DH 50'/15m RVR 200m	30x300 368' RA108'	60x550 468'	60x1200 468'	125x1200 680'	125x1900 680'	150x1900 760'	150x2700 760'

RWY	A/c type	RNAV (GNSS)		VOR DME	NDB	SRA (non-CDFA)	CIRCLE-TO-LAND		
		LNAV/VNAV	LNAV				MDA (H)	CEIL	VIS
07	Falcon	95xR1000 520'	125xR1500 610'	135xR1700 650'	-	130xR2000 630'	1180' (280m)	(1250') (380m)	2400
	RRJ95	100xR1500 535'	125xR1500 610'	135xR1700 650'	-	130xR2000 630'	1180' (280m)	(1250') (380m)	3000
	B737	95xR1000 520'	125xR1500 610'	135xR1700 650'	-	130xR2000 630'	1280' (310m)	(1350') (410m)	3600
17	Falcon	-	-	120xR1100 600'	-	130xR1700 630'	1180' (280m)	(1250') (380m)	2400
	RRJ95	-	-	120xR1500 600'	-	130xR1700 630'	1180' (280m)	(1250') (380m)	3000
	B737	-	-	120xR1100 600'	-	130xR1700 630'	1280' (310m)	(1350') (410m)	3600
25	Falcon	-	-	120xR1100 660'	150xR1500 760'	195xC2700 910'	1180' (280m)	(1250') (380m)	2400
	RRJ95	-	-	120xR1100 660'	150xR1500 760'	195xC2700 910'	1180' (280m)	(1250') (380m)	3000
	B737	-	-	120xR1100 660'	150xR1500 760'	195xC2700 910'	1280' (310m)	(1350') (410m)	3600

Дата утверждения

Дата введения в действие
21.07.2016



Руководство по производству полетов
Часть С Глава 3 Приложение
Эксплуатационные минимумы каждого из аэродромов,
которые предполагается использовать в качестве
аэродромов намеченной посадки или запасных аэродромов

Per. №
2.O.34.002

RWY	A/c type	RNAV (GNSS)		VOR DME	NDB	SRA (non-CDFA)	CIRCLE-TO-LAND		
		LNAV/VNAV	LNAV				MDA (H)	CEIL	VIS
35	Falcon	-	-	130xR1600 680'	-	135xC2100 700'	1180' (280m)	(1250') (380m)	2400
	RRJ95	-	-	130xR1600 680'	-	135xC2100 700'	1180' (280m)	(1250') (380m)	3000
	B737	-	-	130xR1600 680'	-	135xC2100 700'	1280' (310m)	(1350') (410m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
07/25	Falcon RRJ95 B737	150	300	300	400	-
17/35	Falcon RRJ95 B737	-	300	300	400	-

Дата утверждения

Дата введения в действие
21.07.2016