

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Per. № 2.O.34.002</p>
--	---	---

LIMA-CALLAO / Jorge Chavez
Лима-Кальяо / Хорхе Чавес

SPJC (B)

Peru
Перу

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1	ILS ALS out	LOC (GS out)	RNAV (RNP 0.30)	VOR	CIRCLE-TO-LAND Not authorized East of airport		
								MDA (H)	CEIL	VIS
15	Falcon	30xR350 146' RA106'	60xR550 246'	60xR1200 246'	100xR1600 370'	160x2000 570'	180x3200 630'	870' (230m)	(1080') (330m)	5000
	B737	30xR350 146' RA106'	60xR550 246'	60xR1200 246'	100xR1600 370'	160x2000 570'	180x3200 630'	870' (230m)	(1080') (330m)	5000
33	Falcon	-	-	-	-	-	200x4000 750'	870' (230m)	(1080') (330m)	5000
	B737	-	-	-	-	-	200x4000 750'	870' (230m)	(1080') (330m)	5000

TAKE-OFF MINIMUMS*

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
15	Falcon	RVR 400m	RVR 400m	RVR 400m	RVR 400m	-
	B737	Vis 400m	Vis 400m	Vis 400m	Vis 400m	-
33	Falcon	Vis 800m	Vis 800m	Vis 800m	Vis 800m	-
	B737	Vis 1600m	Vis 1600m	Vis 1600m	Vis 1600m	-

* - Minimums listed are applicable in case of Take-off Alternate Airport filled (2 hour 1 eng inoperative for Falcon and 1 hour 1 eng inoperative for Boeing), otherwise Take-off minimum is not below available Landing Minimum.

ГОРНЫЙ / MOUNTAINUOS TERRAIN

RWY Heading 155/335

RWY Dimensions 3507x45m

ARP Coordinates S 12 01.3 W 077 06.9

AD Elevation 113'/ 34m

Дата утверждения	Дата введения в действие 18.07.2016	
------------------	--	--