



IQUITOS
Икитос

SPQT (B)

Peru
Перу

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC (GS out)	LOC (GS out) ALS out	VOR	VOR ALS out	CIRCLE-TO-LAND		
								MDA (H)	CEIL	VIS
06	Falcon	80x800 570'	80x1300 570'	110x1600 667'	110x2000 667'	150x2800 800'		1120' (250m)	(1150') (350m)	5000
	B737	80x800 570'	80x1300 570'	110x1600 667'	110x2000 667'	150x2800 800'		1120' (250m)	(1150') (350m)	5000
24	Falcon	-	-	-	-	155x2800 800'		1120' (250m)	(1150') (350m)	5000
	B737	-	-	-	-	155x2800 800'		1120' (250m)	(1150') (350m)	5000

TAKE-OFF MINIMUMS*

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
06/24	Falcon	-	Vis 800m	Vis 800m	Vis 800m	-
	B737	-	Vis 1600m	Vis 1600m	Vis 1600m	-

* - Minimums listed are applicable in case of Take-off Alternate Airport filled (2 hour 1 eng inoperative for Falcon and 1 hour 1 eng inoperative for Boeing), otherwise Take-off minimum is not below available Landing Minimum.

RWY Heading

063/243

RWY Dimensions

2500x45m

ARP Coordinates

S 03 47.1 W 073 18.5

AD Elevation

306'/ 93m

Дата утверждения	Дата введения в действие 18.07.2016	
------------------	--	--