



Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Per. №
2.O.34.002

ABERDEEN / Dyce
Абердин /Дайс

EGPD (B)

United Kingdom
Великобритания

LANDING MINIMUMS

RWY	A/c type	ILS		LOC (+DME) (GS out)		VOR DME		NDB DME	
			ALS out		ALS out		ALS out		ALS out
16	Falcon	60xR750 VIS 800 405'	60x1200 405'	150x1500 690'	150x2300 690'	225x2400 940'	225x2400 940'	-	-
	RRJ95	60x800 405'	60x1200 405'	150x1500 690'	150x2300 690'	225x2400 940'	225x2400 940'	-	-
	B737 BBJ	60xR750 VIS 800 405'	60x1200 405'	150x1500 690'	150x2300 690'	225x2400 940'	225x2400 940'	-	-
34	Falcon	60xR750 VIS 800 415'	60x1200 415'	150x1500 700'	150x2300 700'	255x2400 1050'	255x2400 1050'	285x2400 1140'	285x2400 1140'
	RRJ95	60xR750 415'	60x1200 415'	150x1500 700'	150x2300 700'	255x2400 1050'	255x2400 1050'	285x2400 1140'	285x2400 1140'
	B737 BBJ	60xR750 VIS 800 415'	60x1200 415'	150x1500 700'	150x2300 700'	255x2400 1050'	255x2400 1050'	285x2400 1140'	285x2400 1140'

RWY	A/c type	CIRCLE-TO-LAND					
		East of Rwy 16/34					
		MDA (H)	CEIL	VIS	MDA (H)	CEIL	VIS
16/34	Falcon	1070' (260m)	(1180') (360m)	2400	1430' (370m)	(1540') (470m)	2400
	RRJ95	1070' (260m)	(1180') (360m)	3000	1430' (370m)	(1540') (470m)	3000
	B737 BBJ	1070' (260m)	(1180') (360m)	3600	1430' (370m)	(1540') (470m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
16/34	Falcon RRJ95 B737	150	300	300	400	-

Дата утверждения

Дата введения в действие
04.10.2017