Руководство по производству полетов



Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Per. № 2.O.34.002

GIRONA Жирона LEGE (B)

Spain Испания

LANDING MINIMUMS

									CIRCLI	E-TO-
>									LAND	
RWY	A/c	ILS CAT	ILS	ILS	ILS	LOC	VOR	NDB	MDA	VIS
~	type	3A	CAT 2	CAT 1	ALS out	(GS out)			(H)	
	F900	-	-	-	-	-	140x1700	170x2100	1620'	2400
12							860'	960'	(350m)	
	RRJ95	-	-	-	-	1	140x1700	170x2100	1620'	3000
							860'	960'	(350m)	
	B737	-	-	-	-	-	140x1700	170x2100	2140'	3600
							860'	960'	(510m)	
	F900	-	50xR450	75x550	75x1300	135x1400	140x1500	210x2400	1620'	2400
			633'	715'	715'	910'	930'	1160'	(350m)	
			RA204'							
	RRJ95 DH 50'/15m	50xR450	75x550	75x1300	135x1400	140x1500	210x2400	1620'	3000	
30		RVR 200m	633'	715'	715'	910'	930'	1160'	(350m)	
		KVK ZUUIII	RA204'							
	B737	DH 50'/15m	50xR450	75x550	75x1300	135x1400	140x1500	210x2400	2140'	3600
			633'	715'	715'	910'	930'	1160'	(510m)	
		RVR 200m	RA204'							

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline		Runway Centerline Lights vith Runway Lights (RL)	RCLM (without Runway Centerline Lights, without Runway Lights)	
		Lights (CL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
02/20	F900 RRJ95 B737	150	300	300	400	-

Дата утверждения	Дата введения в действие	
	08.07.2016	