Руководство по производству полетов

Часть С Глава 3

B

Рег. №

2.O.34.002

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

MARIBOR / Orehova Vas Марибор / Орехова Вас

LJMB

Slovenia Словения

LANDING MINIMUMS

		ILS			LOC		Letr	
RWY	A/c	CAT 1			(GS out)			
	type	FULL	Limited	ALS out		ALS out		ALS out
32	Falcon	60x550	60x750	60x1200	110x900	110x1600	135x1300	135x2000
		1056'	1056'	1056'	1210'	1210'	1290'	1290'
	RRJ95	60x550	60x750	60x1200	110x900	110x1600	150x1800	150x2000
		1056'	1056'	1056'	1210'	1210'	1350'	1350'
	B737	60x550	60x750	60x1200	110x900	110x1600	135x1300	135x2000
		1056'	1056'	1056'	1210'	1210'	1290'	1290'

		CIRCLE-TO-LAND with prescribed flight tracks			
RWY	A/c				
	type	MDA (H)	VIS		
	Falson	1880'	2400		
	Falcon	(310m)			
14	RRJ95	1880'	3000		
14	KKJ93	(310m)			
	B737	2040'	3600		
	D/3/	(360m)			

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (RCLL) and Runway		Runway Centerline Lights (RCLL) h Runway Lights (RL)	Runway Centerline Marking (RCLM) without RCLL & RL	
		Lights (RL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
14/32	Falcon RRJ95 B737	150	300	300	400	-