

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
--	---	--

ROVANIEMI
Рованиеми

EFRO (A)

Finland
Финляндия

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1	ILS ALS out	RNAV (GNSS)		VOR	CIRCLE-TO-LAND		
					LNAV/VNAV	LNAV		MDA (H)	CEIL	VIS
03	F900	-	-	-	85xR750 910'	120xR1100 1027'	120xR1100 1027'	1330' (210m)	(1017') (310m)	2400
	RRJ95	-	-	-	100xR1500 962'	120xR1500 1027'	120xR1500 1027'	1330' (210m)	(1017') (310m)	3000
	B737	-	-	-	85xR750 910'	120xR1100 1027'	120xR1100 1027'	1365' (220m)	(1050') (320m)	3600
21	F900	32xR300 713' RA125'	60xR550 810'	60xR1200 810'	85xR750 890'	125xR1200 1020'	125xR1200 1020'	1330' (210m)	(1017') (310m)	2400
	RRJ95	32xR300 713' RA125'	60xR550 810'	60xR1200 810'	100xR1500 938'	125xR1500 1020'	125xR1500 1020'	1330' (210m)	(1017') (310m)	3000
	B737	32xR300 713' RA125'	60xR550 810'	60xR1200 810'	85xR750 890'	125xR1200 1020'	125xR1200 1020'	1365' (220m)	(1050') (320m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
03/21	F900 RRJ95 B737	150	300	300	400	-

Дата утверждения	Дата введения в действие 18.05.2016	
------------------	--	--