

	<p align="center">Руководство по производству полетов</p> <p align="center">Часть С Глава 3 Приложение</p> <p>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Per. № 2.O.34.002</p>
--	---	---

KHANH HOA / Cam Ranh Intl.
Хань Хоа/ Камрань

VVCR (B)

Vietnam
Вьетнам

LANDING MINIMUMS

RWY	A/c type	ILS		LOC (GS out)	
			ALS out		ALS out
02	Falcon RRJ95 B737 BBJ	DA (H) - 336' (95m) CEIL - 350' VIS – 1600m		MDA (H) - 860' (255m) CEIL - 860' VIS – 3800m	

RWY	A/c type	RNAV (GNSS) LNAV		VOR RWY02 VOR DME RWY20		NDB		CIRCLE-TO-LAND Not Authorized West of Runway		
					ALS out		ALS out	MDA (H)	CEIL	VIS
02	Falcon RRJ95 B737 BBJ	MDA (H) - 600' (180m) CEIL - 600' VIS – 3400m		MDA (H) - 830' (250m) CEIL-1320' VIS – 4500m		-		1820' (540m)	(2100') (640m)	5000
20	Falcon RRJ95 B737 BBJ	MDA (H) - 610' (175m) CEIL - 610' VIS – 3400m		MDA (H) - 660' (190m) CEIL - 660' VIS – 3400m		MDA (H) - 1970' (590m) CEIL - 1970' VIS – 6000m		1820' (540m)	(2100') (640m)	5000

TAKE-OFF MINIMUMS

RWY	A/c type	Take-Off Alternate Apt. Field	Take-Off Alternate Apt. Not Field
02/20	Falcon RRJ95 B737/BBJ	800m	Available Landing Minimums

Take-off alternate airports: Tan Son Nhat (VVTS), Da Nang (VVDN).

When the aircraft cannot choose any take-off alternate airports as mentioned above, the value of airport operating minima for take-off will be the value of landing equally.

ГОРНЫЙ / MOUNTAINOUS TERRAIN

RWY Heading 018/198

RWY Dimensions 3048x45m

ARP Coordinates N 11 59.7 E 109 13.1

AD Elevation + 43'/ 13m

Дата утверждения	Дата введения в действие 24.10.2017	
------------------	--	--