

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
---	---	---

BUCHAREST / Baneasa-Aurel Vlaicu
Бухарест /аэр. Бэняса им. Аурэла Влайку

LRBS (B)

Romania
Румыния

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1			LOC (GS out)		NDB (+DME)	
			FULL	TDZ or CL out	ALS out		ALS out		ALS out
07	Falcon RRJ95 B737/BBJ	30xR300 399' RA102'	60xR550 VIS 800 499'	60xR750 VIS 800 499'	60x1200 499'	125x1200 710'	125x1900 710'	185x2100 900'	185x2400 900'
25	Falcon	-	60xR750 VIS 800 482'		60x1200 482'	110x1200 640'	110x1600 640'	125x1500 690'	125x1900 690'
	RRJ95	-	60xR750 VIS 800 482'		60x1200 482'	110x1200 640'	110x1600 640'	150x1800 775'	150x1900 775'
	B737/BBJ	-	60xR750 VIS 800 482'		60x1200 482'	110x1200 640'	110x1600 640'	125x1500 690'	125x1900 690'

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
07/25	Falcon RRJ95 B737	150	300	300	400	-

	Дата введения в действие 25.12.2017	
--	--	--