

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Пер. № 2.О.34.002</p>
---	---	---

VERONA /Villafranca
Верона / Виллафранка

LIPX (B)

Italy
Италия

LANDING MINIMUMS

RWY	A/c type	ILS CAT 3A	ILS CAT 2	ILS CAT 1			LOC (GS out)	
				FULL	Limited	ALS out		ALS out
04	Falcon	-	41x400 353' RA 140'	65x550 432'	65x750 432'	65x1200 432'	110x900 570'	110x1600 570'
	RRJ95 B737	DH 50'/15m RVR 200m	41x400 353' RA 140'	65x550 432'	65x750 432'	65x1200 432'	110x900 570'	110x1600 570'

RWY	A/c type	RNAV (GNSS) LNAV/VNAV		RNAV (GNSS) LNAV		VOR (+DME)	
			ALS out		ALS out		ALS out
04	Falcon	115x1000 590'	115x1700 590'	135x1300 650'	135x2000 650'	185x2000 820'	185x2400 820'
	RRJ95	115x1500 590'	115x1700 590'	135x1500 650'	135x2000 650'	185x2000 820'	185x2400 820'
	B737	115x1000 590'	115x1700 590'	135x1300 650'	135x2000 650'	185x2000 820'	185x2400 820'

RWY	A/c type	CIRCLING	
		MDA (H)	VIS
04/22	Falcon	1000' (230m)	2400m
	RRJ95	1000' (230m)	3000m
	B737	1130' (270m)	3600m

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (RCLL) and Runway Lights (RL)	Without Runway Centerline Lights (RCLL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without RCLL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
04/22	Falcon RRJ95 B737	200* (150**)	300*	300*	400	-

* - LVP must be in force

** - Multiple RVR indications (TDZ, Mid, Rollout)

Дата расчета минимума аэродрома
«21» 10. 2021 г.