



TURKU
Турку

EFTU (A)

Finland
Финляндия

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	RNAV (GNSS)		VOR	CIRCLE-TO-LAND Not authorized South of airport		
				LNAV/VNAV	LNAV		MDA (H)	CEIL	VIS
08	F900	-	-	115xR1300 510'	140xR1700 590'	140xR1700 590'	820' (200m)	(985') (300m)	2400
	RRJ95	-	-	115xR1500 510'	140xR1700 590'	140xR1700 590'	820' (200m)	(985') (300m)	3000
	B737	-	-	115xR1300 510'	140xR1700 590'	140xR1700 590'	1048' (270m)	(1214') (370m)	3600
26	F900	60xR750 342'	60xR1200 342'	115xR1000 520'	130xR1300 568'	130xR1300 570'	820' (200m)	(985') (300m)	2400
	RRJ95	60xR800 342'	60xR1200 342'	115xR1500 520'	130xR1500 568'	130xR1500 570'	820' (200m)	(985') (300m)	3000
	B737	60xR750 342'	60xR1200 342'	115xR1000 520'	130xR1300 568'	130xR1300 570'	1048' (270m)	(1214') (370m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
08/26	F900 RRJ95 B737	-	250*	250*	400	-

* - LVP must be in force, otherwise take-off minimum is 400m

RWY Heading

077/257

RWY Dimensions

2500x60m

ARP Coordinates

N 60 30.9 E 022 15.7

AD Elevation

+162'/ 49m

Дата утверждения

Дата введения в действие
21.03.2016