

Vishwakarma Institute of Technology, Pune



**VISHWAKARMA INSTITUTE
OF TECHNOLOGY, PUNE**

COMPILER DESIGN PROJECT - I

Lexical Analyzer for C Language

Submitted To:

Prof. Anant Kaulage

Prof. Jyoti Kanjalkar-Kulkarni

Group members:

Riya Loya (12111145)

Rohan Sasne (12110431)

Tejas Rokade (12110154)

Rushikesh Chandak (12110202)


ABSTRACT

A compiler is a special program that processes statements written in a particular programming language and turns them into machine language or code that a computer's processors use. The file used for writing a C-language contains what are called the source statements. The programmer then runs the appropriate language compiler, specifying the name of the file that contains the source statements. When executing, the compiler first parses all of the language statements syntactically one after the other and then, in one or more successive stages, builds the output code, making sure that statements that refer to other statements are referred to correctly in the final code. The output of the compilation is called object code or sometimes an object module. Lexical analysis is the first phase of a compiler. It takes the modified source code from language preprocessors that are written in the form of sentences. The lexical analyzer breaks these syntaxes into a series of tokens, by removing any whitespace or comments in the source code. Symbol table is an important data structure created and maintained by compilers in order to store information about the occurrence of various entities such as variable names, function names, etc. Symbol table is used by both the analysis and the synthesis parts of a compiler. We have designed a lexical analyzer for the C language using lex. It takes as input a C code and outputs a stream of tokens. The tokens displayed as part of the output include keywords, identifiers, signed/unsigned integer/floating point constants, operators, special characters, headers, data-type specifiers, array, single-line comment, multi-line comment, preprocessor directive, pre-defined functions (printf and scanf), user-defined functions and the main function. The token, the type of token and the line number of the token in the C code are being displayed. The line number is displayed so that it is easier to debug the code for errors. Errors in single-line comments, multi-line comments are displayed along with line numbers. The output also contains the symbol table which contains tokens and their type. The symbol table is generated using the hash organisation.

COMPILER DESIGN PHASES

A compiler is a special program that processes statements written in a particular programming language and turns them into machine language or code that a computer's processors use. A compiler can broadly be divided into two phases based on the way they compile.


1. **Analysis phase:** Known as the front-end of the compiler, the analysis phase of the compiler reads the source program, divides it into core parts and then checks for lexical, grammar and syntax errors. The analysis phase generates an intermediate representation of the source program and symbol table. This phase consists of:
 - Lexical Analysis
 - Syntax Analysis
 - Semantic Analysis
 - Intermediate Code Generation
2. **Synthesis phase:** Known as the back-end of the compiler, the synthesis phase generates the target program with the help of intermediate source code representation and symbol table. This phase consists of:
 - Code Optimization
 - Code Generator



Lexical Analysis

Lexical analysis is the first phase of a compiler. It takes the modified source code from language preprocessors that are written in the form of sentences. The lexical analyzer breaks these syntaxes into a series of tokens, by removing any whitespace or comments in the source code.

If the lexical analyzer finds a token invalid, it generates an error. The lexical analyzer works closely with the syntax analyzer. It reads character streams from the source code, checks for legal tokens, and passes the data to the syntax analyzer when it demands.



Syntax Analysis

Syntax analysis or parsing is the second phase of a compiler. It takes the token produced by lexical analysis as input and generates a parse tree (or syntax tree).

Semantic Analysis

Semantic analysis is the third phase of a compiler. Semantic analyzer checks whether the parse tree constructed by the syntax analyzer follows the rules of language.

Intermediate Code generation

After semantic analysis the compiler generates an intermediate code of the source code for the target machine. It represents a program for some abstract machine. It is in between the high-level language and the machine language. This intermediate code should be generated in such a way that it makes it easier to be translated into the target machine code.

Code Optimization

In this phase, code optimization of the intermediate code is done. Optimization can be assumed as something that removes unnecessary code lines, and arranges the sequence of statements in order to speed up the program execution without wasting resources (CPU, memory).

Code Generation

In this phase, the code generator takes the optimized representation of the intermediate code and maps it to the target machine language.

THE LEXICAL ANALYSIS

In computer science, lexical analysis is the process of converting a sequence of characters (such as in a computer program or web page) into a sequence of tokens (strings with an identified "meaning"). A program that performs lexical analysis may be called a lexer, tokenizer, or scanner (though "scanner" is also used to refer to the first stage of a lexer). Such a lexer is generally combined with a parser, which together analyze the syntax of programming languages, web pages, and so forth.

The script written by us is a computer program called the "lex" program, is the one that generates lexical analyzers ("scanners" or "lexers"). Lex reads an input stream specifying the lexical analyzer and outputs source code implementing the lexer in the C programming language.

The structure of the lex program consists of three sections:

```
{definition section}
```

```
%%
```

```
{rules section}
```

```
%%
```

```
{C code section}
```

The definition section defines macros and imports header files written in C. It is also possible to write any C code here, which will be copied verbatim into the generated source file.

The rules section associates regular expression patterns with C statements. When the lexer sees text in the input matching a given pattern, it will execute the associated C code.

The C code section contains C statements and functions that are copied verbatim to generated source file. These statements presumably contain code called by the rules in the rules section. In large programs it is more convenient to place this code in a separate file linked in at compile time.

The lex program, when compiled using the lex command, generates a file called lex.yy.c, which when executed recognizes the tokens present in the input C program.

Lexical analysis only takes care of parsing the tokens and identifying their type. The output of this phase is the stream of tokens as well as the symbol table representing the tokens and their type.

THE LEX PROGRAM: (lexer.l)

```
%{
```

```
int lineno = 1;
```

```
#include<stdio.h>
#include<stdlib.h>
#include<string.h>
>
```

```
#define AUTO 1
#define BREAK 2
#define CASE 3
#define CHAR 4
#define CONST 5
#define CONTINUE 6
#define DEFAULT 7
#define DO 8
#define DOUBLE 9
#define ELSE 10
#define ENUM 11
#define EXTERN 12
#define FLOAT 13
#define FOR 14
#define GOTO 15
#define IF 16
#define INT 17
#define LONG 18
#define REGISTER 19
#define RETURN 20
#define SHORT 21
#define SIGNED 22
#define SIZEOF 23
#define STATIC 24
#define STRUCT 25
#define SWITCH 26
```

```
#define TYPEDEF 27
#define UNION 28
#define UNSIGNED 29
#define VOID 30
#define VOLATILE 31
#define WHILE 32
```

```
#define IDENTIFIER 33
#define SLC 34
#define MLCS 35
#define MLCE 36
```

```
#define LEQ 37
#define GEQ 38
#define EQEQ 39
#define NEQ 40
#define LOR 41
#define LAND 42
#define ASSIGN 43
#define PLUS 44
#define SUB 45
#define MULT 46
#define DIV 47
#define MOD 48
#define LESSER 49
#define GREATER 50
#define INCR 51
#define DECR 52

#define COMMA 53
```


#define SEMI 54

#define HEADER 55

#define MAIN 56

#define PRINTF 57

#define SCANF 58

#define DEFINE 59

#define INT_CONST 60

#define FLOAT_CONST 61

#define TYPE_SPEC 62

#define DQ 63

#define OBO 64

#define OBC 65

#define CBO 66

#define CBC 67

#define HASH 68

#define ARR 69

#define FUNC 70

#define NUM_ERR 71

#define UNKNOWN 72

#define CHAR_CONST 73

#define SIGNED_CONST 74

```
#define STRING_CONST 75
```

```
%}
```

```
alpha [A-Za-z]
```

```
digit [0-9]
```

```
und [_]
```

```
space [ ]
```

```
tab [ \t]
```

```
line [\n]
```

```
char
```

```
\.\' at
```

```
[@]
```

```
string \"(^[%d][%f][%s][%c])\"
```

```
%%
```

```
{space}* {}
```

```
{tab}* {}
```

```
{string} return STRING_CONST;
```

```
{char} return CHAR_CONST;
```

```
{line} {lineno++;}
```

```
auto return AUTO;
```

```
break return BREAK;
```

```
case return CASE;
```

```
char return CHAR;
```

```
const return CONST;
```

```
continue return CONTINUE;
```

```
default return DEFAULT;
```

```
do return DO;
```

```
double return
```

```
DOUBLE; else return
```

```
ELSE;
```

enum return ENUM;
extern return EXTERN;
float return FLOAT; for
return FOR;
goto return GOTO;
if return IF;
int return INT;
long return
LONG;
register return REGISTER;
return return RETURN;
short return SHORT;
signed return SIGNED;
sizeof return SIZEOF;
static return STATIC;
struct return STRUCT;
switch return SWITCH;
typedef return TYPEDEF;
union return UNION;
unsigned return UNSIGNED;
void return VOID;
volatile return VOLATILE;
while return WHILE;

printf return PRINTF;
scanf return SCANF;

{alpha}{alpha}|{digit}|{und})* return IDENTIFIER;

[+][0-9]{digit}*({digit}+)? return SIGNED_CONST;

"//" return SLC;
"/*" return MLCS;
"*/" return MLCE;

"<=" return LEQ;
">=" return GEQ;
"==" return EQEQ;
"!=" return NEQ;
"|" return LOR;
"&&" return LAND;
"=" return ASSIGN;
"+" return PLUS;
"-" return SUB;
"*" return MULT;
"/" return DIV;
"%" return MOD;
"<" return
LESSER;
">" return GREATER;
"++" return INCR;
"--" return DECR;

"," return COMMA;
";" return SEMI;

"#include<stdio.h>" return HEADER;
"#include <stdio.h>" return HEADER;
"main()" return MAIN;

{digit}+ return INT_CONST;
({digit}+)\.({digit}+) return FLOAT_CONST;

```
"%d" | "%f" | "%u" | "%s" return TYPE_SPEC;
```

```
"\" return DQ;
```

```
"(" return OBO;
```

```
")" return OBC;
```

```
"{" return CBO;
```

```
"}" return CBC;
```

```
"#" return
```

```
HASH;
```

```
{alpha}{alpha}|{digit}|{und})*\[{digit}*] return ARR;
```

```
{alpha}{alpha}|{digit}|{und})*\(({alpha}|{digit}|{und}|{space})*\) return FUNC;
```

```
({digit}+)\.({digit}+)\.({digit}|\.)* return NUM_ERR;
```

```
({digit}|{at})+({alpha}|{digit}|{und}|{at})* return UNKNOWN;
```

```
%%
```

```
struct node
```

```
{
```

```
    char token[100];
```

```
        char attr[100];
```

```
    struct node *next;
```

```
};
```

```
struct hash
```

```
{
```

```
    struct node *head;
```

```
    int count;
```

```
};
```

```
struct hash hashTable[1000];
```

```
int eleCount = 1000;
```

```

struct node * createNode(char *token, char *attr)
{
    struct node *newnode;
    newnode = (struct node *) malloc(sizeof(struct node));
    strcpy(newnode->token, token);
    strcpy(newnode->attr, attr);
    newnode->next = NULL;
    return newnode;
}

```

```

int hashIndex(char *token)
{
    int hi=0;
    int l,i;
    for(i=0;token[i]!='\0';i++)
    {
        hi = hi + (int)token[i];
    }
    hi = hi%eleCount;
    return hi;
}

```

```

void insertToHash(char *token, char *attr)
{
    int flag=0;
    int hi;
    hi = hashIndex(token);
    struct node *newnode = createNode(token, attr);
    /* head of list for the bucket with index "hashIndex" */
}

```

```

if (hashTable[hi].head==NULL)
{
    hashTable[hi].head = newnode;
    hashTable[hi].count = 1;
    return;
}
struct node *myNode;
    myNode = hashTable[hi].head;
while (myNode != NULL)
{
    if (strcmp(myNode->token, token)==0)
    {
        flag = 1;
        break;
    }
    myNode = myNode->next;
}
if(!flag)
{
    //adding new node to the list
    newnode->next = (hashTable[hi].head);
    //update the head of the list and no of nodes in the current bucket
    hashTable[hi].head = newnode;
    hashTable[hi].count++;
}
return;
}

void display()
{

```

```

struct node *myNode;

int i,j, k=1;

printf("                                ");

printf("\nSNo \t|\tToken \t|\tToken Type \t\n");

printf("                                \n");

for (i = 0; i < eleCount; i++)
{
    if (hashTable[i].count == 0)
        continue;

    myNode = hashTable[i].head;
    if (!myNode)
        continue;

    while (myNode != NULL)
    {
        printf("
        %d\t\t"
        , k++);
        printf("
        %s\t\t\
        t",
        myNode
        e->token);
        printf("
        %s\t\n"
        ,
        myNode
        e->attr)
        ;
        myNode
        e =
        myNode

```



```
e->next ;
```

```
int main()
{
    int scan, slcline=0, mlc=0, mlcline=0, dq=0, dqline=0;
    yyin = fopen("isPrime.c","r");
    printf("\n\n")
    ;    scan    =
    yylex();
    while(scan)
```

```

{
    if(lineno == slcline)
    {
        scan = yylex();
        continue;
    }

    if(lineno!=dqline && dqline!=0)
    {
        if(dq%2!=0)
            printf("\n***** ERROR!! INCOMPLETE STRING at Line %d
*****\n\n", dqline);
        dq=0;
    }

    if((scan>=1 && scan<=32) && mlc==0)
    {
        printf("%s\t\t\tKEYWORD\t\t\tLine %d\n", yytext, lineno);
        insertToHash(yytext, "KEYWORD");
    }

    if(scan==33 && mlc==0)
    {
        printf("%s\t\t\tIDENTIFIER\t\t\tLine %d\n", yytext, lineno);
        insertToHash(yytext, "IDENTIFIER");
    }

    if(scan==34)
    {
        printf("%s\t\t\tSingleline Comment\t\t\tLine %d\n", yytext, lineno);
        slcline = lineno;
    }

    if(scan==35 && mlc==0)
    {

```

```

        printf("%s\t\tMultiline Comment Start\t\tLine %d\n", yytext, lineno);
        mlcline = lineno;
        mlc = 1;
    }
    if(scan==36 && mlc==0)
    {
        printf("\n***** ERROR!! UNMATCHED MULTILINE COMMENT END %s at
Line %d *****\n\n", yytext, lineno);
    }
    if(scan==36 && mlc==1)
    {
        mlc = 0;
        printf("%s\t\tMultiline Comment End\t\tLine %d\n", yytext, lineno);
    }
    if((scan>=37 && scan<=52) && mlc==0)
    {
        printf("%s\t\tOPERATOR\t\tLine %d\n", yytext, lineno);
        insertToHash(yytext, "OPERATOR");
    }
    if((scan==53 || scan==54 || scan==63 || (scan>=64 && scan<=68)) && mlc==0)
    {
        printf("%s\t\tSPECIAL SYMBOL\t\tLine %d\n", yytext, lineno);
        if(scan==63)
        {
            dq++;
            dqline = lineno;
        }
        insertToHash(yytext, "SPECIAL SYMBOL");
    }
    if(scan==55 && mlc==0)

```

```
{  
    printf("%s\tHEADER\t\tLine %d\n",yytext, lineno);  
}  
  
if(scan==56 && mlc==0)  
{  
    printf("%s\t\tMAIN FUNCTION\t\tLine %d\n", yytext, lineno);  
    insertToHash(yytext, "IDENTIFIER");  
}  
  
if((scan==57 || scan==58) && mlc==0)  
{  
    printf("%s\t\tPRE DEFINED FUNCTION\t\tLine %d\n", yytext, lineno);  
    insertToHash(yytext, "PRE DEFINED FUNCTION");  
}  
  
if(scan==59 && mlc==0)  
{  
    printf("%s\t\tPRE PROCESSOR DIRECTIVE\t\tLine %d\n", yytext, lineno);  
}  
  
if(scan==60 && mlc==0)  
{  
    printf("%s\t\tINTEGER CONSTANT\t\tLine %d\n", yytext, lineno);  
    insertToHash(yytext, "INTEGER CONSTANT");  
}  
  
if(scan==61 && mlc==0)  
{  
    printf("%s\t\tFLOATING POINT CONSTANT\t\tLine %d\n", yytext, lineno);  
    insertToHash(yytext, "FLOATING POINT CONSTANT");  
}  
  
if(scan==62 && mlc==0)  
{  
    printf("%s\t\tTYPE SPECIFIER\t\tLine %d\n", yytext, lineno);
```

```

    }

    if(scan==69 && mlc==0)
    {

        printf("%s\t\t\tARRAY\t\t\t\tLine %d\n", yytext, lineno);

        insertToHash(yytext, "ARRAY");

    }

    if(scan==70 && mlc==0)
    {

        printf("%s\t\t\tUSER DEFINED FUNCTION\t\t\tLine %d\n", yytext, lineno);

        insertToHash(yytext, "USER DEFINED FUNCTION");

    }

    if(scan==71 && mlc==0)
    {

        printf("\n***** ERROR!! CONSTANT ERROR %s at Line %d
*****\n\n", yytext, lineno);

    }

    if(scan==72 && mlc==0)
    {

        printf("\n***** ERROR!! UNKNOWN TOKEN %s at Line %d
*****\n\n", yytext, lineno);

    }

    if(scan==73 && mlc==0)
    {

        printf("%s\t\t\tCHARACTER CONSTANT\t\t\t\tLine %d\n", yytext, lineno);

        insertToHash(yytext, "CHARACTER CONSTANT");

    }

    if(scan==74 && mlc==0)
    {

        printf("%s\t\t\tSIGNED CONSTANT\t\t\t\tLine %d\n", yytext, lineno);

        insertToHash(yytext, "SIGNED CONSTANT");

```

```

    }
    if(scan==75 && mlc==0)
    {
        printf("%s\t\t\tSTRING CONSTANT\t\t\tLine %d\n", yytext, lineno);
        insertToHash(yytext, "STRING CONSTANT");
    }

    scan = yylex();
}

if(mlc==1)
    printf("\n***** ERROR!! UNMATCHED COMMENT STARTING at Line %d
*****\n\n",mlcline);

printf("\n");
printf("\n\t***** SYMBOL TABLE *****\t\t\n");
display();

printf("                                \n\n");
}

int yywrap()
{
    return 1;
}

```

Input file (isPrime.c)

```

#include<stdio.h>

int main()
{
    int a,i,flag=0;
    printf("Input no");
    scanf("%d",&a);
    i=2;
    while(i <= a/2)
    {

```

f
l
a
g
=
1
;
b
r
e
a
k
;

Output:

```
shivananda@shivananda-X555LB: ~/Desktop
shivananda@shivananda-X555LB:~/Desktop$ lex lexer.l
shivananda@shivananda-X555LB:~/Desktop$ cc lex.yy.c
shivananda@shivananda-X555LB:~/Desktop$ ./a.out

#include<stdio.h>      HEADER      Line 1
int                   KEYWORD      Line 2
main()                MAIN FUNCTION Line 2
{                     SPECIAL SYMBOL Line 3
int                   KEYWORD      Line 4
a                     IDENTIFIER   Line 4
,                     SPECIAL SYMBOL Line 4
i                     IDENTIFIER   Line 4
flag                  IDENTIFIER   Line 4
=                     OPERATOR     Line 4
0                     INTEGER CONSTANT Line 4
;                     SPECIAL SYMBOL Line 4
printf                PRE DEFINED FUNCTION Line 5
(                     SPECIAL SYMBOL Line 5
Input                 IDENTIFIER   Line 5
no                    IDENTIFIER   Line 5
"                     SPECIAL SYMBOL Line 5
)                     SPECIAL SYMBOL Line 5
;                     SPECIAL SYMBOL Line 5
scanf                 PRE DEFINED FUNCTION Line 6
(                     SPECIAL SYMBOL Line 6
"%d                   TYPE SPECIFIER Line 6
"                     SPECIAL SYMBOL Line 6
,                     SPECIAL SYMBOL Line 6
&a                    IDENTIFIER   Line 6
)                     SPECIAL SYMBOL Line 6
;                     SPECIAL SYMBOL Line 6
i                     IDENTIFIER   Line 7
=                     OPERATOR     Line 7
2                     INTEGER CONSTANT Line 7
while                 SPECIAL SYMBOL Line 7
(                     SPECIAL SYMBOL Line 8
i                     IDENTIFIER   Line 8
<=                    OPERATOR     Line 8
a                     IDENTIFIER   Line 8
/                     OPERATOR     Line 8
2                     INTEGER CONSTANT Line 8
)                     SPECIAL SYMBOL Line 8
```

```
shivananda@shivananda-X555LB: ~/Desktop
{ SPECIAL SYMBOL Line 9
if KEYWORD Line 10
( SPECIAL SYMBOL Line 10
a IDENTIFIER Line 10
% OPERATOR Line 10
i IDENTIFIER Line 10
== OPERATOR Line 10
0 INTEGER CONSTANT Line 10
) SPECIAL SYMBOL Line 10
{ SPECIAL SYMBOL Line 11
flag IDENTIFIER Line 12
= OPERATOR Line 12
1 INTEGER CONSTANT Line 12
; SPECIAL SYMBOL Line 12
break KEYWORD Line 13
; SPECIAL SYMBOL Line 13
; SPECIAL SYMBOL Line 14
i IDENTIFIER Line 15
++ OPERATOR Line 15
; SPECIAL SYMBOL Line 15
; SPECIAL SYMBOL Line 16
} KEYWORD Line 17
if KEYWORD Line 17
( SPECIAL SYMBOL Line 17
flag IDENTIFIER Line 17
== OPERATOR Line 17
0 INTEGER CONSTANT Line 17
) SPECIAL SYMBOL Line 17
printf PRE DEFINED FUNCTION Line 18
( SPECIAL SYMBOL Line 18
" SPECIAL SYMBOL Line 18
%d TYPE SPECIFIER Line 18
Prime IDENTIFIER Line 18
" SPECIAL SYMBOL Line 18
, SPECIAL SYMBOL Line 18
a IDENTIFIER Line 18
) SPECIAL SYMBOL Line 18
; SPECIAL SYMBOL Line 18
else KEYWORD Line 19
printf PRE DEFINED FUNCTION Line 20
( SPECIAL SYMBOL Line 20
" SPECIAL SYMBOL Line 20
Not IDENTIFIER Line 20
Prime IDENTIFIER Line 20
" SPECIAL SYMBOL Line 20
) SPECIAL SYMBOL Line 20
; SPECIAL SYMBOL Line 20
return KEYWORD Line 21
```

```
shivananda@shivananda-X555LB: ~/Desktop
) SPECIAL SYMBOL Line 20
; SPECIAL SYMBOL Line 20
return KEYWORD Line 21
0 INTEGER CONSTANT Line 21
; SPECIAL SYMBOL Line 21
} SPECIAL SYMBOL Line 22

***** SYMBOL TABLE *****
-----
SNo | Token | Token Type
-----
1 | " | SPECIAL SYMBOL
2 | % | OPERATOR
3 | ( | SPECIAL SYMBOL
4 | ) | SPECIAL SYMBOL
5 | , | SPECIAL SYMBOL
6 | / | OPERATOR
7 | 0 | INTEGER CONSTANT
8 | 1 | INTEGER CONSTANT
9 | 2 | INTEGER CONSTANT
10 | ; | SPECIAL SYMBOL
11 | = | OPERATOR
12 | ++ | OPERATOR
13 | a | IDENTIFIER
14 | i | IDENTIFIER
15 | <= | OPERATOR
16 | == | OPERATOR
17 | { | SPECIAL SYMBOL
18 | } | SPECIAL SYMBOL
19 | if | KEYWORD
20 | no | IDENTIFIER
21 | Not | IDENTIFIER
22 | int | KEYWORD
23 | flag | IDENTIFIER
24 | else | KEYWORD
25 | main() | IDENTIFIER
26 | Prime | IDENTIFIER
27 | break | KEYWORD
28 | scanf | PRE DEFINED FUNCTION
29 | Input | IDENTIFIER
30 | while | KEYWORD
31 | printf | PRE DEFINED FUNCTION
32 | return | KEYWORD
-----

shivananda@shivananda-X555LB:~/Desktop$
```


TEST CASES

Without errors

1. Input file

(test5.c) :

```
#include<stdio.h>
```

```
void foo()
```

```
{
```

```
    return;
```

```
}
```

```
void main()
```

```
{
```


```
    int a;
```

```
    foo();
```

```
    //user defined function
```

```
}
```

Output :



```
shivananda@shivananda-X555LB: ~/Desktop
shivananda@shivananda-X555LB:~/Desktop$ lex lexer.l
shivananda@shivananda-X555LB:~/Desktop$ cc lex.yy.c
shivananda@shivananda-X555LB:~/Desktop$ ./a.out

#include<stdio.h>      HEADER      Line 1
void                  KEYWORD      Line 2
foo()                 USER DEFINED FUNCTION      Line 2
{                     SPECIAL SYMBOL      Line 3
return                KEYWORD      Line 4
;                     SPECIAL SYMBOL      Line 4
}                     SPECIAL SYMBOL      Line 5
void                  KEYWORD      Line 6
main()                MAIN FUNCTION      Line 6
{                     SPECIAL SYMBOL      Line 7
int                   KEYWORD      Line 8
a                     IDENTIFIER      Line 8
;                     SPECIAL SYMBOL      Line 8
foo()                 USER DEFINED FUNCTION      Line 9
;                     SPECIAL SYMBOL      Line 9
//                    SingleLine Comment      Line 10
}                     SPECIAL SYMBOL      Line 11

***** SYMBOL TABLE *****
SNo | Token | Token Type
-----|-----|-----
1 | ; | SPECIAL SYMBOL
2 | a | IDENTIFIER
3 | { | SPECIAL SYMBOL
4 | } | SPECIAL SYMBOL
5 | int | KEYWORD
6 | foo() | USER DEFINED FUNCTION
7 | void | KEYWORD
8 | main() | IDENTIFIER
9 | return | KEYWORD

shivananda@shivananda-X555LB:~/Desktop$
```

2. Input file

(test2.c) :

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    signed int a = -2;
```

```
    //Single line comment
```

```
    a++;
```

```
    printf("%d\n", a);
```

```
    /* Multiline
```

```
    comment
```

```
    */
```

```
}
```

Output :

```
shivananda@shivananda-X555LB: ~/Desktop
#include<stdio.h>
void
main()
{
signed
int
a
=
-2
;
//
printf
(
"
%d\n
"
,
a
)
;
/*
Multiline
comment
*/
}
```

SNo	Token	Token Type
1	"	SPECIAL SYMBOL
2	(SPECIAL SYMBOL
3)	SPECIAL SYMBOL
4	,	SPECIAL SYMBOL
5	;	SPECIAL SYMBOL
6	=	OPERATOR
7	-2	SIGNED CONSTANT
8	a	IDENTIFIER
9	n	IDENTIFIER
10	{	SPECIAL SYMBOL
11	}	SPECIAL SYMBOL
12	int	KEYWORD
13	void	KEYWORD
14	main()	IDENTIFIER
15	signed	KEYWORD
16	printf	PRE DEFINED FUNCTION

```
***** SYMBOL TABLE *****
*****
*****
```

With errors

1. Input file

(test3.c) :

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    int a=5;
```

```
    //identifier rule broken
```

```
    float 3b = 9.5;
```

```
}
```

Output :

```
shivananda@shivananda-X555LB: ~/Desktop
shivananda@shivananda-X555LB:~/Desktop$ lex lexer.l
shivananda@shivananda-X555LB:~/Desktop$ cc lex.yy.c
shivananda@shivananda-X555LB:~/Desktop$ ./a.out

#include<stdio.h>      HEADER           Line 1
void                  KEYWORD          Line 2
main()                MAIN FUNCTION   Line 2
{                     SPECIAL SYMBOL  Line 3
int                   KEYWORD          Line 4
a                     IDENTIFIER      Line 4
=                     OPERATOR        Line 4
5                     INTEGER CONSTANT Line 4
;                     SPECIAL SYMBOL  Line 4
//                    Singleline Comment Line 5
float                 KEYWORD          Line 6

***** ERROR!! UNKNOWN TOKEN 3b at Line 6 *****

=                     OPERATOR          Line 6
9.5                   FLOATING POINT CONSTANT Line 6
;                     SPECIAL SYMBOL    Line 6
}                     SPECIAL SYMBOL    Line 7

***** SYMBOL TABLE *****
SNo | Token | Token Type
-----
1 | 5 | INTEGER CONSTANT
2 | ; | SPECIAL SYMBOL
3 | = | OPERATOR
4 | a | IDENTIFIER
5 | { | SPECIAL SYMBOL
6 | } | SPECIAL SYMBOL
7 | 9.5 | FLOATING POINT CONSTANT
8 | int | KEYWORD
9 | void | KEYWORD
10 | main() | IDENTIFIER
11 | float | KEYWORD

shivananda@shivananda-X555LB:~/Desktop$
```

2. Input file

(test4.c) :

```
#include<stdio.h>
```

```
void main()
```

```
{
```

```
    int a=2;
```

```
    /*Unmatched
```

```
    /*Multiline*/
```

```
    comment*/
```

```
}
```

Output :

```
shivananda@shivananda-X555LB: ~/Desktop
shivananda@shivananda-X555LB:~/Desktop$ lex lexer.l
shivananda@shivananda-X555LB:~/Desktop$ cc lex.yy.c
shivananda@shivananda-X555LB:~/Desktop$ ./a.out

#include<stdio.h>      HEADER           Line 1
void                  KEYWORD          Line 2
main()               MAIN FUNCTION     Line 2
{                   SPECIAL SYMBOL     Line 3
{                   KEYWORD           Line 4
a                   IDENTIFIER        Line 4
=                   OPERATOR          Line 4
2                   INTEGER CONSTANT  Line 4
;                   SPECIAL SYMBOL     Line 4
/*                  Multiline Comment Start Line 5
*/                  Multiline Comment End   Line 6
comment             IDENTIFIER         Line 7
***** ERROR!! UNMATCHED MULTILINE COMMENT END */ at Line 7 *****
}                   SPECIAL SYMBOL     Line 8

***** SYMBOL TABLE *****
-----
SNo | Token | Token Type
-----
1 | 2 | INTEGER CONSTANT
2 | ; | SPECIAL SYMBOL
3 | = | OPERATOR
4 | a | IDENTIFIER
5 | { | SPECIAL SYMBOL
6 | } | SPECIAL SYMBOL
7 | int | KEYWORD
8 | void | KEYWORD
9 | main() | IDENTIFIER
10 | comment | IDENTIFIER
-----

shivananda@shivananda-X555LB:~/Desktop$
```

3. Input file

(test6.c) :

```
#include<stdio.h>
```

```
void main()
```

```
{
```


```
    int a = 8;
```

```
    float b = 9.5.7;
```

```
    //constant error
```

```
}
```

Output :



```
shivananda@shivananda-X555LB: ~/Desktop$ lex lexer.l
shivananda@shivananda-X555LB: ~/Desktop$ cc lex.yy.c
shivananda@shivananda-X555LB: ~/Desktop$ ./a.out

#include<stdio.h>      HEADER           Line 1
void                  KEYWORD          Line 2
main()                MAIN FUNCTION    Line 2
{                     SPECIAL SYMBOL   Line 3
int                   KEYWORD           Line 4
a                     IDENTIFIER       Line 4
=                     OPERATOR         Line 4
8                     INTEGER CONSTANT Line 4
;                     SPECIAL SYMBOL   Line 4
float                 KEYWORD           Line 5
b                     IDENTIFIER       Line 5
=                     OPERATOR         Line 5

***** ERROR!! CONSTANT ERROR 9.5.7 at Line 5 *****

;                     SPECIAL SYMBOL   Line 5
//                    SingleLine Comment Line 6
}                     SPECIAL SYMBOL   Line 7

***** SYMBOL TABLE *****
SNo | Token | Token Type
-----
1 | 8 | INTEGER CONSTANT
2 | ; | SPECIAL SYMBOL
3 | = | OPERATOR
4 | a | IDENTIFIER
5 | b | IDENTIFIER
6 | { | SPECIAL SYMBOL
7 | } | SPECIAL SYMBOL
8 | int | KEYWORD
9 | void | KEYWORD
10 | main() | IDENTIFIER
11 | float | KEYWORD
```