

Graphical Abstract

**Topology Optimization strategies for continuous fiber-reinforced and functionally graded anisotropic composite structures:
A brief review**

Yogesh Gandhi, Giangiacomo Minak

Highlights

**Topology Optimization strategies for continuous fiber-reinforced and functionally graded anisotropic composite structures:
A brief review**

Yogesh Gandhi, Giangiacomo Minak

- Research highlight 1

- Research highlight 2

Topology Optimization strategies for continuous fiber-reinforced and functionally graded anisotropic composite structures: A brief review

Yogesh Gandhi^{a,**}, Giangiacomo Minak^a

^aUniversity of Bologna, Department of Industrial Engineering, Forlì, 47121, Emilia-Romagna, Italy

Abstract

Among all types of Additive Manufacturing (AM) technology, Continuous Fiber Fused Filament Fabrication (CF4) can fabricate high-performance composites compared to those manufactured with conventional technologies. AM provides the excellent advantage of a very high degree of reconfigurability, which is in high demand to support the immediate short-term manufacturing chain in medical, transportation, and other industrial applications. Additionally, the CF4 capability enables the fabrication of Continuous Fiber-Reinforced Composite (CFRC) materials and Functionally GRaded Anisotropic Composite (FGRC) structures. The current expedition in AM allows us to integrate Topology Optimization (TO) strategies to design realizable FRC and GFRC structures for a given performance. Various TO strategies for attaining lightweight and high-performance designs have been proposed in the literature, which exploits AM's design freedom. Therefore, the paper attempts to address works related to TO strategies employed to obtain optimal CFRC and FGRC structures. This review intends to overview, compare existing strategies, analyze their similarities and dissimilarities, and discuss challenges and future trends in this field.

Keywords:

1. Introduction

Additive Manufacturing. The cost-effective commercially available Additive Manufacturing (AM) or 3D Printing (3DP) technologies eliminate many limitations that previously plagued the manufacturing of highly tailored structural performance for multifunctional [] and multi-physics [] applications. Moreover, the short metamorphosis of AM technologies offers unique capabilities to realize the next-generation lightweight structure have brought great application potentials in several major industries such as aerospace [1, 2], automotive [] and medical[3]. First, AM's unique ability to fabricate a highly complex shape without a substantial increase in fabrication costs, along with the benefit s of reducing manufacturing preparation time, renders these technologies worthy investment for large-scale industries. Moreover, it offers the fabrication of lattice structures-a lightweight design comparative to the solid-filled parts. Thus, offer diversification of design to answers multifunctional material requirements in weight reduction, [4], their ability to dissipate energy [5, 6], heat [7] and vibration [8]. The printed polymer parts frequently consist of carbon nanotubes and short fibre to upgrade their mechanical performance. Still, it cannot outperform [9, 10], the mechanical strength offered by continuous fibre-reinforced composite laminate manufactured using conventional manufacturing tools. Hence, the

shortcomings of 3D printed polymer composites aggravated the demand to develop Continuous Fiber Filament Fabrication (CF4) technology. CF4 technology provides a unique opportunity to reduce part distortion warping and support structures during printing, and fibre tension prevents nozzle clogging, a constant lookout with the polymer AM. Additionally, controlling the anisotropic properties of the fibre-reinforced composites can effectively distribute the loads throughout the laminate to maximize the structure's strength and stiffness. Recognizing these potentials of AM, returned a resurgent interest in utilizing the design strategies to exploit AM's performance-driven manufacturing technologies towards enhancing printed parts' overall functional performance. In contrast, to the geometric-driven or/and cost-driven manufacturing of components. The concept of performance-driven manufacturing is known as Design for Additive Manufacturing (DfAM) [11].

Topology optimization. Topology Optimization (TO), one of the DfAM methods, is an iterative design tool to optimize a quantifiable objective while being intended to sustains loads, constraints, and boundary conditions. Topology Optimization is frequently adopted to design structurally sound parts and has subsequently surpassed optimization design tools such as shape and size optimization in isolation. The seminal work of Bendsoe and Kikuchi [12] introducing the concept of TO on the homogenization method; since then, TO has been developed rapidly. TO approaches can be summarized as follows: the homogenization method [12]; the Solid Isotropic Material with Penalization (SIMP) method [13, 14], the level set method [15, 16], the Evolutionary Structural Optimization (ESO) method [17]; Topology Derivatives [? ?] and Phase

*Corresponding author

**Corresponding author

Email addresses: yogesh.gandhi@unibo.it (Yogesh Gandhi),
yogesh.gandhi@unibo.it (Yogesh Gandhi),
giangiacomo.minak@unibo.it (Giangiacomo Minak)

Field. The details of these approaches are discussed in the review papers [18, 19, 20] and some emerging TO methods for smooth boundary representation include the 'Metamorphic Development Method' (MDM) [21], and the 'Moving Morphable Method' (MMM) [22]. The general architecture of TO starts with the definition of maximizing or minimizing a single or multi-target-objective function to fulfil a set of constraints such as volume, displacement, or frequency [23]. Then, as part of an iterative process, design variables, Finite Element Analysis (FEA), sensitivity analysis, regularization, and optimization steps are repeated in this order until convergence is achieved [24]. The optimization concept applied to composite materials allows finding the optimized geometric contours of the laminate, the optimized material distribution, the optimized orientation of fiber paths, as well as optimized mapping regions for the insertion of additional layers of material aimed, for example, to increase the strength of regions with distribution of intense loads. This article is focused on the optimization of topology and fiber path orientation and thus, only related works are reviewed.

Usage. Once the package is properly installed, you can use the document class *elsarticle* to create a manuscript. Please make sure that your manuscript follows the guidelines in the Guide for Authors of the relevant journal. It is not necessary to typeset your manuscript in exactly the same way as an article, unless you are submitting to a camera-ready copy (CRC) journal.

Functionality. The Elsevier article class is based on the standard article class and supports almost all of the functionality of that class. In addition, it features commands and options to format the

- document style
- baselineskip
- front matter
- keywords and MSC codes
- theorems, definitions and proofs
- labels of enumerations
- citation style and labeling.

2. Front matter

The author names and affiliations could be formatted in two ways:

- (1) Group the authors per affiliation.
- (2) Use footnotes to indicate the affiliations.

See the front matter of this document for examples. You are recommended to conform your choice to the journal you are submitting to.

3. Bibliography styles

There are various bibliography styles available. You can select the style of your choice in the preamble of this document. These styles are Elsevier styles based on standard styles like Harvard and Vancouver. Please use BibTeX to generate your bibliography and include DOIs whenever available.

References

References

- [1] D. Kokkinis, M. Schaffner, A. R. Studart, Multimaterial magnetically assisted 3D printing of composite materials, *Nat. Commun.* 6 (2015) 1–10. doi:10.1038/ncomms9643.
- [2] L. Berrocal, R. Fernández, S. González, A. Perinián, S. Tudela, J. Vilanova, L. Rubio, J. M. Martín Márquez, J. Guerrero, F. Lasagni, Topology optimization and additive manufacturing for aerospace components, *Prog. Addit. Manuf.* 4 (2019) 83–95. doi:10.1007/s40964-018-0061-3.
- [3] A. D. Cramer, V. J. Challis, A. P. Roberts, Physically Realizable Three-Dimensional Bone Prosthesis Design With Interpolated Microstructures, *J. Biomech. Eng.* 139. doi:10.1115/1.4035481.
- [4] N. A. Fleck, V. S. Deshpande, M. F. Ashby, Micro-architected materials: past, present and future, *Proc. R. Soc. A Math. Phys. Eng. Sci.* 466 (2010) 2495–2516. doi:10.1098/rspa.2010.0215.
- [5] P. Qiao, M. Yang, F. Bobaru, Impact Mechanics and High-Energy Absorbing Materials: Review, *J. Aerosp. Eng.* 21 (2008) 235–248. doi:10.1061/(ASCE)0893-1321(2008)21:4(235).
- [6] I. Maskery, A. Hussey, A. Panesar, A. Aremu, C. Tuck, I. Ashcroft, R. Hague, An investigation into reinforced and functionally graded lattice structures, *J. Cell. Plast.* 53 (2017) 151–165. doi:10.1177/0021955X16639035.
- [7] A. O. Aremu, J. P. J. Brennan-Craddock, A. Panesar, I. A. Ashcroft, R. J. M. Hague, R. D. Wildman, C. Tuck, A voxel-based method of constructing and skinning conformal and functionally graded lattice structures suitable for additive manufacturing, *Addit. Manuf.* 13 (2017) 1–13. doi:10.1016/j.addma.2016.10.006.
- [8] L. Cheng, X. Liang, E. Belski, X. Wang, J. M. Sietins, S. Ludwick, A. To, Natural Frequency Optimization of Variable-Density Additive Manufactured Lattice Structure: Theory and Experimental Validation, *J. Manuf. Sci. Eng.* 140. doi:10.1115/1.4040622.
- [9] P. Parandoush, D. Lin, A review on additive manufacturing of polymer-fiber composites (dec 2017). doi:10.1016/j.compstruct.2017.08.088.
- [10] Y. Sano, R. Matsuzaki, M. Ueda, A. Todoroki, Y. Hirano, 3D printing of discontinuous and continuous fibre composites using stereolithography, *Addit. Manuf.* 24 (2018) 521–527. doi:10.1016/j.addma.2018.10.033.
- [11] J. Plocher, A. Panesar, Review on design and structural optimisation in additive manufacturing: Towards next-generation lightweight structures, *Mater. & Des.* 183 (2019) 108164. doi:10.1016/j.matdes.2019.108164.
- [12] M. P. Bendsøe, N. Kikuchi, Generating optimal topologies in structural design using a homogenization method, *Comput. Methods Appl. Mech. Eng.* 71 (1988) 197–224. doi:10.1016/0045-7825(88)90086-2.
- [13] M. P. Bendsøe, Optimal shape design as a material distribution problem, *Struct. Optim.* 1 (1989) 193–202. doi:10.1007/BF01650949.
- [14] G. I. N. Rozvany, M. Zhou, T. Birker, Generalized shape optimization without homogenization, *Struct. Optim.* 4 (1992) 250–252. doi:10.1007/BF01742754.
- [15] M. Y. Wang, X. Wang, D. Guo, A level set method for structural topology optimization, *Comput. Methods Appl. Mech. Eng.* 192 (2003) 227–246. doi:10.1016/S0045-7825(02)00559-5.
- [16] G. Allaire, F. Jouve, A.-M. Toader, Structural optimization using sensitivity analysis and a level-set method, *J. Comput. Phys.* 194 (2004) 363–393. doi:10.1016/j.jcp.2003.09.032.
- [17] Y. M. Xie, G. P. Steven, A simple evolutionary procedure for structural optimization, *Comput. Struct.* 49 (1993) 885–896. doi:10.1016/0045-7949(93)90035-C.

- [18] G. I. N. Rozvany, A critical review of established methods of structural topology optimization, *Struct. Multidiscip. Optim.* 37 (2009) 217–237. doi:10.1007/s00158-007-0217-0.
- 170 [19] N. P. Van Dijk, K. Maute, M. Langelaar, F. Van Keulen, Level-set methods for structural topology optimization: A review, *Struct. Multidiscip. Optim.* 48 (2013) 437–472. doi:10.1007/s00158-013-0912-y.
- [20] J. D. Deaton, R. V. Grandhi, A survey of structural and multidisciplinary continuum topology optimization: Post 2000, *Struct. Multidiscip. Optim.* 49 (2014) 1–38. doi:10.1007/s00158-013-0956-z.
- 175 [21] J. S. Liu, G. T. Parks, P. J. Clarkson, Metamorphic Development: A new topology optimization method for continuum structures, *Struct. Multidiscip. Optim.* 20 (2000) 288–300. doi:10.1007/s001580050159.
- [22] C. Liu, Z. Du, W. Zhang, Y. Zhu, X. Guo, Additive Manufacturing-Oriented Design of Graded Lattice Structures Through Explicit Topology Optimization, *J. Appl. Mech.* 84. doi:10.1115/1.4036941.
- 180 [23] H. Li, Z. Luo, M. Xiao, L. Gao, J. Gao, A new multiscale topology optimization method for multiphase composite structures of frequency response with level sets, *Comput. Methods Appl. Mech. Eng.* 356 (2019) 116–144. doi:10.1016/j.cma.2019.07.020.
- 185 [24] M. P. Bendsoe, O. Sigmund, *Topology optimization: theory, methods, and applications*, Springer Science & Business Media, 2013.