Program 2: Props in React Components (Header, Footer, App)

2. Develop a React application that demonstrates the use of props to pass data from parent component to child components. The application should include the parent component named App that serves as the central container. Create two separate child components, Header and Footer, and pass data using props.

Step-1: Create React Application

```
npx create-react-app props-app
```

Step-2: Modify App.js

```
import { useState } from 'react';
import Header from './Header';
import Footer from './Footer';
import './App.css';

export default function App() {
  const [text, setText] = useState('');

  return (
    <div className="App">
      <Header title="Welcome to My React App" />
      <h1>Dynamic Text Display</h1>
      <input
        value={text}
        onChange={(e) => setText(e.target.value)}
        placeholder="Type Something..."
      />
      <p>You typed: {text}</p>
      <Footer
        tagline="Building great apps with React"
        copyright="@2026 MyApp, All Rights Reserved"
      />
    </div>
  );
}
```

Step-3: Header.js

```
export default function Header({ title }) {
  return (
    <header>
      <h1>{title}</h1>
    </header>
  );
}
```

Step-4: Footer.js

```
export default function Footer({ tagline, copyright }) {
  return (
```

```
    <footer>
      <p>{tagline}</p>
      <p>{copyright}</p>
    </footer>
  );
}
```