



Design & Data Specification

Whhooohh Path HRMS · colours, type, tokens, stack and every database object

43 tables · 359 columns · 20 views · 67 functions · 19 enums · 10 September 2026

Read from the repository, not written from memory. Where a value here disagrees with a design file, the repository is right and the design file is stale.

Section	Source of truth in the repository
Mobile colour	mobile/src/theme.tsx — lightColors and darkColors
Mobile type and sizing	mobile/src/ui.ts, plus each screen's own StyleSheet
Module tints	mobile/src/sections.ts
Web colour	frontend/src/index.css — :root and .dark
Web type	frontend/src/index.css @theme, @fontsource/inter
Portal module colours	frontend/src/app/nav-config.ts
Stack	frontend/package.json · mobile/package.json · mobile/app.json · server/package.json
Database	neon/schema.sql merged with neon/migrations/0001-0033

1 • Colour

One green runs through the whole product, and it is the same value in every place it appears:

Token	Hex	Where it appears
 #0f4c34	#0f4c34	The app's brand and accent · the portal's --primary and --ring · the letterhead, payslip and offer-letter templates · the browser and PWA theme-colour on light
 #c0912a	#c0912a	The logo and letterhead gold — the portal's --brand-accent, used for highlights, badges and chart series

Everything below is derived from, or sits beside, those two.

1.1 Mobile — light palette

Defined once in mobile/src/theme.tsx and passed into each screen's stylesheet through useStyles(), never imported directly — a screen that closes over a colour keeps whichever theme was loaded first and never repaints.

Token	Hex	Used for
 bg	#f8fafc	The page behind every screen
 card	ffffff	Cards, list rows, sheets
 border	#e2e8f0	Hairlines, dividers, input outlines
 text	#0f172a	Body text and headings
 muted	#64748b	Secondary text, subtitles, labels
 faint	#7b8a9e	Timestamps, placeholders, inactive tab labels. Darkened from slate-400 (#94a3b8), which measured 2.56:1 on white — under the 3:1 non-body text needs
 brand	#0f4c34	Solid fills that carry white text
 accent	#0f4c34	Drawn ON a surface: active tab, link, spinner. Same as brand in light, different in dark
 onFill	ffffff	Text and icons on brand / dangerFill
 danger	#b91c1c	Destructive text and icons
 dangerFill	#dc2626	Solid red — the unread badge
 warn	#b45309	Warning text
 onFillMuted	rgba(255,255,255,0.78)	Secondary marks on a brand fill
 tickRead	#8ed8ff	Read receipt on your own message
 tickFailed	#ffb4a8	Failed-to-send mark
 chatHeader	ffffff	Conversation header
 chatHeaderText	#0f172a	Name in the conversation header
 chatHeaderMuted	#64748b	Online / last seen line
 chatGround	#ece5dd	Wallpaper behind a thread
 chatMine	#0b3d2c	Your own message bubble
 chatTheirs	ffffff	The other person's bubble
 chatOnline	#4ade80	Live presence dot
 subtle	#eef2f7	Inset panel — help text, empty states
 subtleText	#475569	Text inside a subtle panel
 successBg	#dcfce7	Approved / present pill background
 successText	#166534	Approved / present pill text

Token	Hex	Used for
 warningBg	#fef3c7	Pending / half-day pill background
 warningText	#92400e	Pending / half-day pill text
 dangerBg	#fee2e2	Rejected / absent pill background
 dangerText	#991b1b	Rejected / absent pill text

1.2 Mobile — dark palette

A re-mix, not an inversion. Surfaces match the web portal's dark theme so somebody moving between the two does not meet a different product. Status pills keep their hue and swap roles — the light fill becomes a dim tint, the dark text becomes a bright one.

Token	Hex	Used for
 bg	#0b1220	The page
 card	#111a2c	Cards and rows
 border	#1e293b	Hairlines
 text	#f1f5f9	Body text
 muted	#94a3b8	Secondary text
 faint	#64748b	Timestamps and placeholders
 brand	#15795a	Solid fill — dark enough to carry white text
 accent	#4ade80	Drawn on a surface — bright enough to read as an icon on near-black
 onFill	#ffffff	Text on a fill
 danger	#f87171	Destructive text
 dangerFill	#dc2626	Unread badge — unchanged from light
 warn	#fbbf24	Warning text
 onFillMuted	rgba(255, 255, 255, 0.78)	Unchanged — the surface behind it is the same green in both themes
 tickRead	#8ed8ff	Unchanged, for the same reason
 tickFailed	#ffb4a8	Unchanged, for the same reason
 chatHeader	#0d2a20	Conversation header
 chatHeaderText	#f1f5f9	Name in the header
 chatHeaderMuted	rgba(241, 245, 249, 0.68)	Online / last seen
 chatGround	#0b141a	Thread wallpaper — lifted off the page, not the light one darkened
 chatMine	#15795a	Your own bubble
 chatTheirs	#202c33	Their bubble
 chatOnline	#4ade80	Presence dot
 subtle	#16213a	Inset panel
 subtleText	#cbd5e1	Text in a subtle panel
 successBg	#0f3d28	Approved pill background
 successText	#86efac	Approved pill text
 warningBg	#42320c	Pending pill background
 warningText	#fcd34d	Pending pill text
 dangerBg	#4a1618	Rejected pill background
 dangerText	#fca5a5	Rejected pill text

1.3 Web portal — light tokens

CSS custom properties on :root in frontend/src/index.css, consumed by Tailwind 4 and shadcn/ui (style “new-york”, base colour slate, icon library lucide).

Token	Hex	Used for
--background	#f8fafc	Page
--foreground	#0f172a	Body text
--card	#ffffff	Card surface
--card-foreground	#0f172a	Text on a card
--popover	#ffffff	Popover / dropdown surface
--popover-foreground	#0f172a	Text in a popover
--primary	#0f4c34	Brand green — matches the letterhead, payslip and offer-letter templates
--primary-foreground	#f8fafc	Text on primary
--secondary	#12241a	Deep green surface
--secondary-foreground	#f8fafc	Text on secondary
--accent	#eaf0ec	Neutral hover tint — ghost buttons, menu items
--accent-foreground	#12241a	Text on accent
--brand-accent	#c0912a	The logo and letterhead gold — highlights, badges, chart series
--brand-accent-foreground	#12241a	Text on the gold
--muted	#f1f5f9	Muted surface
--muted-foreground	#64748b	Muted text
--success	#22c55e	Success
--success-foreground	#f8fafc	Text on success
--warning	#f59e0b	Warning
--warning-foreground	#1e293b	Text on warning
--danger	#ef4444	Danger
--destructive	#ef4444	shadcn destructive — same value as danger
--destructive-foreground	#f8fafc	Text on destructive
--border	#e2e8f0	Borders
--input	#e2e8f0	Input outlines
--ring	#0f4c34	Focus ring

1.4 Web portal — dark tokens

On .dark, applied by next-themes. The mobile app writes this same key into the WebView's storage so the Portal tab matches the app rather than the browser.

Token	Hex	Used for
--background	#0b1220	Page
--foreground	#f1f5f9	Body text
--card	#111a2c	Card surface
--card-foreground	#f1f5f9	Text on a card
--popover	#111a2c	Popover surface
--popover-foreground	#f1f5f9	Text in a popover

Token	Hex	Used for
--primary	#1f7a54	Brand green, lifted for dark
--primary-foreground	#0b1220	Text on primary
--secondary	#16281c	Deep green surface
--secondary-foreground	#f1f5f9	Text on secondary
--accent	#1b2e22	Hover tint
--accent-foreground	#f1f5f9	Text on accent
--brand-accent	#d9ac55	Gold, lifted for dark
--brand-accent-foreground	#0b1220	Text on the gold
--muted	#1e293b	Muted surface
--muted-foreground	#94a3b8	Muted text
--success	#22c55e	Success — unchanged
--success-foreground	#0b1220	Text on success
--warning	#f59e0b	Warning — unchanged
--warning-foreground	#0b1220	Text on warning
--danger	#ef4444	Danger — unchanged
--destructive	#ef4444	Destructive — unchanged
--destructive-foreground	#f1f5f9	Text on destructive
--border	#1e293b	Borders
--input	#1e293b	Input outlines
--ring	#1f7a54	Focus ring

1.5 Module tints — mobile

One tint per module, set in mobile/src/sections.ts. The tile icon on the Modules grid is drawn in it.

Token	Hex	Module and its icon
people	#6366f1	People — people-outline
tasks	#0ea5e9	Tasks — checkmark-done-outline
leaves	#f59e0b	Leaves — airplane-outline
payslips	#16a34a	Payslips — wallet-outline
projects	#8b5cf6	Projects — folder-open-outline
attendance	#0284c7	Attendance — time-outline
reporting	#6366f1	Reporting Hierarchy — git-network-outline
assets	#06b6d4	Assets — laptop-outline
policies	#64748b	Policies — document-text-outline
letters	#d97706	HR Letters — ribbon-outline
calendar	#f43f5e	Calendar — calendar-outline
announcements	#f97316	Announcements — megaphone-outline

1.6 Module colours — web portal

Set in frontend/src/app/nav-config.ts. Sixteen modules, each with its own colour and animation.

	Token	Hex	Used for
	Dashboard	#5A9AA8	
	Employees	#818cf8	
	Attendance	#38bdf8	
	Leaves	#fbbf24	
	Projects	#a78bfa	
	Tasks	#34d399	
	Payroll	#22c55e	
	Company Bank Details	#0ea5e9	
	Assets	#22d3ee	
	Recruitment	#f472b6	
	Documents	#60a5fa	
	Calendar	#fb7185	
	Announcements	#fb923c	
	Messages	#2dd4bf	
	Reports	#c084fc	
	Settings	#94a3b8	

1.7 Platform colours

	Token	Hex	Used for
	theme-color (light)	#0f4c34	Browser and PWA chrome — index.html
	theme-color (dark)	#0b1220	Browser and PWA chrome — index.html
	adaptiveIcon background	#ffffff	Android launcher icon — app.json
	splash background	#ffffff	Splash screen, light and dark — app.json

2.1 Font families

Where	Family	Weights	Loaded how
Web portal	Inter, then ui-sans-serif, system-ui, sans-serif	400 · 500 · 600 · 700	@fontsource/inter, imported in index.css — self-hosted, no Google Fonts call
Mobile app	The platform's own UI font — Roboto on Android, SF Pro on iOS	500 · 600 · 700	No custom font is bundled; React Native's default is used
Mobile icons	Ionicons, via @expo/vector-icons	—	Bundled with the app
Web icons	lucide-react	—	Bundled with the build
Documents	Segoe UI Semibold (headings), Calibri (body), Consolas (code)	—	This document set only, not the product

The web sets `--font-sans` in an `@theme` inline block, so every Tailwind class resolves to Inter. The app deliberately does not bundle a font: the platform face is already on the device, renders faster, and is what people are used to reading on that phone.

2.2 How mobile sizes work

Every size in the app is written as `scale(n)`, never as a raw number. Two different problems are being solved and both must be, or the app is wrong somewhere:

Mechanism	Value	What it does
scale(n)	baseline 375pt	Sizes against the width most designs are drawn at. A 5" phone and a 7" one differ by about 40% in width, and a layout tuned for one is cramped or sparse on the other.
clamp	320 – 480 px	Below 320 the result is unreadable; above 480 — tablets and foldables — everything would simply inflate instead of getting the extra room it should. Past that width the layout breathes rather than zooms.
FONT_SCALE_CAP	1.25	How far the phone's own text-size setting may enlarge our text. Passed as <code>maxFontSizeMultiplier</code> on every <code>Text</code> — not <code>allowFontScaling</code> , which would ignore the setting outright. A phone set to "large" would otherwise render a 24pt title at 33pt.
ANDROID_STATUS_BAR	<code>StatusBar.currentHeight</code> ?? 24	Fallback only. Screens read real insets from <code>react-native-safe-area-context</code> , because React Native's own <code>SafeAreaView</code> does nothing on Android.

So a size written as `scale(14)` renders at 14pt on a 375pt-wide phone, about 12pt on a 320pt phone, and about 18pt on a 480pt one — then multiplied by the user's text-size setting, up to 1.25×

2.3 The mobile size ladder

Every size actually in use, and what carries it. Sizes are the `scale(n)` argument.

Size	Weight	Used for
24	700	Screen title on the sign-in and letter screens; the profile avatar's initials

Size	Weight	Used for
22	700	Section heading; module list title; the chevron on a row
21	700	The number on a Home counter tile — leaves pending, open tasks
20	700 / 600	Home greeting; a person's name in a conversation header; a clock time
19	700	The in / out time on the attendance card
18	700	Screen bar title; compact heading
17	700	Bottom-sheet title
16	700 / 600	Primary and secondary button text; company name; modal title; Sign out
15	700 / 600	Back label; menu label; a person's name in a list; Confirm punch; error text; text inputs
14	700 / 600 / regular	Row title; field value; message bubble text; the search box; document title; punch state; Forgot password
13	600 / regular	Field label; email; section label; empty-state text; paragraph text in a letter; help and error text
12	700 / 600 / regular	Card label; detail label and value; chip text; hints; notice body; camera hints
11	700 / 600 / regular	Quick-action label; module grid label; counter tile label; timestamps; notes; company address
10	700 / 600	Tab bar label; status badge text; letter reference and stamp
9	700	The unread count inside the tab badge

Three weights only — 500, 600 and 700. There is no 400 declaration anywhere: unweighted text uses the platform default.

2.4 Web type

Item	Value	Note
Type scale	Tailwind 4 defaults	text-xs 0.75rem · text-sm 0.875rem · text-base 1rem · text-lg 1.125rem · text-xl 1.25rem · text-2xl 1.5rem, and up
Form controls	max(16px, 1rem)	Set explicitly in index.css. Below 16px, iOS Safari zooms the page when a field is focused — this is the fix, not a preference
Radius	--radius: 0.25rem	4px. Every shadcn component derives its corners from this one value
Viewport	width=device-width, viewport-fit=cover, maximum-scale=5.0	cover lets the app paint under the notch; index.css pays it back with safe-area padding

2.5 Mobile corner radii

All written as scale(n). The values in use, by frequency:

Radius	Count	Used for
10	17	The standard card and list-row corner

Radius	Count	Used for
12	8	Larger cards and sheets
14	7	Punch card, module tiles
16 · 15 · 11	6	Buttons and inset panels
20 – 26	8	Pills, avatars, floating buttons
4 – 9	8	Badges, chips, small marks
34 · 36	2	Large circular controls
100 · 999	3	Fully round — the role pill, the presence dot, the avatar

3 · What the frontend is built with

3.1 Web portal — runtime dependencies

Package	Version	What it does
react · react-dom	^19.2.7	The framework
vite	^8.1.1	Build and dev server
typescript	~6.0.2	Types
tailwindcss · @tailwindcss/vite	^4.3.3	Styling. Tokens come from index.css, not a config file
radix-ui · @radix-ui/react-*	1.x	Accessible primitives behind shadcn/ui — avatar, checkbox, dialog, dropdown-menu, label, popover, select, separator, slot, tabs, toast, tooltip
class-variance-authority	^0.7.1	Component variants
clsx · tailwind-merge	^2.1.1 · ^3.6.0	Conditional and conflicting class handling
tw-animate-css	^1.4.0	Animation utilities
lucide-react	^1.27.0	Icons
@fontsource/inter	^5.3.0	Self-hosted Inter, weights 400–700
next-themes	^0.4.6	Light / dark switching
@tanstack/react-query	^5.101.4	Server state, caching and refetching
react-router-dom	^7.18.1	Routing
react-hook-form · @hookform/resolvers	^7.83.0 · ^5.5.7	Forms
zod	^4.4.3	Schema validation, shared between form and API call
recharts	^3.10.1	Charts on the dashboard and reports
date-fns	^4.4.0	Dates
sonner	^2.0.7	Toasts
cmdk	^1.1.1	Command palette
jspdf · html2canvas	^4.2.1 · ^1.4.1	Client-side PDF export — payslips and letters
@simplewebauthn/browser	^13.3.0	Passkey sign-in in the browser

Build tooling: @vitejs/plugin-react 6, postcss 8, autoprefixer 10, oxlint 1.71.

3.2 Mobile app

Package	Version	What it does
expo	~57.0.21	The SDK

Package	Version	What it does
react-native	0.86.3	The framework
react	19.2.3	Same major as the web
typescript	~6.0.3	Types
@expo/vector-icons	^15.0.3	Ionicons
@noble/ed25519 · @noble/hashes	^2.2.3 · ^2.4.0	The device key pair for biometric attendance
expo-secure-store	~57.0.3	The session token and the private key, in the OS keystore
expo-local-authentication	~57.0.2	Fingerprint and Face ID
expo-camera	~57.0.4	The check-in selfie
expo-location	~57.0.16	The login place on a punch
expo-image-picker · expo-media-library	~57.0.16 · ~57.0.4	Attachments and saving
expo-document-picker · expo-file-system	~57.0.1 · ~57.0.6	Files
expo-print · expo-sharing	~57.0.1 · ~57.0.18	Letter and payslip output
expo-audio	~57.0.4	Voice notes in messaging
expo-crypto	~57.0.2	Random values
expo-constants	~57.0.17	Reads apiUrl from app.json
expo-splash-screen · expo-status-bar · expo-font · expo-asset	~57.x	Shell
react-native-webview	13.16.1	The Portal tab
react-native-safe-area-context	~5.7.0	Real insets — notch and gesture bar
react-native-svg	15.15.4	The logo mark

3.3 App identity and permissions

Setting	Value
Name	Whhoohh Path HRMS
Bundle / package	com.whhoohhpath.hrms (Android and iOS)
Version	1.0.0
Orientation	portrait
Interface style	automatic — follows the phone unless the app is set to light or dark
Scheme	hrms://

Setting	Value
Tablet	Supported on iOS
Android permissions	CAMERA · USE_BIOMETRIC · USE_FINGERPRINT · RECORD_AUDIO · ACCESS_COARSE_LOCATION · ACCESS_FINE_LOCATION
iOS usage strings	NSFaceIDUsageDescription · NSCameraUsageDescription — written in plain language, because the phone shows them verbatim

3.4 API layer

Package	Version	What it does
express	^5.1.0	The HTTP layer
pg	^8.13.1	PostgreSQL client, pooled at max 10
jsonwebtoken	^9.0.2	Session tokens — 8 h TTL in production
@simplewebauthn/server	^13.3.3	Passkey verification
nodemailer	^9.1.1	SMTP, per tenant
cors	^2.8.5	Browser origin control
Node	>=20, deployed on 22	Runtime

4 • The database

PostgreSQL on Neon. The API connects as the `hrms_app` role and never as the table owner — Postgres exempts owners from row-level security, and connecting as one would silently disable every tenant policy in the system.

Object	Count
Tables	43
Columns	359
Views (the read models the app queries)	20
Functions (every write and every report)	67
Enumerated types	19
Row-level security policies	118
Migrations	0001 – 0033

Nothing in the app reads a table directly where a view exists for it, and nothing writes to a table at all — every write goes through a `SECURITY DEFINER` function that re-checks the caller.

4.1 Enumerated types

`gender_enum` `male` · `female` · `other`

`employee_status_enum` `active` · `inactive` · `on_notice` · `exited`

`attendance_status_enum` `present` · `absent` · `half_day` · `on_leave`

`leave_status_enum` `pending` · `approved` · `rejected`

`priority_enum` `low` · `medium` · `high`

`project_status_enum` `planning` · `active` · `on_hold` · `completed`

`task_status_enum` `assigned` · `in_progress` · `review` · `completed`

`asset_category_enum` `laptop` · `monitor` · `keyboard` · `mouse` · `mobile` · `accessory` · `other`

`asset_status_enum` `available` · `assigned` · `retired` · `maintenance`

`candidate_status_enum` `applied` · `interview_scheduled` · `interviewed` · `offered` · `joined` · `rejected`

`interview_outcome_enum` `pending` · `pass` · `fail`

`letter_type_enum` `offer` · `appointment` · `experience` · `relieving` · `certificate` · `joining` · `internship` · `promotion` · `appraisal` · `confirmation` · `warning` · `termination`

`announcement_category_enum` `news` · `holiday` · `event` · `general`

`event_type_enum` `meeting` · `event` · `holiday`

`company_status_enum` `trial` · `active` · `suspended` · `inactive`

`onboarding_status_enum` `new` · `setup_in_progress` · `configuration` · `ready` · `active`

`billing_cycle_enum` `monthly` · `quarterly` · `annual`

`subscription_status_enum` `trialing` · `active` · `past_due` · `cancelled` · `expired`

`service_status_enum` `requested` · `scheduled` · `in_progress` · `completed` · `cancelled`

4.2 Views — what the app reads

The API's read endpoint can only name a view on this list. An unknown name never reaches Postgres.

<code>announcement_detail</code>	<code>asset_assignment_detail</code>	<code>asset_detail</code>
<code>attendance_detail</code>	<code>audit_log_detail</code>	<code>candidate_directory</code>
<code>company_event_detail</code>	<code>employee_directory</code>	<code>generated_letter_detail</code>

interview_detail	leave_balance_detail	leave_request_detail
message_detail	payslip_detail	policy_detail
project_directory	project_member_detail	salary_structure_detail
task_comment_detail	task_directory	

4.3 Functions — what the app calls

Every write, every report and every operation that spans tables. Each one re-checks the caller before it does anything.

advance_candidate_on_interview	app_company_id	app_employee_id
app_is_founder	app_is_hr	app_is_super_admin
app_manages_projects	app_manages_tasks	app_module_enabled
app_role	app_user_id	apply_leave
assert_password_policy	assign_asset	attendance_check_in
attendance_check_in_verified	attendance_check_out	attendance_check_out_verified
attendance_summary	bump_policy_version	change_own_password
compute_payslip	consume_password_reset	create_employee_profile
create_employee_with_login	create_password_reset	current_user_profile
deactivate_employee	decide_leave_request	generate_letter
generate_payslip	generate_payslips_bulk	get_calendar
get_company_email_settings	get_company_smtp_transport	get_email_branding
get_employee_detail	get_letter_view	letter_payload
log_email_attempt	log_security_event	mark_email_result
message_contacts	message_threads	messages_guard_amend
next_employee_code	payroll_summary	presence_for
presence_window	report_attendance	report_employees
report_leaves	report_projects	report_reporting_manager
report_tasks	return_asset	set_employee_password
set_employee_role	set_own_password	set_updated_at
sync_task_progress	touch_presence	update_task
upgrade_password_hash	upsert_company_email_settings	upsert_company_settings
user_display_name		

4.4 Every table, every column

Types and defaults exactly as declared. A column marked with a migration number was added after the base schema was written.

roles 3 columns · 1 row-level policy

id	serial primary key
name	varchar(50) not null unique
description	varchar(255)

permissions 3 columns · 1 row-level policy

id	serial primary key
code	varchar(100) not null unique
description	varchar(255)

role_permissions 2 columns · 1 row-level policy

role_id	integer not null references roles (id) on delete cascade
permission_id	integer not null references permissions (id) on delete cascade
constraint	primary key (role_id, permission_id)

users 8 columns · 4 row-level policies

id	serial primary key
auth_id	uuid unique
email	varchar(255) not null
role_id	integer not null references roles (id)
is_active	boolean not null default true
created_at	timestampz not null default now()
updated_at	timestampz not null default now()
last_seen_at	timestampz [0033]

departments 3 columns · 4 row-level policies

id	serial primary key
name	varchar(100) not null unique
description	varchar(255)

designations 3 columns · 4 row-level policies

id	serial primary key
title	varchar(100) not null unique
description	varchar(255)

employees 25 columns · 4 row-level policies

id	serial primary key
user_id	integer not null unique references users (id) on delete cascade
employee_code	varchar(20) not null
first_name	varchar(100) not null
and	last_name varchar(100) not null default ''
offer	letter and directory row. full_name varchar(201) generated always as (trim(first_name ' ' last_name)) stored
phone	varchar(20)

address	varchar(500)
dob	date
gender	gender_enum
department_id	integer references departments (id) on delete set null
designation_id	integer references designations (id) on delete set null
reporting_manager_id	integer references employees (id) on delete set null
joining_date	date
skills	varchar[]
experience_years	integer
photo_url	varchar(500)
pan_number	varchar(10)
aadhaar_number	varchar(12)
bank_account_number	varchar(30)
bank_ifsc	varchar(11)
bank_name	varchar(100)
status	employee_status_enum not null default 'active'
created_at	timestampz not null default now()
updated_at	timestampz not null default now()

attendance_records 18 columns · 2 row-level policies

id	serial primary key
employee_id	integer not null references employees (id) on delete cascade
date	date not null
check_in	timestampz
check_out	timestampz
break_minutes	integer not null default 0
status	attendance_status_enum not null default 'present'
created_at	timestampz not null default now()
<i>constraint</i>	constraint uq_attendance_employee_date unique (employee_id, date)
check_in_method	public.attendance_method_enum not null default 'manual' [0014]
check_in_latitude	numeric(9, 6) [0032]
check_out_method	public.attendance_method_enum not null default 'manual' [0014]
check_out_photo_id	uuid references public.files(id) on delete set null [0014]
check_in_longitude	numeric(9, 6) [0032]
check_in_accuracy_m	numeric(7, 1) [0032]
check_out_latitude	numeric(9, 6) [0032]
check_out_longitude	numeric(9, 6) [0032]
check_out_accuracy_m	numeric(7, 1) [0032]
check_in_photo_id	uuid references public.files(id) on delete set null [0014]

leave_types 3 columns · 4 row-level policies

id	serial primary key
name	varchar(50) not null unique
default_days_per_year	integer not null default 0

leave_balances 6 columns · 4 row-level policies

id	serial primary key
employee_id	integer not null references employees (id) on delete cascade

leave_type_id	integer not null references leave_types (id) on delete cascade
year	integer not null
allocated_days	numeric(4, 1) not null
used_days	numeric(4, 1) not null default 0
constraint	constraint uq_leave_balance_employee_type_year unique (employee_id, leave_type_id, year)

leave_requests 12 columns · 4 row-level policies

id	serial primary key
employee_id	integer not null references employees (id) on delete cascade
leave_type_id	integer not null references leave_types (id)
start_date	date not null
end_date	date not null
days_count	numeric(4, 1) not null
reason	varchar(500)
status	leave_status_enum not null default 'pending'
decided_by	integer references users (id) on delete set null
decided_at	timestamptz
created_at	timestamptz not null default now()
decision_note	varchar(500) [0026]

projects 11 columns · 4 row-level policies

id	serial primary key
name	varchar(200) not null
description	varchar(2000)
tech_stack	varchar[]
priority	priority_enum not null default 'medium'
status	project_status_enum not null default 'planning'
deadline	date
progress	integer not null default 0
created_by	integer not null references users (id)
created_at	timestamptz not null default now()
updated_at	timestamptz not null default now()

project_members 3 columns · 4 row-level policies

project_id	integer not null references projects (id) on delete cascade
employee_id	integer not null references employees (id) on delete cascade
role_in_project	varchar(100)
constraint	primary key (project_id, employee_id)

tasks 20 columns · 6 row-level policies

id	serial primary key
project_id	integer references projects (id) on delete set null
title	varchar(200) not null
description	varchar(2000)
assigned_to	integer references employees (id) on delete set null
priority	priority_enum not null default 'medium'
due_date	date

status	task_status_enum not null default 'assigned'
progress	integer not null default 0
created_by	integer not null references users (id)
created_at	timestampz not null default now()
updated_at	timestampz not null default now()
is_active	boolean not null default true [0029]
project_stage	varchar(50) not null default 'Todo' [0029]
start_date	date [0029]
end_date	date [0029]
task_file_url	text [0029]
task_file_name	text [0029]
task_managers	integer[] default '{} [0029]
task_members	integer[] default '{} [0029]

task_checklist_items 5 columns · 4 row-level policies

id	serial primary key
task_id	integer not null references tasks (id) on delete cascade
label	varchar(300) not null
is_done	boolean not null default false
created_at	timestampz not null default now()

task_comments 5 columns · 4 row-level policies

id	serial primary key
task_id	integer not null references tasks (id) on delete cascade
user_id	integer not null references users (id) on delete cascade
body	varchar(2000) not null
created_at	timestampz not null default now()

assets 8 columns · 4 row-level policies

id	serial primary key
name	varchar(200) not null
category	asset_category_enum not null
serial_number	varchar(100) unique
purchase_date	date
status	asset_status_enum not null default 'available'
notes	varchar(1000)
created_at	timestampz not null default now()

asset_assignments 6 columns · 2 row-level policies

id	serial primary key
asset_id	integer not null references assets (id) on delete cascade
employee_id	integer not null references employees (id) on delete cascade
assigned_date	date not null
returned_date	date
notes	varchar(500)

candidates 9 columns · 2 row-level policies

id	serial primary key
----	--------------------

full_name	varchar(200) not null
email	varchar(255) not null
phone	varchar(20)
applied_designation_id	integer references designations (id) on delete set null
status	candidate_status_enum not null default 'applied'
source	varchar(100)
notes	varchar(2000)
created_at	timestamp tz not null default now()

interviews 6 columns · 2 row-level policies

id	serial primary key
candidate_id	integer not null references candidates (id) on delete cascade
scheduled_at	timestamp tz not null
interviewer_id	integer references employees (id) on delete set null
notes	varchar(2000)
outcome	interview_outcome_enum not null default 'pending'

salary_structures 9 columns · 4 row-level policies

id	serial primary key
employee_id	integer not null unique references employees (id) on delete cascade
basic	numeric(10, 2) not null
hra	numeric(10, 2) not null default 0
special_allowance	numeric(10, 2) not null default 0
pf_percent	numeric(5, 2) not null default 12
esi_percent	numeric(5, 2) not null default 0.75
effective_from	date not null
created_at	timestamp tz not null default now()

payslips 14 columns · 2 row-level policies

id	serial primary key
employee_id	integer not null references employees (id) on delete cascade
month	integer not null
year	integer not null
basic	numeric(10, 2) not null
hra	numeric(10, 2) not null
special_allowance	numeric(10, 2) not null
gross_pay	numeric(10, 2) not null
pf_deduction	numeric(10, 2) not null
esi_deduction	numeric(10, 2) not null
professional_tax	numeric(10, 2) not null
net_pay	numeric(10, 2) not null
generated_at	timestamp tz not null default now()
generated_by	integer not null references users (id)
constraint	constraint uq_payslip_employee_month_year unique (employee_id, month, year)

policies 6 columns · 4 row-level policies

id	serial primary key
title	varchar(200) not null

content	text not null
version	integer not null default 1
updated_by	integer not null references users (id)
updated_at	timestampz not null default now()

generated_letters 9 columns · 2 row-level policies

id	serial primary key
employee_id	integer not null references employees (id) on delete cascade
letter_type	letter_type_enum not null
custom_message	text
annual_ctc_override	numeric(12, 2)
probation_text	varchar(200)
notice_period_text	varchar(200)
generated_by	integer not null references users (id)
generated_at	timestampz not null default now()

announcements 7 columns · 4 row-level policies

id	serial primary key
title	varchar(200) not null
body	text not null
category	announcement_category_enum not null default 'general'
pinned	boolean not null default false
created_by	integer not null references users (id)
created_at	timestampz not null default now()

company_events 7 columns · 4 row-level policies

id	serial primary key
title	varchar(200) not null
description	varchar(1000)
event_date	date not null
event_type	event_type_enum not null default 'event'
created_by	integer not null references users (id)
created_at	timestampz not null default now()

company_settings 5 columns · 4 row-level policies

id	serial primary key
company_name	varchar(200) not null
address	varchar(500)
logo_url	varchar(500)
updated_at	timestampz not null default now()

audit_logs 7 columns · 4 row-level policies

id	serial primary key
user_id	integer references users (id) on delete set null
action	varchar(100) not null
entity	varchar(100) not null
entity_id	integer
meta	jsonb

created_at	timestampz not null default now()
------------	-----------------------------------

companies 19 columns · 2 row-level policies

id	serial primary key
name	varchar(200) not null
code	varchar(20) not null
email	varchar(255)
phone	varchar(20)
website	varchar(255)
address	varchar(500)
city	varchar(100)
state	varchar(100)
country	varchar(100)
logo_url	varchar(500)
industry	varchar(100)
company_size	varchar(50)
status	company_status_enum not null default 'trial'
onboarding_status	onboarding_status_enum not null default 'new'
denormalised	from the active subscription so employee_limit integer
notes	text
created_at	timestampz not null default now()
updated_at	timestampz not null default now()

company_modules 5 columns · 2 row-level policies

id	serial primary key
company_id	integer not null references companies (id) on delete cascade
so	the sidebar and module varchar(50) not null
is_enabled	boolean not null default true
updated_at	timestampz not null default now()
constraint	constraint uq_company_module unique (company_id, module)

subscription_plans 10 columns · 2 row-level policies

id	serial primary key
name	varchar(100) not null unique
description	varchar(500)
employee_limit	integer
storage_mb	integer
price_amount	numeric(10, 2)
price_currency	varchar(3) not null default 'INR'
so	a plan change never default_modules varchar[] not null default '{}'
is_active	boolean not null default true
created_at	timestampz not null default now()

company_subscriptions 10 columns · 2 row-level policies

id	serial primary key
company_id	integer not null references companies (id) on delete cascade
plan_id	integer not null references subscription_plans (id)
status	subscription_status_enum not null default 'trialing'

billing_cycle	billing_cycle_enum not null default 'monthly'
start_date	date not null
end_date	date
employee_limit	integer
created_at	timestampz not null default now()
updated_at	timestampz not null default now()

platform_services 5 columns · 2 row-level policies

id	serial primary key
name	varchar(150) not null unique
description	varchar(500)
is_active	boolean not null default true
created_at	timestampz not null default now()

company_services 10 columns · 2 row-level policies

id	serial primary key
company_id	integer not null references companies (id) on delete cascade
service_id	integer not null references platform_services (id)
status	service_status_enum not null default 'requested'
assigned_date	date
due_date	date
which	after 0011 assigned_to integer references users (id) on delete set null
notes	text
created_at	timestampz not null default now()
updated_at	timestampz not null default now()

support_sessions 7 columns · 2 row-level policies

id	serial primary key
super_admin_user_id	integer not null references users (id) on delete cascade
company_id	integer not null references companies (id) on delete cascade
reason	varchar(500)
started_at	timestampz not null default now()
ended_at	timestampz
ip_address	inet

files 8 columns · 4 row-level policies

id	uuid primary key default gen_random_uuid()
company_id	integer not null references companies (id) on delete cascade
path	varchar(500) not null
mime_type	varchar(100) not null
size_bytes	integer not null
data	bytea not null
uploaded_by	integer references users (id) on delete set null
created_at	timestampz not null default now()
constraint	constraint uq_files_company_path unique (company_id, path)

webauthn_credentials 11 columns · 1 row-level policy

id	serial primary key
----	--------------------

user_id	integer not null references public.users(id) on delete cascade
base64url	as the browser
and	a replay from another account has nowhere to land. credential_id text not null unique
public_key	bytea not null
so	it is checked and stored counter bigint not null default 0
so	someone can transports text
device_label	text
created_at	timestampz not null default now()
last_used_at	timestampz
company_id	integer not null references public.companies(id) on delete cascade

mobile_device_credentials 6 columns · 1 row-level policy

id	serial primary key
user_id	integer not null references public.users(id) on delete cascade
label	text
created_at	timestampz not null default now()
last_used_at	timestampz
company_id	integer not null references public.companies(id) on delete cascade

messages 9 columns · 4 row-level policies

id	serial primary key
company_id	integer not null references public.companies(id) on delete cascade
sender_id	integer not null references public.users(id) on delete cascade
recipient_id	integer not null references public.users(id) on delete cascade
body	varchar(2000) not null
which	is what the badge read_at timestampz
created_at	timestampz not null default now()
<i>constraint</i>	constraint messages_not_to_self check (sender_id <> recipient_id)
<i>constraint</i>	constraint messages_body_not_blank check (btrim(body) <> '')
edited_at	timestampz [0030]
deleted_at	timestampz [0030]

email_logs 12 columns · 1 row-level policy

id	serial primary key
or	a password reset for someone whose company is not yet known. company_id integer references public.companies(id) on delete cascade
recipient	varchar(320) not null
sender	varchar(320) not null
subject	varchar(500) not null
template	varchar(64)
status	varchar(16) not null default 'queued'
provider_message_id	varchar(255)
error_code	varchar(64)
not	a error_message varchar(1000)
created_at	timestampz not null default now()
sent_at	timestampz
<i>constraint</i>	constraint email_logs_status check (status in ('queued', 'sending', 'sent', 'failed'))

password_reset_tokens 7 columns · no policy

id	serial primary key
user_id	integer not null references public.users(id) on delete cascade
token_hash	varchar(64) not null unique
expires_at	timestampz not null
used_at	timestampz
created_at	timestampz not null default now()
requested_ip	varchar(64)

company_email_settings 12 columns · no policy

company_id	integer primary key references public.companies(id) on delete cascade
host	varchar(255) not null
port	integer not null default 587
secure	boolean not null default false
username	varchar(255)
password_ciphertext	text
from_email	varchar(320) not null
from_name	varchar(120)
reply_to	varchar(320)
enabled	boolean not null default false
updated_at	timestampz not null default now()
updated_by	integer references public.users(id)
<i>constraint</i>	constraint company_email_settings_port check (port between 1 and 65535)

message_edits 5 columns · no policy

id	serial primary key
message_id	integer not null references public.messages(id) on delete cascade
previous_body	varchar(2000) not null
edited_by	integer not null references public.users(id)
edited_at	timestampz not null default now()