BULK INDEPENDENCE [9374002]

M/E L.O. SETTLING TANK [-]

Manufactu Port Lande Fuel Grade	ed : Nethe	APPLICABLE rlands		Model Volume[ltr] Dispatched	: N.A. : : 02-Oct-23
Recommer		90 6 CO		Received	: 05-Oct-23
		Sample Details	1 (Current)	2	3
		Rating	Normal		
Sample No Bottle No		Sample No	23098209		
		Bottle No	50333166		
		Sampled Date	26-Sep-23		
		Oil Grade In Use	NAVIGO 6 CO		
		Unit Service Hrs	75148		
		Oil Service Hrs	Not Stated		
		Daily Makeup[ltr]	Not Stated		
New Oil	Alert Value.	Analysis	ı	1	1
		Appearance	Dark		
100		KV@40°C[mm²/s]	118.9		
11.5	<9.3 or>15.5*	KV@100°C[mm²/s]	12.61		
6	<2 or>30*	BN[mgKOH/g]	8.9		
_	<170*	Flash Point[°C]	>200		
	>1.2*	Soot/Insoluble[%wt]	0.20		
	>0.5*	Water[%wt]	0.20		
	70.5	PQ Index/2ml	<10		
			10		
		Wear Elemental [ppm]	1_	1	I
	>100*	Aluminium (AI)	2		
	>50*	Chromium (Cr)	<1		
	>100*	Copper (Cu)	4		
	>200*	Iron (Fe)	14		
	>100*	Lead (Pb)	<1		
	>100*	Tin (Sn)	<1		
		Contaminant Elemental	[ppm]		
		Boron (B)	6		
	>250*	Sodium (Na)	22		
	>100*	Silicon (Si)	7		
		Molybdenum (Mo)	<1		
		Nickel (Ni)	3		
		Silver (Ag)	<1		
		Vanadium (V)	3		
		Additive Elements [ppn	n]	1	1
		Calcium (Ca)	3524		
		Phosphorus (P)	466		
		Zinc (Zn)	528		
		Magnesium (Mg)	17		
		magnesiani (wg)	· ·		

Oil Rating:	
The oil is fit for further use provided the landed used oil sample is representative for the application.	
The on is it for farther use provided the landed used on sample is representative for the application.	
Unit Rating:	
Wear rate is normal; no abnormalities are evident.	
wear rate is normal, no aprioring lines are evident.	
Astronomy	
Action:	
No action required.	

Dated: 12-Mar-2024

Alert Value Support

:* Indicate Oil supplier/operator critical limits. : technical @lukoil.com