

```

> Frame 3656: 60 bytes on wire (480 bits),
Ethernet II, Src: Cisco_36:86:17 (3c:8b:7f:36:86:17)
  > Destination: IPv4mcast_01 (01:00:5e:00:00:01)
  > Source: Cisco_36:86:17 (3c:8b:7f:36:86:17)
    Type: IPv4 (0x0800)
    Padding: 000000000000000000000000
  > Internet Protocol Version 4, Src: 172.18.98.218,
  > Internet Control Message Protocol
    Type: 9 (Mobile IP Advertisement)
    Code: 0 (Normal router advertisement)
    Checksum: 0xe008 [correct]
    [Checksum Status: Good]
    Number of addresses: 1
    Address entry size: 2
    Lifetime: 1800 (30 minutes)
    Router address: 172.18.98.218
    Preference level: 0

```

0000	01 00 5e 00 00 01 3c 8b 7f 36 86 17 08 00 45 e0	..^...<-6....E-
0010	00 24 ed 64 00 00 01 01 dc a6 ac 12 62 da e0 00	-\$d....b...
0020	00 01 09 00 e0 08 01 02 07 08 ac 12 62 da 00 00b...
0030	00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00