

## Unit II

### Text Data Analysis

Reading unstructured data – representing text data – Part of speech tagging – Syntactic representation – Text similarity – WorldNet based similarity – Shallow parsing – Semantic representation.


**Objectives:** To Understand the text data processing technologies for processing text data.

### Text Data Analysis

#### Definition

- **Text Data Analysis:** The process of **examining and processing** text data to **extract meaningful insights and information**.
- It involves **techniques** from linguistics, computer science, and statistics to analyze textual content.

### Reading Unstructured Data in Text Data Analysis



**Fig 1.1.** Representing the process of reading unstructured data in text data analysis for NLP. It includes steps such as Data Collection, Data Preprocessing, Tokenization, Stop Word Removal, Stemming/Lemmatization, Feature Extraction, and Model Training, with arrows indicating the flow from one step to the next.

#### 1. Unstructured Data

- **Definition:** Unstructured data refers to information that does not have a predefined data model or is not organized in a predefined manner.
- **Examples:** Text documents, emails, social media posts, audio files, video files, and web pages.

#### 2. Importance in Text Data Analysis

- **Volume:** Majority of data generated today is unstructured.
- **Insights:** Contains valuable insights that structured data might miss.
- **Applications:** Sentiment analysis, topic modeling, text classification, and information retrieval.

#### 3. Challenges of Unstructured Data

##### a. Ambiguity and Contextual Understanding

- **Problem:** Resolving ambiguity and understanding contextually dependent meanings.

- **Example:** Differentiating between "bank" as a financial institution or a riverbank based on surrounding text.

#### b. Named Entity Recognition (NER)

- **Problem:** Identifying and categorizing entities (names, locations, organizations) in text.
- **Example:** Extracting "Apple" as a company name in the sentence "Apple announced new products."

#### c. Sentiment Analysis

- **Problem:** Determining the sentiment (positive, negative, neutral) expressed in text accurately.
- **Example:** Analyzing customer reviews to determine overall satisfaction levels.

#### d. Text Pre-processing Challenges

- **Problem:** Cleaning and preparing text data by removing noise, stop words, and handling special characters.
- **Example:** Removing HTML tags and punctuation marks from web-scraped content.

### 4. Techniques for Reading Unstructured Data

- **Text Preprocessing**
  - **Tokenization:** Splitting text into individual words or tokens.
  - **Example:** "The quick brown fox" becomes ["The", "quick", "brown", "fox"].
  - **Stop Words Removal:** Eliminating common words that do not add significant meaning.
  - **Example:** "The", "is", "in" are removed from the text.
  - **Stemming and Lemmatization:** Reducing words to their root form.
  - **Example:** "Running" and "ran" both reduced to "run".
- **Vectorization**
  - **Bag of Words (BoW):** Representing text as a set of word counts.
  - **Example:** "The quick brown fox" and "The quick blue fox" become vectors: [2, 1, 1, 1, 0] and [2, 1, 0, 1, 1] respectively.
  - **Term Frequency-Inverse Document Frequency (TF-IDF):** Adjusting the weight of words based on their frequency in the document and across documents.
  - **Example:** In a document corpus, "rareword" appears in one document, boosting its weight in that document compared to common words.
  - **Word Embeddings:** Using models like Word2Vec, GloVe, or FastText to represent words in continuous vector space.
  - **Example:** Word2Vec represents "king" and "queen" as vectors close in the embedding space.
- **Natural Language Processing (NLP) Tools**
  - **NLTK (Natural Language Toolkit):** A suite of libraries and programs for symbolic and statistical natural language processing.
  - **spaCy:** An open-source library for advanced NLP.
  - **Gensim:** A library for topic modeling and document similarity analysis.

### 5. Data Sources and Collection Methods

- **Web Scraping:** Extracting data from websites using tools like BeautifulSoup, Scrapy.
- **APIs:** Accessing data from social media platforms, news sites, etc., via their provided APIs.
- **Manual Collection:** Gathering data manually from various sources.

### 6. Data Cleaning and Preparation

- **Noise Removal:** Eliminating irrelevant or redundant data.
- **Normalization:** Converting text to a standard format (e.g., lowercasing, removing punctuation).

- **Handling Missing Data:** Strategies for dealing with incomplete information.

## 7. Analyzing Unstructured Data

- **Exploratory Data Analysis (EDA):** Understanding the dataset using visualizations and summary statistics.
- **Text Mining:** Extracting meaningful information and patterns from text data.
- **Machine Learning Models:** Applying models like Naive Bayes, SVM, or neural networks for tasks like classification, clustering, and regression.

## Representing Text Data in Text Data Analysis

### 1. Text Data Representation

- **Purpose:** Transforming raw text into a structured format that can be used for analysis and modeling.
- **Importance:** Enables the application of statistical and machine learning techniques to text data.

### 2. Basic Text Representation Techniques

- **Bag of Words (BoW)**
  - **Definition:** Represents text as a collection of words, disregarding grammar and word order.
  - **Process:** Tokenize text, count the occurrences of each word.
  - **Advantages:** Simple and easy to implement.
  - **Disadvantages:** Ignores word order and context, leading to loss of semantic meaning.
- **Term Frequency-Inverse Document Frequency (TF-IDF)**
  - **Definition:** Weighs the importance of a word in a document relative to its frequency across all documents.
  - **Example:**
    - Document 1: "Machine learning is fascinating."
    - Document 2: "Machine learning involves algorithms."
  - **TF-IDF Vectors:**
    - Document 1: [0.5, 0.5, 0.5, 0.5]
    - Document 2: [0.5, 0.5, 0.0, 0.0]
  - Vocabulary: {"machine": 0.5, "learning": 0.5, "is": 0.5, "fascinating": 0.5, "involves": 0.5, "algorithms": 0.5}
  - **Advantages:** Reduces the weight of common words, highlighting more informative terms.
  - **Disadvantages:** Still a sparse representation, context and word order are ignored.

### 3. Advanced Text Representation Techniques

- **Word Embeddings**
  - **Definition:** Dense vector representations of words that capture semantic meaning.
  - **Common Models:**
    - **Word2Vec:** Creates embeddings by predicting word context (CBOW, Skip-gram).
    - **GloVe (Global Vectors for Word Representation):** Builds embeddings by factorizing the word co-occurrence matrix.
    - **FastText:** Extends Word2Vec by considering subword information.
  - **Advantages:** Captures semantic relationships and word similarity.
  - **Disadvantages:** Fixed vector size for words, context-specific meaning might be lost.
- **Contextualized Word Embeddings**

**Definition:** Embeddings that vary based on the context in which the word appears.

**Example :** Sentence: "**The bank on the river was steep.**"

In this sentence, the word "**bank**" can have different meanings based on its context:

**Bank (financial institution):** "The bank on the river was closed for renovations."

**Bank (slope of land beside a body of water):** "The bank on the river was steep."

- **Common Models:**
  - **BERT (Bidirectional Encoder Representations from Transformers):** Generates context-aware embeddings using transformer architecture.
  - **ELMo (Embeddings from Language Models):** Uses deep bidirectional language models to generate embeddings.
- **Advantages:** Captures context-specific meaning, improving performance on various NLP tasks.
- **Disadvantages:** Computationally intensive, requires large datasets for training.

#### 4. Document-Level Representations

- **Document Embeddings**
  - **Definition:** Representing entire documents as vectors.
  - **Techniques:**
    - **Doc2Vec:** Extends Word2Vec to documents, creating vectors for sentences, paragraphs, or documents.
    - **Universal Sentence Encoder:** Uses transformer and deep averaging network architectures to create embeddings.
  - **Advantages:** Captures the overall meaning of the document, useful for document classification and clustering.
  - **Disadvantages:** Requires large amounts of data and computational resources for training.

#### 5. Other Text Representation Techniques

- **N-grams**

**Definition:** Sequences of n words/tokens used to capture local context.

**Types:** Unigrams (1-gram), Bigrams (2-gram), Trigrams (3-gram), etc.

**Example Sentence:** "I love natural language processing."

**1-grams (Unigrams):**

"I"  
 "love"  
 "natural"  
 "language"  
 "processing"

**2-grams (Bigrams):**

"I love"  
 "love natural"  
 "natural language"  
 "language processing"

**3-grams (Trigrams):**

"I love natural"  
 "love natural language"  
 "natural language processing"

- **Advantages:** Captures some local context, simple to implement.
- **Disadvantages:** Can lead to data sparsity, computationally expensive for large n.
- **Topic Models**
  - **Definition:** Represents documents in terms of topics, which are distributions over words.
  - **Common Models:**
- **Latent Dirichlet Allocation (LDA):** Tokenize each document into words.
  - Remove stopwords (commonly used words like "the", "and", "is").
  - Normalize words (convert to lowercase, remove punctuation).
  - **Advantages:** Identifies hidden thematic structures in text.
  - **Disadvantages:** Complex to implement, parameter tuning can be challenging.

## 6. Evaluation of Text Representations

- **Intrinsic Evaluation:** Measures the quality of representations based on predefined linguistic tasks (e.g., word similarity).
- **Extrinsic Evaluation:** Assesses the performance of representations on downstream NLP tasks (e.g., text classification, sentiment analysis).

## Part of Speech Tagging in Text Data Analysis

### 1. Part of Speech (POS) Tagging

- **Definition:** Part of Speech (POS) tagging is the process of labeling each word in a text with its corresponding part of speech (noun, verb, adjective, etc.).
- **Importance:** Understanding the grammatical structure of text, which is crucial for various natural language processing (NLP) tasks.

### 2. Common Parts of Speech

- **Nouns (NN):** Person, place, thing, or idea (e.g., "dog", "city").
- **Verbs (VB):** Actions or states (e.g., "run", "is").
- **Adjectives (JJ):** Describes nouns (e.g., "happy", "blue").
- **Adverbs (RB):** Modifies verbs, adjectives, or other adverbs (e.g., "quickly", "very").
- **Pronouns (PRP):** Replaces nouns (e.g., "he", "they").
- **Prepositions (IN):** Shows relationships between nouns (e.g., "in", "on").
- **Conjunctions (CC):** Connects words or groups of words (e.g., "and", "but").
- **Determiners (DT):** Introduces nouns (e.g., "the", "a").
- **Interjections (UH):** Expresses emotion (e.g., "oh", "wow").

### 3. Techniques for POS Tagging

- **Rule-Based Tagging**

**Definition:** Uses a set of hand-crafted rules to assign POS tags.

**Example:**

□ **Input Text:** "John likes to eat pizza with his friends."

□ **Task:** Tag each word with its part of speech (POS).

□ **Rules:**

Proper nouns (like names) typically start with a capital letter.

Words ending in "s" are often plural nouns or third person singular verbs.

Words ending in "ed" are usually past tense verbs.

□ **Rule-Based Tagging Steps:**

Tokenization: Split the sentence into tokens (words).

Tokens: ["John", "likes", "to", "eat", "pizza", "with", "his", "friends", "."]

**Apply Rules:**

- "John" → Proper noun (NNP)
- "likes" → Verb (VBZ)
- "to" → Preposition (IN)
- "eat" → Verb (VB)
- "pizza" → Noun (NN)
- "with" → Preposition (IN)
- "his" → Possessive pronoun (PRP\$)
- "friends" → Noun (NNS)
- "." → Punctuation (.)

□ **Output:** Tagged tokens based on the rules.

- Tagged Output: [("John", "NNP"), ("likes", "VBZ"), ("to", "IN"), ("eat", "VB"), ("pizza", "NN"), ("with", "IN"), ("his", "PRP\$"), ("friends", "NNS"), (".", ".")]

- **Advantages:** Simple, interpretable.

- **Disadvantages:** Not scalable, requires extensive linguistic knowledge.
- **Statistical Tagging**
- It involves automatically assigning parts-of-speech (such as nouns, verbs, adjectives, etc.) to words in a text
  - **Hidden Markov Models (HMM)**
    - **Definition:** Uses probabilistic models to predict the sequence of POS tags.
    - **Example: Input** - “He saw the man with the telescope”
    - **Output:** POS Tagged – [(“He”, ”Pronoun”), ( “saw”, ”verb”), ( “the”, ”Determiner”) “man” “with” “the”, “telescope”
    - **Advantages:** Captures sequence information.
    - **Disadvantages:** Requires large annotated corpora, assumes independence between words.
  - **Conditional Random Fields (CRF)**
    - **Definition:** A type of statistical modeling method used for structured prediction.
    - **Advantages:** Handles dependencies between neighboring tags more effectively.
    - **Disadvantages:** Computationally intensive.
- **Machine Learning-Based Tagging**
- To automatically assign tags or labels to text data based on patterns learned from annotated training examples.
  - **Supervised Learning**
    - **Algorithms:** Decision trees, Support Vector Machines (SVM), Neural Networks.
    - **Advantages:** Can learn complex patterns from data.
    - **Disadvantages:** Requires labeled training data.
  - **Deep Learning Approaches**
    - **Recurrent Neural Networks (RNN):** Captures dependencies in sequences.
    - **Long Short-Term Memory (LSTM):** Addresses vanishing gradient problem in RNNs.
    - **Transformers (e.g., BERT):** Provides context-aware tagging using attention mechanisms.
    - **Advantages:** High accuracy, captures long-range dependencies.
    - **Disadvantages:** Requires substantial computational resources and large datasets.

#### 4. POS Tagging Process

- **Text Preprocessing:** Tokenization, cleaning.
- **Feature Extraction:** Extract features relevant for tagging (e.g., word prefixes, suffixes, capitalization).
- **Model Training:** Training a POS tagger on annotated corpora.
- **Tagging:** Applying the trained model to new text.

#### 5. Evaluation of POS Tagging

- **Metrics**
  - **Accuracy:** The proportion of correctly tagged words.
  - **Precision, Recall, F1-Score:** Evaluates the performance of specific tags.
- **Annotated Corpora:** Datasets like Penn Treebank, Brown Corpus used for training and evaluation.

#### 6. Applications of POS Tagging

- **Syntax Parsing:** Helps in understanding the grammatical structure of sentences.
- **Named Entity Recognition (NER):** Assists in identifying entities like names, dates, locations.
- **Machine Translation:** Improves the quality of translated text by providing grammatical context.
- **Information Retrieval:** Enhances search engines by understanding the context of queries.
- **Text-to-Speech Systems:** Improves pronunciation and intonation by understanding word roles.

# Syntactic Representation in Text Data Analysis

## 1. Introduction to Syntactic Representation

- **Definition:** Syntactic representation involves the analysis and depiction of the structure of sentences based on grammar and syntax rules.
- **Importance:** Understanding sentence structure is crucial for various NLP tasks such as parsing, translation, and sentiment analysis.

## 2. Basic Concepts in Syntax

- **Grammar:** The set of rules that define the structure of sentences in a language.
- **Syntax:** The arrangement of words and phrases to create well-formed sentences.
- **Constituents:** Words or groups of words that function as a single unit within a hierarchical structure.
- **Parse Trees:** Tree structures that represent the syntactic structure of sentences.

## 3. Types of Syntactic Representation

- **Constituency Grammar (Phrase Structure Grammar)**
  - **Definition:** Represents sentences as hierarchically nested phrases.
  - **Components:**
    - **Noun Phrases (NP):** Groups of words centered around a noun (e.g., "the quick brown fox").
    - **Verb Phrases (VP):** Groups of words centered around a verb (e.g., "jumps over the lazy dog").
    - **Advantages:** Clearly shows hierarchical relationships and phrase boundaries.
    - **Disadvantages:** Can be complex and computationally expensive for long sentences.
- **Dependency Grammar**
  - **Definition:** Represents sentences based on dependencies between words, emphasizing the relationship between head words and their dependents.
  - **Components:**
    - **Head:** The central word that other words depend on.
    - **Dependent:** Words that modify or complement the head.
  - **Advantages:** Simpler representation, efficient parsing algorithms.
  - **Disadvantages:** Less intuitive for understanding hierarchical structures.
- **Hybrid Approaches**
  - **Combination:** Uses elements of both constituency and dependency grammars to leverage their strengths.

## 4. Syntactic Parsing Techniques

- **Rule-Based Parsing**
  - **Definition:** Uses a predefined set of grammatical rules to parse sentences.
  - **Advantages:** High precision for well-defined grammatical structures.
  - **Disadvantages:** Not scalable, requires extensive manual rule creation.
- **Statistical Parsing**
  - **Definition:** Uses probabilistic models to determine the most likely parse tree for a sentence.
  - **Common Models:**
    - **Probabilistic Context-Free Grammars (PCFG):** Extends CFGs by associating probabilities with production rules.
    - **Advantages:** Handles ambiguities, adapts to different languages and domains.
    - **Disadvantages:** Requires large annotated corpora for training.
- **Machine Learning-Based Parsing**
  - **Supervised Learning**
    - **Algorithms:** Decision trees, Support Vector Machines (SVM), Neural Networks.
    - **Advantages:** Learns complex patterns from annotated data.
    - **Disadvantages:** Depends on the availability of labeled training data.
  - **Deep Learning Approaches**

- **Recurrent Neural Networks (RNN):** Captures sequential dependencies in text.
- **Long Short-Term Memory (LSTM):** Addresses vanishing gradient problem in RNNs.
- **Transformers (e.g., BERT, GPT):** Uses self-attention mechanisms for more accurate parsing.
- **Advantages:** High accuracy, handles long-range dependencies.
- **Disadvantages:** Computationally intensive, requires substantial resources for training.

## 5. Applications of Syntactic Representation

- **Machine Translation:** Improves the quality of translations by understanding sentence structure.
- **Information Extraction:** Extracts structured information from unstructured text by identifying relationships and entities.
- **Question Answering Systems:** Enhances understanding of questions and generates more accurate answers.
- **Sentiment Analysis:** Improves sentiment detection by understanding the role and relationship of words in a sentence.
- **Text Summarization:** Helps in generating concise summaries by understanding sentence structure and importance.

## 6. Evaluation of Syntactic Representation

- **Metrics**
  - **Precision and Recall:** Measures the accuracy of correctly identified syntactic structures.
  - **F1-Score:** Combines precision and recall into a single metric.
  - **Parsing Accuracy:** Evaluates the correctness of generated parse trees compared to gold standard annotations.
- **Annotated Corpora:** Datasets like Penn Treebank, Universal Dependencies used for training and evaluation.

## Text Similarity in Text Data Analysis

### 1. Introduction to Text Similarity

- **Definition:** Text similarity measures how alike two pieces of text are in terms of their content, structure, or semantics.
- **Importance:** Crucial for various NLP applications such as information retrieval, document clustering, and plagiarism detection.

### 2. Types of Text Similarity

- **Lexical Similarity**
  - **Definition:** Measures similarity based on the surface forms of the text (e.g., word overlap).

#### Methods of Measuring Lexical Similarity:

- **Edit Distance:**
  - **Definition:** Calculates the minimum number of single-character edits (insertions, deletions, substitutions) required to transform one word into another.
  - **Example:**
    - Words: "cat", "hat"
    - Edit Distance: 1 (substitute 'c' with 'h')
- **Cosine Similarity:**
  - **Definition:** Measures the cosine of the angle between two vectors representing the word embeddings (semantic meanings) of the words.
  - **Example:**
    - Word Embeddings:
      - "cat": [0.3, -0.1, 0.5, ...]
      - "dog": [0.2, 0.4, 0.6, ...]



- **Cosine Similarity:** Calculated using the vectors.
- **Jaccard Similarity:**
  - **Definition:** Measures similarity between sets of words based on the intersection and union of their tokens.
  - **Example:**
    - Sets: {"cat", "dog", "pet"}, {"cat", "dog", "animal"}
    - Jaccard Similarity:  $|\{"cat", "dog"\}| / |\{"cat", "dog", "pet", "animal"\}|$ .
- **WordNet-based Similarity:**
  - **Definition:** Uses WordNet, a lexical database, to compute similarity based on semantic relationships between words.
  - **Example:**
    - Words: "cat", "dog"
    - WordNet Similarity: Based on their hierarchical relationships in WordNet.
  - **Advantages:** Simple to compute.
  - **Disadvantages:** Ignores semantic meaning and context.
- **Semantic Similarity**
  - **Definition:** Measures similarity based on the meaning of the text.
  - **Methods:**
    - **Word Embeddings (Word2Vec, GloVe):** Represents words as dense vectors capturing semantic meaning.
    - **Sentence Embeddings (Doc2Vec, Universal Sentence Encoder):** Represents entire sentences or documents as vectors.
    - **Transformers (BERT, GPT):** Uses context-aware embedding to capture deep semantic meaning.
  - **Advantages:** Captures the semantic meaning of the text.
  - **Disadvantages:** Computationally intensive, requires pre-trained models.

### 3. Text Similarity Techniques

- **Bag of Words (BoW)**
  - **Definition:** Represents text as a collection of words, ignoring grammar and word order.
  - **Usage:** Simple similarity measures like Jaccard and Cosine similarity.
  - **Advantages:** Easy to implement.
  - **Disadvantages:** Ignores context and word order.
- **TF-IDF (Term Frequency-Inverse Document Frequency)**
  - **Definition:** Weighs words by their importance in a document relative to a corpus.
  - **Usage:** Enhances the effectiveness of similarity measures like Cosine similarity.
  - **Advantages:** Highlights informative words.
  - **Disadvantages:** Still a sparse representation.
- **Word Embeddings**
  - **Definition:** Dense vector representations capturing semantic meaning.
  - **Common Models:** Word2Vec, GloVe, FastText.
  - **Advantages:** Captures word semantics and similarities.
  - **Disadvantages:** Fixed vector size, context-independent.
- **Sentence and Document Embeddings**
  - **Definition:** Vector representations of sentences or documents capturing overall meaning.
  - **Common Models:** Doc2Vec, Universal Sentence Encoder.
  - **Advantages:** Captures the meaning of entire sentences or documents.
  - **Disadvantages:** Requires substantial data and computational resources for training.
- **Contextualized Embeddings**
  - **Definition:** Context-aware embeddings that change based on the surrounding words.
  - **Common Models:** BERT, GPT, ELMo.
  - **Advantages:** Captures nuanced, context-specific meaning.
  - **Disadvantages:** Computationally intensive, requires large datasets.

### 4. Applications of Text Similarity

- **Information Retrieval:** Finding documents or content similar to a query.
- **Document Clustering:** Grouping similar documents together.

- **Plagiarism Detection:** Identifying copied or similar content.
- **Recommendation Systems:** Suggesting similar items or content to users.
- **Text Summarization:** Finding sentences that best represent the content of a document.
- **Paraphrase Detection:** Identifying different ways of expressing the same idea.

## WorldNet-Based Similarity in Text Data Analysis

### 1. Introduction to WordNet-Based Similarity

- **Definition:** WordNet-based similarity measures use the WordNet lexical database to determine the similarity between words based on their meanings and relationships.
- **Importance:** Enhances semantic understanding in NLP applications by leveraging the structured knowledge in WordNet.

### 2. Overview of WordNet

- **Definition:** WordNet is a large lexical database of English, where words are grouped into sets of cognitive synonyms (synsets), each expressing a distinct concept.
- **Components:**
  - **Synsets:** Sets of synonyms representing a single concept.
  - **Relations:** Various relationships between synsets such as hypernymy (is-a), hyponymy (subtype), meronymy (part-of), and antonymy (opposites).

### 3. Types of WordNet-Based Similarity Measures

- **Path-Based Similarity**
  - **Definition:** Measures similarity based on the shortest path between concepts in the WordNet graph.

#### Methods of Path-Based Similarity:

##### □ Shortest Path Distance:

- **Definition:** Computes the shortest path (minimum number of edges) between two nodes (words/concepts) in a structured knowledge graph or ontology.
- **Example:**
  - Knowledge Graph (Graph structure):
    - Nodes: "cat", "dog", "animal", "pet"
    - Edges: Relationships like "is-a", "part-of"
  - Shortest Path:
    - Between "cat" and "dog": [cat] -- is-a --> [animal] -- is-a --> [dog]

##### □ Wu-Palmer Similarity:

- **Definition:** Measures similarity based on the depth of the least common subsumer (ancestor) and the depths of the two concepts in a structured hierarchy.
- **Example:**
  - WordNet (Hierarchical structure):
    - Words: "cat", "dog"
    - Wu-Palmer Similarity: Calculated using the depths of their least common ancestor and their own depths.

##### □ Leacock-Chodorow Similarity:

- **Definition:** Similar to Wu-Palmer, but incorporates the shortest path distance in addition to the depths of concepts.
- **Example:**

- WordNet:
    - Words: "cat", "dog"
    - Leacock-Chodorow Similarity: Combines shortest path distance and depths in the hierarchy.
    - **Advantages:** Simple and easy to compute.
    - **Disadvantages:** Does not account for the depth of concepts in the hierarchy.
- **Information Content (IC)-Based Similarity**

**Definition:** Information content (IC)-based similarity measures in NLP calculate the similarity between words or concepts based on their rarity or specificity in a large corpus of text or a knowledge base.

#### Methods of IC-Based Similarity:

- **Resnik Similarity:**
- **Definition:** Measures similarity based on the information content of the most informative common ancestor (MICA) in a taxonomy or ontology.
- **Example:**
  - WordNet (Hierarchical structure):
    - Words: "cat", "dog"
    - Information Content: Based on the frequencies of occurrences of "cat" and "dog" in a large corpus.
    - Resnik Similarity: Calculated using the information content of their MICA.
- **Lin Similarity:**
- **Definition:** Combines information content with the concept's depth in the hierarchy to measure similarity.
- **Example:**
  - WordNet:
    - Words: "cat", "dog"
    - Information Content: Frequency-based rarity of "cat" and "dog".
    - Lin Similarity: Incorporates both information content and depth of concepts.
- **Jiang-Conrath Similarity:**
- **Definition:** Similar to Lin similarity but penalizes for the depth difference between concepts.
- **Example:**
  - WordNet:
    - Words: "cat", "dog"
    - Information Content: Rarity or specificity measure of "cat" and "dog".
    - Jiang-Conrath Similarity: Accounts for both information content and the distance between concepts in the hierarchy.
- - **Advantages:** Accounts for the specificity of concepts.
  - **Disadvantages:** Requires a corpus to compute IC values.

#### Feature-Based Similarity

- **Definition:** Measures similarity based on the properties and features shared by the concepts.

#### Methods of Feature-Based Similarity:

- **Word Embedding-Based Similarity:**
  - **Definition:** Uses word embeddings (dense vector representations) to capture semantic similarities between words based on their contextual meanings.
  - **Example:**
    - Word Embeddings:
      - "cat": [0.3, -0.1, 0.5, ...]
      - "dog": [0.2, 0.4, 0.6, ...]
    - Similarity Measure (e.g., cosine similarity): Calculated using the vectors.

- **Sentence Embedding-Based Similarity:**
  - **Definition:** Represents entire sentences or documents as embeddings and measures similarity based on their overall semantic content.
  - **Example:**
    - Sentence Embeddings:
      - "The cat is on the mat.": [0.1, 0.2, -0.3, ...]
      - "A dog sits on the rug.": [0.3, 0.0, -0.2, ...]
    - Similarity Measure (e.g., cosine similarity): Comparing the sentence embeddings.
- **Feature Engineering-Based Similarity:**
  - **Definition:** Constructs features such as n-grams, syntactic patterns, or lexical attributes to quantify similarity between texts.
  - **Example:**
    - Features:
      - N-grams: "cat" vs "bat"
      - Syntactic Patterns: Verb-object relationships
      - Lexical Attributes: Word frequencies, POS patterns
- **Topic Modeling-Based Similarity:**
  - **Definition:** Uses topic distributions from models like Latent Dirichlet Allocation (LDA) to measure similarity based on shared topics between texts.
  - **Example:**
    - Topics:
      - Document 1: Topic A (60%), Topic B (30%), Topic C (10%)
      - Document 2: Topic A (70%), Topic B (20%), Topic C (10%)
    - Similarity Measure: Based on the overlap of topic distributions.

#### 4. Applications of WordNet-Based Similarity

- **Word Sense Disambiguation:** Determines the correct sense of a word based on context.
- **Information Retrieval:** Enhances search results by understanding the semantic similarity between queries and documents.
- **Text Classification:** Improves the classification of text by considering semantic relationships between words.
- **Machine Translation:** Enhances translation quality by understanding the meanings and relationships of words.
- **Text Summarization:** Identifies semantically similar sentences for better summarization.

### Shallow Parsing in Text Data Analysis

#### 1. Introduction to Shallow Parsing

- **Definition:** Shallow parsing, also known as chunking, involves identifying the constituents (like noun phrases, verb phrases, etc.) in a sentence without deep hierarchical parsing.
- **Importance:** Provides a balance between full syntactic parsing and basic part-of-speech tagging, useful in many NLP tasks.

#### 2. Key Concepts in Shallow Parsing

- **Chunks:** Groups of words that form a single syntactic unit, such as noun phrases (NP), verb phrases (VP), and prepositional phrases (PP).
- **Chunking vs. Full Parsing:** Unlike full parsing, which builds complete parse trees, chunking only identifies and labels the flat structure of phrases.

#### 3. Components of Shallow Parsing

- **Tokenization:** Splitting text into individual tokens (words, punctuation).
- **Part-of-Speech Tagging:** Assigning parts of speech to each token (noun, verb, adjective, etc.).
- **Chunk Identification:** Grouping tokens into chunks based on their part-of-speech tags and predefined patterns.

## 4. Shallow Parsing Techniques

- **Rule-Based Methods**
  - **Definition:** Use predefined rules and patterns to identify chunks.
  - **Advantages:** Simple and interpretable.
  - **Disadvantages:** Limited flexibility and coverage, requires extensive manual rule creation.
- **Machine Learning-Based Methods**
  - **Supervised Learning**
    - **Algorithms:** Hidden Markov Models (HMM), Conditional Random Fields (CRF), Support Vector Machines (SVM).
    - **Advantages:** Can learn complex patterns from annotated data.
    - **Disadvantages:** Requires labeled training data.
  - **Neural Network Approaches**
    - **Recurrent Neural Networks (RNN):** Captures sequential dependencies in text.
    - **Long Short-Term Memory (LSTM):** Addresses vanishing gradient problem in RNNs.
    - **Bidirectional LSTM (BiLSTM):** Considers context from both directions in a sentence.
    - **Advantages:** High accuracy, captures long-range dependencies.
    - **Disadvantages:** Computationally intensive, requires substantial data and resources for training.

## 5. Applications of Shallow Parsing

- **Named Entity Recognition (NER):** Identifying and classifying named entities (persons, organizations, locations) in text.
- **Information Extraction:** Extracting structured information from unstructured text, such as relations and events.
- **Sentiment Analysis:** Analyzing sentiment by focusing on specific chunks (e.g., noun phrases).
- **Text Summarization:** Identifying important phrases and key information for concise summaries.
- **Question Answering:** Enhancing the understanding of questions and generating accurate answers.

### Semantic representation in Text Data Analysis

- **Definition:** Semantic representation is the process of encoding the meanings of words, phrases, and sentences in a form that a computer can process and understand.
- **Importance:** Essential for various NLP tasks such as machine translation, information retrieval, question answering, and text summarization.

#### 1. Key Concepts in Semantic Representation

- **Semantics:** Study of meaning in language.
- **Semantic Representation:** Techniques to capture and encode the meaning of linguistic units.

#### 2. Types of Semantic Representation

- **Lexical Semantics**
  - **Definition:** Focuses on the meaning of individual words.
  - **Techniques:**
    - **Dictionaries and Thesauri:** Traditional resources for word meanings.
    - **WordNet:** A lexical database that groups words into synsets representing specific concepts.
  - **Limitations:** Static and does not capture contextual meaning.
- **Compositional Semantics**
  - **Definition:** Studies how meanings of individual words combine to form the meaning of phrases and sentences.
  - **Techniques:**
    - **Formal Semantics:** Uses logical formalisms like lambda calculus to represent meaning.

- **Distributional Semantics:** Represents words based on the contexts in which they appear.
  - **Limitations:** Can be complex and computationally intensive.
- **Distributional Semantics**
  - **Definition:** Based on the idea that words appearing in similar contexts have similar meanings.
  - **Techniques:**
    - **Vector Space Models:** Words are represented as vectors in high-dimensional space.
    - **Word Embeddings:** Dense vector representations capturing semantic similarity.
    - **Limitations:** May not capture nuances of meaning and word sense disambiguation.

### 3. Techniques for Semantic Representation

- **Bag of Words (BoW)**
  - **Definition:** Represents text as an unordered collection of words.
  - **Advantages:** Simple and easy to implement.
  - **Disadvantages:** Ignores word order and context.
- **TF-IDF (Term Frequency-Inverse Document Frequency)**
  - **Definition:** Weights words by their frequency in a document relative to their frequency in a corpus.
  - **Advantages:** Highlights important words.
  - **Disadvantages:** Still a sparse representation, ignores context.
- **Word Embeddings**
  - **Definition:** Dense vector representations capturing semantic meaning.
  - **Techniques:**
    - **Word2Vec:** Uses neural networks to create word embeddings based on context.
    - **GloVe (Global Vectors for Word Representation):** Combines local context and global statistical information.
    - **FastText:** Extends Word2Vec by considering subword information.
  - **Advantages:** Captures semantic relationships between words.
  - **Disadvantages:** Context-independent.
- **Contextualized Word Embeddings**
  - **Definition:** Word embeddings that change based on the surrounding context.
  - **Techniques:**
    - **ELMo (Embeddings from Language Models):** Uses bidirectional LSTM to capture context.
    - **BERT (Bidirectional Encoder Representations from Transformers):** Pre-trained on large corpora to capture deep contextual meaning.
  - **Advantages:** Highly accurate, captures nuanced meanings.
  - **Disadvantages:** Computationally intensive.
- **Sentence and Document Embeddings**
  - **Definition:** Vector representations capturing the meaning of entire sentences or documents.
  - **Techniques:**
    - **Doc2Vec:** Extends Word2Vec to sentences and documents.
    - **Universal Sentence Encoder:** Uses deep learning to encode sentences.
    - **Advantages:** Captures the meaning of larger text units.
    - **Disadvantages:** Requires substantial data and computational resources.
- **Knowledge Graphs**
  - **Definition:** Structured representations of knowledge in graph form, where nodes represent entities and edges represent relationships.
  - **Techniques:**
    - **RDF (Resource Description Framework):** Standard model for data interchange on the web.
    - **OWL (Web Ontology Language):** Formal language for representing rich and complex knowledge about things, groups of things, and relations between things.
    - **Advantages:** Captures complex relationships and rich semantic information.
    - **Disadvantages:** Complex to create and maintain.

### 4. Applications of Semantic Representation

- **Information Retrieval:** Improving search results by understanding the meaning of queries and documents.
- **Machine Translation:** Translating text by understanding the semantic content.
- **Question Answering:** Providing accurate answers by understanding the semantics of questions and potential answers.
- **Text Summarization:** Creating summaries by understanding the main ideas and concepts in a text.
- **Sentiment Analysis:** Analyzing sentiment by understanding the meaning and context of words and phrases.