

---

## Software Development

[Tutorials](#) [Articles](#) [Ebooks](#) [Free Practice Tests](#) [On-demand Webinars](#)

[Home](#) [Resources](#) [Software Development](#) [C++ Tutorial for Beginner](#) [Top 60 C++ Interview Questions And Answers for 2025](#)



# Top 60 C++ Interview Questions And Answers for 2025

Lesson 20 of 24

By Pulkrit Jain

Last updated on Apr 10, 2025

903525

[Previous](#)

[Next](#)

---

**Tutorial Playlist**

---

## Table of Contents

[C++ Interview Questions For Freshers](#)

[C++ Interview Questions For Intermediate](#)

[C++ Interview Questions For Experienced](#)

[Related Software Developer Interview Guides](#)

[Choose The Right Software Development Program](#)

[View More](#)

Interview questions are a necessary part of the selection process of any company or organization. To face the interviewer, one needs to be fully prepared for the interview questions. In this C++ interview questions tutorial, you will look at the most commonly asked C++ interview questions that one should know.

In this C++ interview questions tutorial, you will go through some conceptual questions, multiple-choice, output-based, and programming questions that you can expect in any C++ interview.

So let’s begin with the top 40 commonly asked C++ interview questions.

Want a Top Software Development Job? Start Here!


Full Stack Developer - MERN Stack

EXPLORE PROGRAM

C++ Interview Questions For Freshers

The C++ Interview Questions addressed in this section cover the [fundamentals of the C++ language](#), an aspect to be known mandatorily.

1. What is the difference between C and C++?

C	C++
C is a procedure-oriented programming language	C++ is a partially object-oriented <a href="#">programming language</a>
It follows a top-down approach	It follows a bottom-up approach
	

C doesn't support function or operator overloading	C++ supports function as well as function overloading
C language doesn't support virtual and friend function	C++ language supports both virtual and friend functions.
C language has 32 keywords	C++ language contains 52 keywords

## 2. What are classes and objects in C++?

A **class** is like a blueprint of an object. It is a user-defined data type with data members and member functions and is defined with the keyword **class**.

**keyword** → **class class\_name**  
**{**  
    **Access specifier;**  
    **data members;**  
    **member functions()**  
**};**

You define objects as an instance of a class. Once it creates the object, then it can operate on both data members and member functions.

## 3. What are access modifiers?

You use access modifiers to define accessibility for the class members. It defines how to access the members of the class outside the class scope.

There are three types of access modifiers:

- Private
- Public
- Protected

#### 4. Difference between equal to (==) and assignment operator(=)?

The equal to operator == checks whether two values are equal or not. If equal, then it's true; otherwise, it will return false.

The assignment operator = allots the value of the right-side expression to the left operand.

#### 5. What is the difference between a while loop and a do-while loop?

while	do-while
The <b>while loop</b> verifies the condition; if it's true, then it iterates the loop till the condition becomes false.	The <b>do-while loop</b> first iterates the loop body once, then it checks for the condition.
Syntax:  while (condition)  {  statements	Syntax:  do{  statements  }

<code>}</code>	<code>while(condition);</code>
If the condition is false in a while loop, then not a single statement will execute inside the loop.	If the condition in a do-while loop is false, then the body will also execute once.

## Want a Top Software Development Job? Start Here!

Full Stack Developer - MERN Stack

EXPLORE PROGRAM

### 6. What is the size of the int data type?

1. 4 bytes
2. 1 byte
3. 8 bytes
4. 2 bytes

1 - 4 bytes, the integer data type is 4 bytes.

### 7. Which among the following operators cannot be overloaded?

1. -
2. +
3. ?:



4. %

3 - ?: operator cannot be overloaded because it is not syntactically possible.

### 8. What among these is used to return the number of characters in the string?

1. Size

2. Length

3. Both size and length

4. Name

3. Both size and length are used to return the number of characters in the string.

### 9. Discuss the difference between prefix and postfix?

In prefix (++i), first, it increments the value, and then it assigns the value to the expression.

In postfix (i++), it assigns the value to the expression, and then it increments the variable's value.

### 10. Can you compile a program without the main function?

Yes, you can compile a program without the [main function](#), but you cannot run or execute the program because the main() function is the entry point, from where all the execution begins. And without the entry point, then you can execute the program.

## Unleash Your Career as a Full Stack Developer!

Full Stack Developer - MERN Stack

EXPLORE COURSE

### 11. What is std in C++?



1. std is a standard class in C++
  2. std is a standard file reading header
  3. std is a standard header file
  4. std is a standard namespace
- 4 - std is a standard namespace in C++

## 12. What are the four different data types in C++?

- Primitive/Basic: Char, int, short, float, double, long, bool, etc.
- Derived: Array, pointer, etc.
- Enumeration: Enum
- User-defined: Structure, class, etc.

## 13. How is struct different from class?

Structure	Class
Its members are public by default.	Its members are private by default.
The default access specifiers are public when deriving a struct from a class/struct.	The default access specifiers are private when deriving a class.

## 14. What do you understand about polymorphism in C++?

The term polymorphism refers to the presence of multiple forms. Polymorphism usually occurs



when there is a hierarchy of classes that are linked by inheritance.

C++ polymorphism means that depending on the type of object that invokes the function, a different function will be executed.

### 15. Compare compile time and runtime polymorphism.

Compile-time Polymorphism	Runtime Polymorphism
The method to be executed is known at compile time. And the call is resolved by the compiler.	The method to be executed is known at run time. The compiler does not resolve the call.
Provides quicker execution because it is known at the compile time.	Provides slower execution because it is known at the run time.
Achieved by operation or function overloading.	Achieved by function overriding.

## Prepare Yourself to Answer All Questions!

Automation Testing Masters Program

EXPLORE PROGRAM



### 16. What is a constructor in C++?

In C++, a function Object is a particular "MEMBER FUNCTION" that shares the same title as the class it belongs to and is used to initialize specific values to an object's data members.

```
#include <iostream>
```

```
using namespace std;
```

```
class student {
```

```
    int no;
```

```
public:
```

```
    student()
```

```
{
```

```
    cout << "Enter the RollNo:";
```

```
    cin >> rno;
```

```
}
```

```
void display()
```

```
{
```

```
    cout << endl << rno << "\t";
```

```
}
```

```
};
```

```
int main()
```

```
{
```



```
student s; // constructor gets called automatically when  
  
    // we create the object of the class  
  
s.display();  
  
return 0;  
  
}
```

### 17. What is a virtual function?

A member function in the base class redefined in a derived class is a virtual function. It is declared using the virtual keyword. It ensures that the correct function is called for an object, irrespective of the type of reference/pointer used for the function call. Virtual functions are mainly used for runtime polymorphism.

### 18. What do you understand about friend class and friend function?

Like a friend function, a friend class can access personal and guarded variables of the type in which it is declared. All member functions for classes specified as friends to another class are friend functions for the friend class.

```
class Node {  
  
private:  
  
int key;  
  
Node* next;  
  
/* Other members of Node Class */  
  
// Now class LinkedList can  
  
// access private members of Node
```



```
friend class LinkedList;
```

```
};
```

## 19. What are the three different types of C++ access specifiers?

- **Public:** All member functions and data members are accessible outside the class.
- **Protected:** All member functions and data members are accessible within the class and to the derived class.
- **Private:** All member functions and data members cannot be accessed outside the class.

## 20. What is an abstraction in C++?

Abstraction means displaying the essential details to the user while hiding the irrelevant or particular details that you don't want to show to a user. It is of two types:

- Control abstraction
- Data abstraction

## Learn 15+ In-Demand Tools and Skills!

Automation Testing Masters Program

**EXPLORE PROGRAM**

## 21. What are destructors in C++?

A destructor member function is instantly called when an object exits its scope or is specifically deleted by a call to delete.

```
class X {
```

public:

```
// Constructor for class X
```

```
X();
```

```
// Destructor for class X
```

```
~X();
```

```
};
```

## 22. Is it possible to overload a destructor? Give reasons for your answer.

No, it is impossible as destructors do not take arguments or return anything. There has to be only one empty destructor per class. It should have a void parameter list.

## 23. What is an abstract class? When is it used?

An abstract class is a class whose objects cannot be created. It serves as a parent for the derived classes. Placing a pure virtual function in the class makes it an abstract class.

## 24. What do you understand about static members and static member functions?

A variable in a class declared as static has its space allocated for the lifetime of the program. Regardless of the number of objects of that class created, there is only a single copy of the static member. The same static member is accessible to all the objects of that class.

A static member function can be called even if no class objects exist. It is accessed using only the class name and the scope resolution operator (::).

## C++ Interview Questions For Intermediate

This set of C++ Interview Questions are bit more complex and advanced and form the next stage of your preparation for the C++ interview.

## 25. What is the C++ OOPs concept?

### OOPs concept in C++:

- Object
- Class
- Inheritance
- Polymorphism
- Encapsulation
- Abstraction

Object: Anything that exists physically in the real world is called an object.

Class: The collection of objects is called class.

Inheritance: Properties of parent class inherited into child class is known as inheritance.

Polymorphism: It is the ability to exist in more than one form.

Encapsulation: Binding of code and data together into a single unit.

Abstraction: Hiding internal details and showing functionality to the user.

## Want a Top Software Development Job? Start Here!

Full Stack Developer - MERN Stack

**EXPLORE PROGRAM**



## 26. When is void() return type used?

You use the void() return type when you don't want to return any value. It specifies that the function doesn't return a value. A function with a void return type completes its task and then returns the control to the caller.

## 27. What is call by value and call by reference in C++?

In the [call by value method](#), you pass the copies of actual parameters to the function's formal parameters. This means if there is any change in the values inside the function, then that change will not affect the actual values.

In the call-by-reference method, the reference or address of actual parameters is sent to the function's formal parameters. This means any change in values inside the function will be reflected in the actual values.

## 28. What is an inline function?

An [inline function](#) when called expands in line. When you call this function, the whole code of the inline function gets inserted or substituted at the inline function call.

Syntax:

Inline return-type function-name(parameters)

```
{  
  
}
```

## 29. What are pointers in C++?

[Pointers](#) are the variables that store the memory address of another variable. The type of the variable must correspond with the type of pointer.

Syntax: type \*name

## 30. What is a scope resolution operator?



A scope resolution operator is represented as ::

This operator is used to associate function definition to a particular class.

The scope operator is used for the following purposes:

- To access a global variable when you have a local variable with the same name.
- To define a function outside the class.

## Unleash a High-paying Automation Testing Job!

Automation Testing Masters Program

EXPLORE PROGRAM

31. What should be the output of the following C++ program?

```
111  #include<iostream>
112  using namespace std;
113
114  int main()
115  {
116      int i=0;
117      int x=0;
118      do{
119          if( i%5 ==0 )
120          {
```



```
121         cout<<x;
122         x++;
123     }
124     ++i;
125 }
126 while(i<10);
127
128 cout<<x;
129 return 0;
130 }
```

1. 01
2. 02
3. 012
4. 011

3 - 012, the value of i is 0 and  $i \% 5$  is equal to 0, so x is displayed and incremented and i is also incremented, then  $1 \% 5$  is not zero, so the condition is not met. Similarly, the process will repeat till  $4 \% 5$  because  $5 \% 5$  is zero. So the value of x is one and gets incremented to two. Then, the process will repeat for 6,7,8,9, but  $10 \% 10$  will be zero again, and the value of x is printed, which is 2.

### 32. What is a constructor?

A **constructor is defined** as a member function that is invoked whenever you create an object; it has the same name as that of the class.

There are two types of constructors:

- Default constructor: This auto-generated constructor doesn't take any arguments.
- Parameterized constructor: In this constructor, it can pass arguments.



### 33. Define operator overloading and function overloading.

An example of compile-time polymorphism is operator overloading. It is the concept of modifying an existing C++ operator without altering its original meaning.

Let us take an example for this

```
class A  
  
{  
  
};  
  
int main()  
  
{  
  
    A a1,a2,a3;  
  
    a3= a1 + a2;  
  
    return 0;  
  
}
```

### 34. How to input strings in C++ with spaces?

```
111  #include <iostream>  
112  #include <string>  
113  using namespace std;  
114  
115  int main()  
116  {  
117      string s;  
118  
119      cout << "Enter the sentence with spaces "<<endl;  
120      getline(cin, s);
```

```

120     getline(cin, s);
121
122     cout << s;
123     return 0;
124 }

```

### 35. Discuss the difference between new and malloc

new	malloc
new is an operator	malloc() is a function
It calls the constructor	The malloc function doesn't call the constructor
There is no need to specify memory size while using new()	You have to specify the memory size
new operator can be overloaded	malloc() can never be overloaded

### 36. What is operator overloading?

Operator overloading is a mechanism in which a special meaning is given to an operator.

For example, you can overload the '+' operator in a class-like string to concatenate two strings only using '+'

## Want a Top Software Development Job? Start Here!

Full Stack Developer - MERN Stack

EXPLORE PROGRAM

37. What is the output of the below C++ program?

```
111  #include<iostream>
112
113  using namespace std;
114
115  int main()
116  {
117      enum { blue, green = 5, GREAT };
118
119
120      cout<<blue<<" "<<GREAT;
121  }
```

1. 0 3

2. 0 8

3. 0 6

4. 0 2

3 - 0 6. In enum, the element's value is one greater than the previous element. The value of blue is 0 by default, and the value of green is five, so the value of GREAT will become six automatically.

38. What among these is used to return the number of characters in the string?

Size

Length

Both size and length

Name

3 - Both size and length are used to return the number of characters in the string

39. Which among the following statements is correct about the program given below?

```
1  #include <iostream>
2  using namespace std;
3  ✓ int main()
4  {
5      int x;
6      int *p;
7      x = 7;
8      p = &x;
9      cout << *p;
10     return 0;
11 }
```

1. The output will be 7

2. The output will be 14



3. The output will be 0

4. The output will be 1

1 - Output will be 7. Pointer p has the memory address of x, and you display the pointer with a dereference operator that will display the value 7.

40. Which among the following statements is correct about the program given below?

```
1  #include <iostream>
2      using namespace std;
3      void duplicate (int& a, int& b, int& c)
4      {
5          a *= 2;
6          b *= 2;
7          c *= 2;
8      }
9      int main ()
10     {
11         int x = 2, y = 4, z = 5;
12         duplicate (x, y, z);
13         cout << x << y << z;
14         return 0;
15     }
```

1. The output will be 245

2. The output will be 222

3. The output will be 4810

4. The output will be 4812

3 - Output will be 4810, because you are passing the references of the function here.



## Become an Automation Test Engineer in 11 Months!

Automation Testing Masters Program

EXPLORE PROGRAM

### 41. What is a friend function?

You can define a **friend function** as a function that can access private, public and protect members of the class. You declare the friend function with the help of the friend keyword. You declare this function inside the class.

### 42. Which of the following will give the size of object or type?

1. sizeof
2. malloc
3. realloc
4. calloc

1 - The sizeof operator is used to give the size of object or type

### 43. Which of the following is not a member of a class?

1. Static function
2. Virtual function
3. Const function
4. Friend function


4 - Among the following, friend function is not a member of the class

### 44. What is STL?



STL stands for standard template library. It is a library of container templates that provide generic classes and functions.

STL components are containers, algorithms, iterators, and function objects.



Now, have a look at some advanced-level C++ Interview Questions.

## C++ Interview Questions For Experienced

These C++ Interview Questions test your application skills in C++ and explore practical problems that might be posed to you in a C++ interview.

**45. How to write a program to check if a number is a palindrome or not?**





```
111 #include <iostream>
112 using namespace std;
113
114 ~int main()
115 {
116     int n, num, digit, rev = 0;
117     cout << "Enter a positive number: ";
118     cin >> num;
119     n = num;
120
121 ~    do
122     {
123         digit = num % 10;
124         rev = (rev * 10) + digit;
125         num = num / 10;
126     } while (num != 0);
127
128     cout << " The reverse of the number is: " << rev << endl;
129
130     if (n == rev)
131         cout << " The number is a palindrome.";
132     else
133         cout << " The number is not a palindrome.";
134     return 0;
135 }
```

Want a Top Software Development Job? Start Here!

Full Stack Developer - MERN Stack

EXPLORE PROGRAM



## 46. What is a copy constructor?

A copy function is a member function that uses another object from the same class to initialize a new thing. A copy function is, to put it simply, a function that produces an object by initializing it with a different object of the same class that has already been constructed.

```
#include <iostream>
```

```
using namespace std;
```

```
class A
```

```
{
```

```
    Public:
```

```
    int x;
```

```
    A(int a) // parameterized constructor.
```

```
    {
```

```
        x=a;
```

```
    }
```

```
    A(A &i) // copy constructor
```

```
    {
```

```
        x = i.x;
```

```
    }
```

```
};
```

```
int main()
```




```
{  
  
    A a1(20); // Calling the parameterized constructor.  
  
    A a2(a1); // Calling the copy constructor.  
  
    cout<<a2.x;  
  
    return 0;  
  
}
```

47. Write a program to find the factorial of a number?

```
1  #include <iostream>  
2  using namespace std;  
3  
4  int main() {  
5      int n;  
6  
7      int fact= 1;  
8  
9      cout << "Enter a positive integer: ";  
10     cin >> n;  
11  
12     if (n < 0)  
13     {  
14         cout << "Error!";  
15     }  
16     else {  
17         for(int i = 1; i <= n; ++i)  
18         {  
19             fact *= i;  
20         }  
21         cout << "Factorial of " << n << " = " << fact;  
22     }  
23     return 0;
```

#### 48. What is inheritance?

**Inheritance is the mechanism** in which you can create a new class i.e. child class from the existing class i.e. parent class. This child class is also known as a derived class and the parent class is also called Base class.



#### 49. What is Abstraction?

**Abstraction** can be defined as a technique in which you only show functionality to the user i.e., the details that you want the user to see, hiding the internal details or implementation details.

#### 50. What should be the output of the below code?

```
1  #include <iostream>
2
```

```
3  using namespace std;
4
5  int main()
6  {
7      int a=5;
8      int b=6;
9      int c;
10
11     c= (a>b) ? a : b;
12     cout<<c;
13     return 0;
14 }
```

1. 5

2. 4

3. 7

4. 6

4 - 6, Ternary operator is used, the value of a is less than b which violates the condition that is why 6 is the answer.

## Automation Test Engineer Master's Program

To learn about the automation of web applications

EXPLORE COURSE



51. How to find the frequency of a number in C++?

```
111  #include<iostream>
112  using namespace std;
113
114  ~ int frequency(int num, int k)
115  {
116      int c=0;
117  ~ while(num>0)
118      {
119  ~     if(num%10 == k)
120         {
121             c++;
122         }
123         num=num/10;
124     }
125     return c;
126 }
127
128 int main()
129 {
130     int num= 1332422523;
131
132     int k=2;
133     cout<<frequency(num, k);
134     return 0;
135 }
```

52. What should be the output of the below code?

```
1  #include <iostream>
```

```
2
3  using namespace std;
4
5  int main()
6  {
7      int i;
8      int j=10;
9
10     i=(j++, j+100, 999+j);
11
12     cout<<i;
13     return 0;
14 }
```

1. 1010
2. 1001
3. 11
4. 1000

1 - 1010, the value of j is incremented to 11, then j value is added to 100 but not assigned, and at last the value of j i.e 11 is added to 999 which gives us 1010.

### 53. What should be the correct statement about string objects in C++?

1. String objects should necessarily be terminated by a null character
2. String objects have a static size
3. String objects have a dynamic size



#### 4. String objects use extra memory than required

3 - String objects have a dynamic size.

## Want a Top Software Development Job? Start Here!

Full Stack Developer - MERN Stack

EXPLORE PROGRAM

#### 54. How is a shallow copy different from a deep copy?

Shallow Copy	Deep Copy
It stores the references of objects to the original memory address.	It makes a fresh and separate copy of an entire object and its unique memory address.
Faster	Comparatively slower
It reflects changes made to the new/copied object in the original object.	It doesn't reflect changes made to the new/copied object in the original object.

#### 55. How are virtual functions different from pure virtual functions?





A virtual function is a base class member function that a derived class can modify. A member function of a base class that is a pure virtual function must be defined in the derived type; otherwise, the derived class will become abstract as well.

```
class
```

```
interface Woocommerce{
```

```
void print();
```

```
}
```

```
class Bat implements Woo{
```

```
public void print(){System.out.println("Woo!");}
```

```
public static void main(String args[]){
```

```
Bat obj = new Bat();
```

```
obj.print();
```

```
}
```

```
}
```

**56. Class D is derived from a base class B. If creating an object of type D, what order will the constructors of these classes get called?**

The derived class consists of two parts: the base part and the derived part. C++ constructs derived objects in phases. The process begins with constructing the most-base class (at the top of the inheritance tree), followed by each child class construction in order, and then the most-child class. Thus, first, the Constructor of class B will be called, and then the constructor of class D.

**57. Can a virtual function be called from a constructor?**

A virtual process may be called a function Object, but exercise caution. It might perform differently than expected. The virtual call mechanism in a function Object is disabled since overriding from

derived classes hasn't happened yet. Building blocks are used to create objects, "base before derived."

```
class Dog{

void make(){

System.out.println("labrador");

}

}

public class Big extends Dog{

void make(){

System.out.println("Big Dog labrador ");

}

public static void main(String args[]){

Dog ob1 = new Big();

ob1.make();

}

}
```

## 58. What are void pointers?

In C, a void pointer has no connection to any particular data type. It designates a location for specific data within the storage. This indicates that it is pointing to a variable's address. It also goes by the name "general purpose pointer."

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
int a = 10;
```

```
char b = 'x';
```

```
void* p = &a; // void pointer holds address of int 'a'
```

```
p = &b; // void pointer holds address of char 'b'
```

```
}
```

## 59. What is this pointer in C++?

A class, struct, or union form only has access to this pointer within non-static member variables. The arrow shows the object for which the member function is called.

```
string food = "Pizza"; // A food variable of type string
```

```
string* ptr = &food; // A pointer variable, with the name ptr, that stores the address of food
```

```
// Output the value of food (Pizza)
```

```
cout << food << "\n";
```

```
// Output the memory address of food (0x6dfed4)
```

```
cout << &food << "\n";
```

```
// Output the memory address of food with the pointer (0x6dfed4)
```

```
cout << ptr << "\n";
```



## 60. How would you deallocate and allocate memory in C++?

The heap is used in C to allocate dynamic memory, and these functions are part of the standard library. Malloc() and free are the two important dynamic memory operations (). The size of the desired memory area in bytes is the only parameter accepted by the malloc() function.

```
#include <iostream>
```

```
#include <cstdlib>
```

```
#include <cstring>
```

```
using namespace std;
```

```
int main() {
```

```
    char *user;
```

```
    user = (char *) malloc(25);
```


```
    strcpy(user, "Jane_Eyre");
```

```
    cout << "User Name = " << user << " " << &user << endl;
```

```
    free(user);
```

```
}
```

## Related Software Developer Interview Guides

Coding	Java	Python 
--------	------	--

Java 8	Node.js	JavaScript
Angular	ReactJS	Spring Boot

Choose The Right Software Development Program

This table compares various courses offered by Simplilearn based on several key features and details. It provides an overview of the courses' duration, skills you will learn, and additional benefits, among other important factors, to help learners make an informed decision about which course best suits their needs.

Program Name	Full Stack Java Developer Masters Program	Automation Testing Masters Program
Geo	IN	All
University	Simplilearn	Simplilearn
Course Duration	11 Months	11 Months
Coding Experience Required	Basic Knowledge	Basic Knowledge
Skills You Will Learn	15+ Skills Including Core Java, SQL, AWS, ReactJS, etc.	Java, AWS, API Testing, TDD
Additional Benefits	Interview Preparation Exclusive Job Portal 200+ Hiring Partners	Structured Guid  Learn From Experts Hands-on Training

	200+ Hiring Partners	Hands-on Training
Cost	\$\$	\$\$
	<a href="#">Explore Program</a>	<a href="#">Explore Program</a>

## Conclusion

After reading these C++ interview questions you must have got an insight into various essential C++ topics. Along with the conceptual questions, you also got the idea of output-based questions, multiple-choice, and programming questions.

If you are looking to build a career in [software development](#), please check the [Full Stack Developer - MERN Stack](#) by Simplilearn. It can be the ideal solution to help you build your career in the right way.

## About the Author



Pulkit Jain

Pulkit Jain is a Product Manager for Salesforce & Payments at Simplilearn, where he drives impactful product launches and updates. With deep expertise in CRM, cloud & DevOps, and product marketing, Pulkit has a proven track record in...

[View More](#)

## Recommended Programs





**Full Stack Java Developer Masters Program**

1033 Learners

Lifetime Access\*



**Full Stack Developer - MERN Stack Masters Program**

767 Learners

Lifetime Access\*



**Java Certification Training**


15989 Learners

Lifetime Access\*


\*Lifetime access to high-quality, self-paced e-learning content.

[Explore Category](#)

## Recommended Resources



**180+ Core Java Interview Questions an...**



**KUBERNETES**

**Kubernetes Interview**

© 2009 -2025- Simplilearn Solutions.

### Acknowledgement

PMP, PMI, PMBOK, CAPM, PgMP, PfMP, ACP, PBA, RMP, SP, OPM3 and the PMI ATP seal are the registered marks of the Project Management Institute, Inc.



