

IEC 60617 · BS 7671:2018 + AMENDMENT 4:2026

UK Electrical Symbols Chart

The complete reference set for installation drawings, distribution board schedules and certificates

SYMBOLS INCLUDED

114

ABOUT THIS CHART

STANDARD	IEC 60617 — the graphical symbol standard referenced by BS 7671 Regulation 514.9.1
CATEGORIES	11 — switch, socket outlet, lighting, distribution board, safety + fire + security, containment, equipment, mechanical + hvac, solar pv + renewables, controls + bms, architectural
USE	Free to print, share and pin up — on site, in the van or in the office
ISSUED	23 August 2026
FULL REFERENCE	elec-mate.com/guides/electrical-symbols-chart — per-symbol pages with wiring context

Switch Symbols

13



One-Way Switch



Two-Way Switch



Intermediate Switch



Dimmer Switch



Double Switch (Two-Gang)



Pull-Cord Switch



Fan Isolator (3-Pole)



PIR Switch (Occupancy Sensor)



Timer Switch



Key Switch



Emergency Stop (E-Stop)



Isolator (Switch-Disconnecter)



Heater Switch (45A DP)

Socket Outlet Symbols

15



Single 13A Socket Outlet



Double 13A Socket Outlet



Fused Spur (Unswitched)



Switched Fused Spur



Unswitched Spur (Non-Fused)



Cooker Outlet (45A)



Shaver Socket



USB Socket



Data Socket (RJ45)



Telephone Socket



TV Aerial Socket



Comms Cabinet Outlet



EV Charger Outlet



Outdoor IP66 Socket



Floor Socket (Floor Box)

Lighting Symbols

13



Pendant Light



Ceiling Light (Flush)



Downlight (Recessed)



Wall Light



Bulkhead Light



Outside Light



PIR Sensor (Lighting)



Emergency Light



Twin Emergency Spot



Exit Sign



Fluorescent Fitting (Batten)



LED Strip Lighting



High Bay Light

Distribution Board Symbols



Consumer Unit



Distribution Board



Sub-Main Board



MCB (Miniature Circuit Breaker)



MCCB (Moulded Case CB)



RCD (Residual Current Device)




RCBO (RCD + MCB Combined)



SPD (Surge Protection Device)



Contactor



Main Switch / Isolator



Electricity Meter



Changeover Switch



Generator Changeover (ATS)



Busbar Chamber

Safety + Fire + Security Symbols



Smoke Detector



Heat Detector



CO Detector



Fire Alarm Sounder



Sounder + Beacon



Manual Call Point (Break Glass)



Emergency Call Point (Disabled WC)



Disabled Refuge Alarm



Motion Detector (Security)



CCTV Camera




Access Control Reader



Door Entry Panel



Door Release Button



Bell / Door Chime



Extractor Fan



Thermostat



Junction Box

Containment Symbols



Conduit



Trunking



Busbar Trunking



Cable Tray



Cable Tray Drop



Floor Trunking



Underfloor Trunking



Vertical Riser



Floor Box (Multi-Service)

Equipment Symbols

9



Electric Motor



Transformer



UPS (Uninterruptible Power Supply)



Sub-Main



Industrial Fan



Pump



Air Handling Unit (AHU)



Lift / Elevator



Panel Board (Motor Control Centre)

Mechanical + HVAC Symbols

8



Boiler



Water Heater (Immersion)



Panel Heater



Air Conditioning Unit



Fan Coil Unit (FCU)



Electric Towel Rail



Heater (General)



Hand Dryer

Solar PV + Renewables Symbols

5



Solar PV Panel



PV Inverter



Battery Storage



EV Distribution Board



Generator

Controls + BMS Symbols

5



BMS Controller



Control Panel



Lighting Control Module



Generic Sensor



Humidity Sensor

					
Door (Hinged Left)	Door (Hinged Right)	Double Door	Window	Stairs	North Arrow

Using these symbols on site

Reference notes — IEC 60617 as applied to UK installation drawings

WHERE THE STANDARD SITS

BS 7671 Regulation 514.9.1 requires that diagrams, charts, tables or schedules are provided for every installation, showing the type and composition of circuits and the information needed to identify protective devices. IEC 60617 is the graphical symbol set those drawings use.

BS EN 60617 was withdrawn — IEC 60617 is the current designation.

READING A DRAWING

- Always check the drawing's own legend first — practice varies between packages and a project legend overrides any general chart.
- Symbols show function, not physical appearance or size.
- Where a symbol is annotated (2xEM, 45A, IP66), the annotation is part of the meaning.
- This chart is a reference aid. Always work to the current edition of BS 7671.