CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

GALAXY FLEXI TAPE

FLEXXIBLE THERMO PLASTIC EXPANSION JOINT TAPE

DESCRIPTION

Galaxy Flexitape is a flexible waterproofing tape based on modified flexible thermo plastic elastomers with advanced adhesion properties. Thickness 1.5 mm the product is part of the Galaxy Expansion Joint System which includes Galaxy MEP as its adhesive in protecting the expansion joints for a durable time.

USES:

- Sealing all types of joints and cracks in many different structures and applications including:
- Tunnels and culverts
- Hydroelectric power plants
- Sewage treatment plants
- Basements
- Water retaining structures
- Drinking water reservoirs
- Sealing of Construction joints
- Cracks

PROPIERTIES	Unit	Test method	Galaxy FlexiTape
Thickness	mm	EN 1849-2	1.2
Mass per unit area	Kg/m2	EN 1849-2	1.5
Water tightness		EN 1928 (B)	Pass
Tensile strength to Break	N/5cm	EN 12311-2 (A	≥ 1100
Elongation to Break	%	EN 12311-2 (A)	≥ 15
Impact resistance	mm	EN 12691 (A	≥ 450
Static puncture resistance	kg	EN 12730	≥ 20
Tear resistance	N	EN 12310-2	≥ 200
Joint peel resistance	N/50 mm	EN 12316-2	≥ 200
Joint shear resistance	N/50 mm	EN 12317-2	> 600
Foldability at low temperatures	ºC	EN 495-5	≤ - 25
Root resistance		EN 13948	Pass
Artificial aging due to prolonged exposure to UV radiation high temperatures and water	Visual (1000h)	EN 1297	Pass
Dimension stability	%	EN 1107-2	≤ 0.5
Water vapor transmission properties	µ	EN 1931	20000

CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

CHARACTERISTICS / ADVANTAGES

- Advanced adhesion, no activation on site required
- Highly flexible - high crack and joint bridging ability
- Good chemical resistance
- Good resistance to ageing
- Resistant to UV exposure
- Resistant to root penetration
- Performs well within a wide range of temperatures
- Plasticizer-free
- Hot air weld able
- Can be used in contact with potable/drinking water

PRODUCT INFORMATION

Chemical Base:	Modified modified flexible thermo plastic elastomers
Packaging:	1 roll of 25 Mtr lengths (Refer to price list for packaging variations)
Appearance / Colour:	Flexible light grey membrane
Effective Thickness:	1.2 mm (-5 % / +10 %)
Mass per Unit Area:	1250 g/m2 (-5 % / +10 %) (EN 1850-2)
Width:	10, 15, 20, 25, 30, 40, 50, 100, 200 cm Length 25 m roll
Shelf Life:	36 months from date of production

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.