CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

POLYBOND SBR™

MULTIPURPOSE SBR LATEX FOR REPAIR, BONDING AND WATERPROOFING

PRODUCTDESCRIPTION

POLYBOND SBR is a single component speciality Styrene Butadiene Latex synthetic rubber emulsion which can be used in cementitious formulation for repair of mortar, damaged concrete, flooring,bonding and waterproofing and other concrete modification purposes. It improves elasticity, flexibility, tensile strength of cement and reduces cracking there by making the mortar waterproof and reducing susceptibility to acids and gases, salt penetration etc. It reduces viscosity of cement injection grout and improves bond cured injected material with substrates.

Appearance	Milky white pourable liquid
Emulsifying System	Synthetic anionic and nonionic
Total Solids (%)	48 ± 2
pH at 25 ^{0}C	9.5 ± 0.5
Viscosity LVF (CPS) SP.1,12 RPM at 25 ^{0}C	80 - 300
Surface Tension (Dynes/cm) at 25 ^{0}C	40 ± 5
Specific Gravity	1.023 ± 0.005
Dilutability with water	Can be diluted in any proportion
Compatibility	Compatible with Cement and Concrete mixture
Coverage	0.5 kg / sqm ^{2}

AREA OF APPLICATION

POLYBOND SBR is used for modification of hydraulic binders in common applications like repair mortar, flooring, rendering, bonding,mineral sealing slurries and as cement based adhesives

For waterproofing of roof slabs, sunken slabs, basements, water tanks, sunshades etc in combination with cement

As a bonding agent for used in repair and plastering

For making polymer mortar for repairs etc

Treatment for leaching and salt penetration

Multipurpose mortar admixture for injection grouts

ADVANTAGES

Provides excellent water impermeability

Good workability at reduced water/cement ratio

Improved bonding and adhesion to substrates

Superior toughness and flexibility

Can be applied in thinner sections

Improved abrasion resistant flooring

Highly durable waterproof cementitious system against UV

CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

APPLICATION METHODOLOGY

SURFACE PREPARATION: Surface should be clean and free from dust, oil and grease and should be saturated surface dry. **MIX PROPORTIONS:** Mix **POLYBOND SBR** in the following ration and proportions as per the applications.

Repair / Patch mortar - 5% to the total value of cement sand mortar.

Bonding Agent - 15 % to the total value of cement sand mortar. **Corrosion Protection Slurry -** In a ration 1:2 to cement.

Injection Grouting - 25 % to the total value of cement.

PACKAGING

Available in 1kg and 5kg PVC container

STORAGE

Store the material in cool and dry place.

Shelf Life is 1 year in unopened containers

CIVILTECH CONSTRUCTION CHEMICALS INDIA PVT. LTD.

Plot No. 125/126, Sardar Patel Colony, Trimulgherry, Secunderabad-500 015.

Ph: +91 8978785341, Off: +91 8978645341 **Email: mailtociviltech@gmail.com**