CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

# GALAXY FLEXI TAPE

## FLEXXIBLE THERMO PLASTIC EXPANSION JOINT TAPE

DESCRIPTION

Galaxy Flexitape is a flexible waterproofing tape based on modified flexible thermo plastic elastomers with advanced adhesion properties. Thickness 1.5 mm the product is part of the Galaxy Expansion Joint System which includes Galaxy MEP as its adhesive in protecting the expansion joints for a durable time.

USES:

- Sealing all types of joints and cracks in many different structures and applications including:
- Tunnels and culverts
- Hydroelectric power plants
- Sewage treatment plants
- Basements
- Water retaining structures
- Drinking water reservoirs
- Sealing of Construction joints
- Cracks

| PROPIERTIES | Unit | Test method | Galaxy FlexiTape |
|---|---|---|---|
| Thickness | mm | EN 1849-2 | 1.2 |
| Mass per unit area | Kg/m2 | EN 1849-2 | 1.5 |
| Water tightness | | EN 1928 (B) | Pass |
| Tensile strength to Break | N/5cm | EN 12311-2 (A | ≥ 1100 |
| Elongation to Break | % | EN 12311-2 (A) | ≥ 15 |
| Impact resistance | mm | EN 12691 (A | ≥ 450 |
| Static puncture resistance | kg | EN 12730 | ≥ 20 |
| Tear resistance | N | EN 12310-2 | ≥ 200 |
| Joint peel resistance | N/50 mm | EN 12316-2 | ≥ 200 |
| Joint shear resistance | N/50 mm | EN 12317-2 | > 600 |
| Foldability at low temperatures | ºC | EN 495-5 | ≤ - 25 |
| Root resistance | | EN 13948 | Pass |
| Artificial aging due to prolonged exposure to UV radiation high temperatures and water | Visual (1000h) | EN 1297 | Pass |
| Dimension stability | % | EN 1107-2 | ≤ 0.5 |
| Water vapor transmission properties | µ | EN 1931 | 20000 |

CIVILTECH CONSTRUCTION CHEMICALS
Sustainable Solutions

CHARACTERISTICS / ADVANTAGES

- Advanced adhesion, no activation on site required
- Highly flexible - high crack and joint bridging ability
- Good chemical resistance
- Good resistance to ageing
- Resistant to UV exposure
- Resistant to root penetration
- Performs well within a wide range of temperatures
- Plasticizer-free
- Hot air weld able
- Can be used in contact with potable/drinking water

**PRODUCT INFORMATION**

| | |
|---|---|
| **Chemical Base:** | Modified modified flexible thermo plastic elastomers |
| **Packaging**: | 1 roll of 25 Mtr lengths (Refer to price list for packaging variations) |
| **Appearance / Colour:** | Flexible light grey membrane |
| **Effective Thickness:** | 1.2 mm (-5 % / +10 %) |
| **Mass per Unit Area:** | 1250 g/m2 (-5 % / +10 %) (EN 1850-2) |
| **Width:** | 10, 15, 20, 25, 30, 40, 50, 100, 200 cm Length 25 m roll |
| **Shelf Life**: | 36 months from date of production |

**BASIS OF PRODUCT DATA**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.