经典卷积网络

主讲人：龙良曲

ImageNet


Classification: ImageNet Challenge top-5 error
152 layers
22 layers
19 layers
8 layers
8 layers
shallow
3.57
6.7
7.3
11.7
16.4
25.8
28.2
ILSVRC'15 ResNet
ILSVRC'14 GoogleNet
ILSVRC'14 VGG
ILSVRC'13
ILSVRC'12 AlexNet
ILSVRC'11
ILSVRC'10

LeNet-5

- 99.2% acc.
- 5/6 layers



AT&T
LeNet 5
RESEARCH
answer: 0
0
103

LeNet5 Demo



AlexNet

- GTX 580
  - 3GBx2
- 11x11
- 8 layers

AlexNet: ILSVRC 2012 winner



- Similar framework to LeNet but:
  - Max pooling, ReLU nonlinearity
  - More data and bigger model (7 hidden layers, 650K units, 60M params)
  - GPU implementation (50x speedup over CPU)
    - Trained on two GPUs for a week
  - Dropout regularization

A. Krizhevsky, I. Sutskever, and G. Hinton,
ImageNet Classification with Deep Convolutional Neural Networks, NIPS 2012

VGG

- 3x3
- 1x1
- 11-19 layer

VGGNet: ILSVRC 2014 2nd place

ConvNet Configuration					
A	A-LRN	B	C	D	E
11 weight layers	11 weight layers	13 weight layers	16 weight layers	16 weight layers	19 weight layers
input (224 × 224 RGB image)					
conv3-64	conv3-64 **LRN**	conv3-64 **conv3-64**	conv3-64 conv3-64	conv3-64 conv3-64	conv3-64 conv3-64
maxpool					
conv3-128	conv3-128	conv3-128 **conv3-128**	conv3-128 conv3-128	conv3-128 conv3-128	conv3-128 conv3-128
maxpool					
conv3-256 conv3-256	conv3-256 conv3-256	conv3-256 conv3-256	conv3-256 conv3-256 **conv1-256**	conv3-256 conv3-256 **conv3-256**	conv3-256 conv3-256 conv3-256 **conv3-256**
maxpool					
conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512 **conv1-512**	conv3-512 conv3-512 **conv3-512**	conv3-512 conv3-512 conv3-512 **conv3-512**
maxpool					
conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512	conv3-512 conv3-512 **conv1-512**	conv3-512 conv3-512 **conv3-512**	conv3-512 conv3-512 conv3-512 **conv3-512**
maxpool					
FC-4096					
FC-4096					
FC-1000					
soft-max					

Table 2: **Number of parameters** (in millions).

Network	A,A-LRN	B	C	D	E
Number of parameters	133	133	134	138	144

- Sequence of deeper networks trained progressively
- Large receptive fields replaced by successive layers of 3x3 convolutions (with ReLU in between)



- One 7x7 conv layer with C feature maps needs $49C^2$ weights, three 3x3 conv layers need only $27C^2$ weights
- Experimented with 1x1 convolutions

K. Simonyan and A. Zisserman,
Very Deep Convolutional Networks for Large-Scale Image Recognition, ICLR 2015

1x1 Convolution

- less computation
- c_in => c_out



GoogLeNet

- 1st in 2014 ILSVRC
- 22 layers



GoogLeNet



C. Szegedy et al., Going deeper with convolutions, CVPR 2015

Stack more layers?

- 1000 layers?

CIFAR-10 experiments



下一课时

ResNet

Thank You.