

# Uintah Installation Guide

John Schmidt, Todd Harman, Jeremy Thornock,  
James Sutherland, J. Davison de St. Germain, Tony Saad

Version 2.1

# Contents

<b>1</b>	<b>Overview of Uintah</b>	<b>3</b>
1.1	Obtaining the Code . . . . .	3
<b>2</b>	<b>Installation Overview</b>	<b>3</b>
<b>3</b>	<b>Generic Library Dependencies</b>	<b>3</b>
<b>4</b>	<b>OS Version Dependencies</b>	<b>4</b>
4.1	Debian & Ubuntu Dependencies . . . . .	4
4.2	Fedora Core Dependencies . . . . .	5
4.3	CentOS Dependencies . . . . .	5
4.3.1	Boost . . . . .	6
4.3.2	CMake . . . . .	6
4.4	OpenSuse Dependencies . . . . .	6
4.5	MacOSX Dependencies . . . . .	6
<b>5</b>	<b>Hypre Installation – Required</b>	<b>7</b>
5.1	Fedora & CentOS . . . . .	7
5.2	OpenSuse . . . . .	8
<b>6</b>	<b>PETSc Installation – Optional</b>	<b>8</b>
6.1	Fedora & CentOS . . . . .	8
6.2	OpenSuse . . . . .	9
<b>7</b>	<b>Configuring and Building Uintah</b>	<b>9</b>
7.1	Configure . . . . .	9
7.1.1	Other configure options . . . . .	11
7.1.2	Common Configure Lines . . . . .	12
7.2	Build . . . . .	13
<b>8</b>	<b>Installing VisIt</b>	<b>13</b>
8.1	VisIt Installation . . . . .	13
8.1.1	Caveats . . . . .	13
8.1.2	Using the “build_visit” Script to Build VisIt . . . . .	14
8.1.3	VisIt executable . . . . .	16
8.1.4	Remote visualization . . . . .	16
8.1.5	Host Profile . . . . .	16

# 1 Overview of Uintah

The **Uintah** library is composed of several executables and a generic library framework for solving PDEs on structured AMR grids on large parallel supercomputers. *VisIt* is used to visualize data generated from **Uintah**.

## 1.1 Obtaining the Code

Uintah can be obtained either as a compressed tarball from <http://www.sci.utah.edu/uintah-survey.html> or by using Subversion (SVN) to download the latest source code:

```
svn co https://gforge.sci.utah.edu/svn/uintah/trunk uintah
```

The above command checks out the **Uintah** source tree and installs it into a directory called uintah in the users home directory.

## 2 Installation Overview

**Uintah** can be installed individually and in conjunction with the visualization tool, *VisIt*. *VisIt* has the Uintah database reader included in the build\_visit scripts.

The installation procedure follows the basic outline:

1. Install basic dependencies: MPI, Blas, Lapack, Hypre, PETSc, Boost, *etc.*
2. Configure Uintah
3. Compile Uintah
4. Install visualization tools (optional if installing on a supercomputer or first time users).

## 3 Generic Library Dependencies

**Uintah** depends on several different libraries that are commonly available or easily installable on various Linux or Unix like OS distributions.

Required libraries:

- mpi (OpenMpi, Mpich, or LAM or a vendor supplied mpi library)
- blas
- lapack
- make
- libxml2-devel
- zlib-devel
- c++
- fortran
- subversion
- cmake (version 3.1.0 or higher) – **Required for Arches/Wasatch**
- git
- boost (version 1.54 or higher) – **Required for Arches/Wasatch**
- Hypre (version 2.9.0b or higher) – **Required**
- PETSc (version 3.5.2 or higher) – **Optional**

## 4 OS Version Dependencies

### 4.1 Debian & Ubuntu Dependencies

The **Gnu/Debian** OS <http://www.debian.org> and **Ubuntu** OS <http://www.ubuntu.org> offer the vast majority of libraries necessary for installing **Uintah** with the exception of VisIt. Either one of these distributions are the recommended OS to install.

Installing the following libraries will ensure that all dependencies required for **Uintah** are satisfied:

```
sudo apt-get install subversion libhypr-dev petsc-dev \
libxml2-dev zlib1g-dev liblapack-dev cmake libglew-dev \
libxmu-dev g++ gfortran libboost-all-dev git \
libxrender-dev libxi-dev
```

For Debian **Jessie**, **version 8**, add the following to `/etc/apt/sources`:

```
deb http://ftp.debian.org/debian jessie-backports main non-free
contrib
```

then replace an older version of `cmake` with a newer version of `cmake` that is compatible with the Wasatch component.

```
sudo apt-get update
sudo apt-get install -t jessie-backports cmake
```

## 4.2 Fedora Core Dependencies

**Fedora Core 25** <http://fedoraproject.org/> offers all the dependencies except for PETSc and HYPRE. Install the following libraries:

```
sudo dnf install make openmpi-devel openmpi lapack-devel \
gcc-gfortran blas-devel gcc-c++ libxml2-devel subversion \
cmake tar diffutils libX11-devel libXext-devel patch wget \
mesa-libGL-devel mesa-libGLU-devel libXt-devel git boost-devel \
libXrender-devel libXi-devel python qt-devel
```

Please see section 5.1 for hypre installation instructions and section 6.1 for petsc installation instructions.

## 4.3 CentOS Dependencies

**CentOS 7** <http://www.centos.org/> is similar to **Fedora Core**. However, a more recent version of `cmake` and `boost` must be installed. Please see the sections for install `cmake` and `boost` below, along with instructions for installing `hypre` (required) and `petsc` (optional).

```
sudo yum install make openmpi-devel openmpi lapack-devel \
gcc-gfortran blas-devel gcc-c++ libxml2-devel subversion \
tar diffutils libX11-devel libXext-devel patch wget \
mesa-libGL-devel mesa-libGLU-devel libXt-devel git \
libXrender-devel libXi-devel bzip2
```

### 4.3.1 Boost

Install **Boost 1.64.0** <http://www.boost.org/users/download/>. After unzipping, then build and install boost:

```
cd path/to/boost_1_64_0
./bootstrap.sh
sudo ./b2 install
```

### 4.3.2 CMake

Install version 3.1.0 or higher of **CMake** <https://cmake.org/download/>

```
./bootstrap
make
sudo make install
```

Please see section 5.1 for hypre installation instructions and section 6.1 for petsc installation instructions.

## 4.4 OpenSuse Dependencies

**OpenSuse-Leap** <http://www.opensuse.org/> is similar to **Fedora Core**

```
sudo zypper install make openmpi-devel openmpi lapack \
gcc-fortran blas gcc-c++ libxml2-devel subversion \
cmake tar diffutils libX11-devel libXext-devel patch wget \
mesa-libGL-devel mesa-libGLU-devel libXt-devel git boost-devel \
libXrender-devel libXi-devel qt-devel glu-devel
```

Please see section 5.2 for hypre installation instructions and section 6.2 for petsc installation instructions.

## 4.5 MacOSX Dependencies

Use Macports to install the following:

```

sudo port install openssh screen dialog zlib cmake bash autoconf \
    xmlstarlet gdb gmake
sudo port install mpich
sudo port install mpich-gcc5
sudo port install lapack +gcc5
sudo port select --set mpi mpich-gcc5-fortran
sudo port select --set gcc mp-gcc5
sudo port install -s icu configure.compiler=macports-gcc-5 \
    configure.cxx_stdlib="libstdc++"
sudo port install -s boost configure.compiler=macports-gcc-5 \
    configure.cxx_stdlib="libstdc++"
sudo port install -s -v hyre +mpich

```

You will want to ensure that your path has the macports install locations before the system ones, i.e., `/opt/local/bin` before `/usr/bin`.

## 5 Hyre Installation – Required

Hyre can be installed by executing the following simplified instructions, however, if you encounter problems please refer to the hyre website for troubleshooting.

Download hyre-2.11.2 from <https://computation.llnl.gov/casc/hyre/software.html>

### 5.1 Fedora & CentOS

The following configure script assumes the location of MPI libraries are in `/usr/lib64/openmpi/lib`. Note that the `LD_LIBRARY_PATH` must be set. It is helpful to include the `/usr/lib64/openmpi/bin` in your path for the location of `mpirun` and `mpiCC`, `mpicc`, and `mpif77`.

```
cd hyre-2.11.2/src
```

```

LD_LIBRARY_PATH=/usr/lib64/openmpi/lib/ \
./configure --enable-shared \
    --prefix=/usr/local \
    --with-MPI-lib-dirs=/usr/lib64/openmpi/lib/ \
    --with-MPI-include=/usr/include/openmpi-x86_64/ \

```

```

--with-MPI-libs="mpi mpi_cxx" \
CC=/usr/lib64/openmpi/bin/mpicc \
CXX=/usr/lib64/openmpi/bin/mpic++ \
F77=/usr/lib64/openmpi/bin/mpif77

make
sudo make install

```

## 5.2 OpenSuse

```

cd hypre-2.11.2/src

./configure --enable-shared \
--prefix=/usr/local \
--with-MPI-libs="mpi mpi_cxx" \
CC=/usr/lib64/mpi/gcc/openmpi/bin/mpicc \
CXX=/usr/lib64/mpi/gcc/openmpi/bin/mpic++ \
F77=/usr/lib64/mpi/gcc/openmpi/bin/mpif77

make
sudo make install

```

## 6 PETSc Installation – Optional

PETSc can be installed by executing the following simplified instructions. Please refer to the PETSc website for comprehensive installation instructions if you encounter any difficulties.

Download petsc-v3.7.6 from <http://www.mcs.anl.gov/petsc/petsc-as/download/index.html>

### 6.1 Fedora & CentOS

The following configure script assumes the location of MPI libraries are in `/usr/lib64/openmpi/lib`. Note that the `LD_LIBRARY_PATH` must be set. It



is helpful to include the `/usr/lib/64/openmpi/bin` in your path for the location of `mpirun` and `mpiCC`, `mpicc`, and `mpif77`.

```
tar xzf petsc-3.7.6.tar.gz
cd petsc-3.7.6
```

```
LD_LIBRARY_PATH=/usr/lib64/openmpi/lib \
./configure --with-shared-libraries \
            --with-debugging=0 \
            --with-mpi-dir=/usr/lib64/openmpi/ \
            --prefix=/usr/local
```

```
make PETSC_DIR=/home/jas/petsc-3.7.6 PETSC_ARCH=arch-linux2-c-opt all
```

```
sudo make install
```

## 6.2 OpenSuse

```
tar xzf petsc-3.7.6.tar.gz
cd petsc-3.7.6
```

```
./configure --with-mpi-dir=/usr/lib64/mpi/gcc/openmpi \
            --with-shared-libraries --with-debugging=0 \
            --prefix=/usr/local
```

```
make PETSC_DIR=/home/jas/petsc-3.7.6 PETSC_ARCH=arch-linux2-c-opt all
```

```
sudo make install
```

# 7 Configuring and Building Uintah

## 7.1 Configure

The following information specifies how to run the “configure” script to prepare for building the Uintah executable. “Configure” is a program that checks the computer’s environment and looks for the location of libraries and header files, etc. When it finishes running, it will create the `configVars.mk` file

which will include all the information it has determined about the computer. The following lines show **generically** how to use “configure”.

Goto the directory `~/uintah` and create the following directories: `dbg` (debug) and `opt` (optimized)

```
cd ~/uintah-2.0
mkdir dbg opt
```

Go to the `dbg` directory and enter the following:

```
../src/configure --enable-debug --enable-all-components \
                 --enable-wasatch_3p --with-boost=[path to boost]
```

After the configuration process, type `make` to compile Uintah.

If you wish to attach a debugger to Uintah, make sure you use the `--enable-debug` configure option.

If you would like to reduce the amount of output given by the make system when making Uintah, you can set the environment variable `SCI_MAKE_BE_QUIET` to true:

```
setenv SCI_MAKE_BE_QUIET true (csh)

export SCI_MAKE_BE_QUIET=true (bash)
```

Once a debug build has finished, change to the `opt` directory and enter the following configure line:

```
../src/configure '--enable-optimize=-O3 -mfpmath=sse' \
                 --enable-all-components --enable-wasatch_3p \
                 --with-boost=[path to boost]
```

The debug/optimize flags do the following: `--enable-debug` adds “-g” to the compile line; `--enable-optimize`, if used without parameters, adds “-O2” to the compile line. Otherwise it adds the parameters specified during configure.

### 7.1.1 Other configure options

Other useful configure options are seen below. Note, depending on where libraries are installed on your system, you may or may not need to specify some (or all) of these options:

By default, Uintah does not build any simulation components (such as ICE, Arches, Wasatch, or MPM) - though Example components are built. To turn on components, use the following configure flags:

```
--enable-all-components      <= Turns on all simulation components
--enable-arches               <= Turns on Arches
--enable-ice                  <= Turns on ICE
--enable-mpm                  <= Turns on MPM
--enable-mpmice               <= Turns on MPMICE
--enable-wasatch              <= Turns on Wasatch

--enable-shared               <= Uses shared libraries (Default)
--enable-static               <= Uses static libraries
--with-mpi=/usr/lib64/openmpi <= Specifies location of MPI
--enable-64bit                <= Specifies a 32 or 64bit build
--enable-32bit
--with-petsc=/path/petsc-3.7.6      <= Specifies location of PETSc
--with-hypre=/path/hypre-2.11.2./hypre_install <= Specifies location of Hypre

F77=gfortran-4.7                <= Specifies compilers (Fortran, C, C++).
CC=/usr/bin/gcc-4.7
CXX=/usr/bin/g++-4.7
PETSC_ARCH=linux-gnu-c-real-opt <= Specifies PETSc architecture
```

```
--without-fortran      <= Turns off the use of Fortran. (Only
useful if you are not building Arches and you do not have a working
Fortran compiler on your computer.
```

Arches requires the Wasatch component to be enabled, therefore to compile the Arches and Wasatch components add:

```
--with-wasatch --with-boost=<path to boost install>, e.g. /usr
--enable-wasatch_3p
```

to the configure line.

To see a full list of all the configure options type:

```
../src/configure --help
```

## 7.1.2 Common Configure Lines

### Debian & Ubuntu

```
../src/configure --enable-debug --enable-all-components \  
--with-boost=/usr --enable-wasatch_3p F77=gfortan
```

### Fedora & CentOS

```
../src/configure --enable-debug --enable-all-components \  
--with-mpi-lib=/usr/lib64/openmpi/lib \  
--with-mpi-include=/usr/include/openmpi-x86_64 \  
--with-boost={/usr,/usr/local} --enable-wasatch_3p \  
--with-hypre=/usr/local \  
--with-petsc=/usr/local
```

### OpenSuse

```
../src/configure --enable-debug --enable-all-components \  
--with-mpi-lib=/usr/lib64/openmpi/lib \  
--with-mpi-include=/usr/include/openmpi-x86_64 \  
--with-boost=/usr --enable-wasatch_3p \  
--with-hypre=/usr/local \  
--with-petsc=/usr/local
```

### MacOSX

```
../src/configure --enable-debug --enable-all-components \  
--with-boost=/opt/local --enable-wasatch_3p \  
--with-hypre=/opt/local --with-lapack=/opt/local \  
--with-zlib=/opt/local \  
CXX=mpicxx CC=mpicc F77=mpif77
```

## 7.2 Build

Then build the software by typing `make` at the command line and create symbolic links to the inputs directory found in `~/uintah/src/StandAlone/inputs`.

`make`

Please see the **User Guide** <http://www.uintah.utah.edu/trac/chrome/site/uintah.pdf> on how to use the various tools and executables within the **Uintah** framework.

## 8 Installing VisIt

Visualization of **Uintah** data is currently possible using **VisIt**. The VisIt package from LLNL is general purpose visualization software that offers all of the usual capabilities for rendering scientific data. It is still developed and maintained by LLNL staff, and its interface to **Uintah** data is supported by the Uintah team.

**VisIt** may be downloaded from the following <https://wci.llnl.gov/simulation/computer-codes/visit/executables>.

### 8.1 VisIt Installation

The latest official release of **VisIt** is 2.12.2. However, the instructions apply to earlier versions such as 2.12.X. Using the `build_visit` script along with the `-uintah` option, UDA reader plugin can be built. **VisIt** can be installed either from one of their binary distributions, or by compiling and installing it from source. You may also need to build **VisIt** from source (using the `build_visit` script) if a binary is not provided for your exact OS and MPI versions and is the recommended installation method outlined below.

#### 8.1.1 Caveats

- Before you install **VisIt**, a number of dependency files are required. These include X11, GL, GLU, GLX, and libz libraries (it is possible that you will find these libraries in the following rpms: `libx11-dev`, `libxext-dev`, `libxt-dev`, `libglu`, `zlib-dev` – notice that most of these are the 'development' rpm). You can either install these directly and hope

you get them right, or you can install the files listed here in Section 4 (which will pull in all the libraries that you need).

- MPI must be installed and the MPI compilers (mpicc, etc) must be in your path.
- The **VisIt** executable is not relocatable once it is built, so make sure you specify the correct installation location in the beginning.
- The build\_visit script may need to be patched if you encounter a glx-Ptr problem when building the VTK library. Apply the patch found in [http://visitusers.org/forum/YaBB.pl?action=downloadfile;file=VTK\\_Mesa\\_2\\_8\\_1\\_patch.txt](http://visitusers.org/forum/YaBB.pl?action=downloadfile;file=VTK_Mesa_2_8_1_patch.txt). The current releases of Debian Jessie, Ubuntu 16.04, CentOS-7, Fedora-25, and OpenSuse Leap 42 requires patching the build\_visit script.
- Building **VisIt** from scratch can take a while. As mentioned below, you can

```
tail -f
    build_visit_log
```

to watch the progress.

- If you are having problems please check the Uintah wiki page on building **VisIt** (<http://www.uintah.utah.edu/trac/wiki/visit>).

### 8.1.2 Using the “build\_visit” Script to Build VisIt

1. Download the build\_visit script from [http://portal.nersc.gov/project/visit/releases/2.12.2/build\\_visit2\\_12\\_2](http://portal.nersc.gov/project/visit/releases/2.12.2/build_visit2_12_2).
2. Change the mode of the build\_visit script so it can execute, and copy it to a VISIT directory (calling it Visit\_2.12.2 in the following description) where you will build the VisIt source code:

```
mkdir ~/Visit_2.12.2
cp build_visit_2.12.2 Visit_2.12.2
cd Visit_2.12.2
chmod +x build_visit_2.12.2
```

3. Build the VisIt source (after it downloads everything) using two processors (or use the number of available processors on your machine). This will take a long time since all the prerequisite software will be downloaded and compiled. Select the 'parallel' option when the script starts up. You will need to set the `PAR_COMPILER` and `PAR_COMPILER_CXX` environment variables to the location of `mpicc` and `mpic++`, i.e.

```
export PAR_COMPILER='which mpicc' (bash)
export PAR_COMPILER_CXX='which mpic++' (bash)
setenv PAR_COMPILER 'which mpicc' (csh)
setenv PAR_COMPILER_CXX 'which mpic++' (csh)
```

```
./build_visit2_12_2 --makeflags -j6 --uintah --alt-uintah-dir ~/uintah/opt
```

For Fedora 25 and OpenSuse Leap, use the system Qt version, with the following build line:

```
./build_visit2_12_2 --makeflags -j6 --uintah --alt-uintah-dir
~/uintah/opt --system-qt
```

4. After VisIt finishes building, go into the `visit2.12.2/src` directory and make a binary distribution for it so it can be installed.

```
cd visit2.12.2/src
make package
```

Within the `visit2.12.2/src` directory there should be a gzip'd tar file that can be installed in different location

```
ls visit2.12.2/src
. . .
visit2_12_2.linux-x86_64.tar.gz
. . .
```

5. Copy the gzip'd tar file to another location and install VisIt (using the `visit-install` script found in `Visit_2.12.2/visit2.12.2/src/svn_bin/visit-install`) in the directory *visit\_bin\_dir*.

```

cp visit2_12_2.linux-x86_64.tar.gz ~/
cd ~/
~/Visit_2.12.2/visit2.12.2/src/svn_bin/visit-install 2.12.2 linux-x86_64
visit_bin_dir

```

### 8.1.3 VisIt executable

After a successful build, the executable will be placed in,

“`visit_bin_dir`”/bin/

where “`visit_bin_dir`” is the directory specified either for the `visit_install` script if using a prebuilt binary, or for `cmake` if building VisIt from source.

### 8.1.4 Remote visualization

In order to read data on a remote machine, you will need to have a version of VisIt and the UDA reader plugin installed on that machine. You will also need to make sure that the VisIt executable is in your path. You may need to edit your shell’s `.rc` file so that the path to VisIt is included in your shell’s `PATH` variable.

NOTE: The version of VisIt installed on your local desktop and the remote machine should be the same.

### 8.1.5 Host Profile

Next you will want to set up a Host Profile for your remote machine. Select ‘Host Profiles’ from the ‘Options’ menu and set up a new profile as shown in Figure 1.

After filling in the remote machine information, select the ‘Advanced options’ tab, then ‘Networking’ and check the ‘Tunnel data connections through SSH’ option. This is illustrated in figure 2a. Click on ‘Apply’ and then do a ‘Save Settings’ in the ‘Options’ menu on the gui.





Figure 1: Setting up Host Profile




For the remote visualization option to work, you must have ports 5600 - 5609 open. You can try this by running the following on your local desktop (on Linux distributions),

```
tracert -p 560[0-9] <remote machine>
```



(a) Setting up advance options



(b) Setting up advance options

Figure 2:

If the tunneling option doesn't work, try the option as shown in Figure 2b. Now you should be able to select 'Open' from VisIt's 'File' menu. After selecting your host from the host entry list, you will be prompted for a password on the remote machine (unless you have set up passwordless ssh access).

Once the ssh login has completed, you should see the directory listing. You can then change directories to your UDA and load the data.