





SINGLE USE ELECTRONIC FLEXIBLE CHOLEDOCHOSCOPE FOR LAPAROSCOPIC SURGERY







- *High Resolution Image
- *Dual light guides facilitate bright, even illumination
- *Three scope models available with a range of outer diameters and channel sizes
- *Raptor sterile single use instruments eliminate cross infection potential associated with re-useable instruments
- *Raptor sterile single use instruments eliminate costly and lengthy repairs that are commonly found with re-useable instruments in addition to significant reprocessing costs as experienced with re-useable endoscopes





Field of view
Depth of view
Deflection up/down
Insertion dia.
Distal end diam
Working length
Working channel

CHV-100-E standard 110° 5-50mm 210°/130° 4.7mm 4.7mm 385mm 2.2mm CHV-100T-E therapeutic 110° 5-50mm 210°/130° 5.3mm 5.3mm 385mm 2.6mm

CHV-US100-H ultraslim 110° 5-50mm 120°/120° 3.0mm **3.0mm** 670mm 1.2mm



Image Process Specification		
Power	Voltage	100240 VAC
Frequency	50/60 Hz	
Rated input	45 VA	
Illumination	Lamp	2W LED
Color temperature	3,000K-7,00	00K
Function	White balance, Luminance control(+-)	
	Enhance(0,1	l,2), Zoom(x1,x2,x3),
	Freeze, Sna	p, Record, USB storage)
Output	DVI*1, S-Video*1, CVBS*1	
Storage	USB (FAT 32)	
Dimensions	350mm(W) * 130mm(H) * 425mm(D)	
Weight	8 kg	

