

Package ‘geohabnet’

September 28, 2023

Title Analysis of Cropland Connectivity

Version 1.0.0

Date 2023-09-22

Description Geographical spatial analysis of cropland connectivity.,
Allows users to visualize risk index plots for a given set of crops.
The functions are developed as an extension to analysis from 10.1093/biosci/biaa067.
The primary function is `'sean()'` and is indicative of how sensitive analysis is to parameters using kernel models.
Package currently supports crops sourced from 'monfreda' and 'mapspam'.
This analysis produces 3 maps - mean, variance, and difference for the crop risk index.
There are multiple ways in which functions can be used -
generate final outcome and then the intermediate outcomes for more sophisticated use cases.
Refer to vignettes.
`'sean()'` will set some global variables which can be accessed using `{the$}` prefix. These values are propagated to other functions for performing operations such as distance matrix calculation.
`'parameters.yaml'` stores the parameters and values and can be accessed using `{link{get_parameters}()}`. Refer it's usage.

License GPL-3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports config (>= 0.3.1),
geodata (>= 0.5.8),
geosphere (>= 1.5.18),
igraph (>= 1.4.2),
terra (>= 1.7.29),
easycsv (>= 1.0.8),
yaml (>= 2.3.7),
stats (>= 4.2.3),
stringr (>= 1.5.0),
memoise (>= 2.0.1),
graphics (>= 4.2.3),
rlang (>= 1.1.1),
viridisLite (>= 0.4.2),
beepr (>= 1.3),
rnaturalearth (>= 0.3.3)

Suggests devtools,
knitr,
lintr (>= 3.0.2),
mockthat (>= 0.2.8),
rmarkdown,
testthat (>= 3.1.7)

URL <http://geohab-site.s3-website.us-east-2.amazonaws.com/docs/>,
<https://github.com/GarrettLab/CroplandConnectivity/tree/main/geohabnet/>,
<https://www.garrettlab.com/>

BugReports <https://github.com/GarrettLab/CroplandConnectivity/issues>

VignetteBuilder knitr

R topics documented:

ccri_diff	3
ccri_mean	3
ccri_variance	4
connectivity	4
cropharvest_rast	5
crops_rast	6
dist_methods	6
geoscale_param	7
get_parameters	7
get_param_metrics	8
get_rasters	8
get_supported_sources	9
global_scales	9
load_parameters	10
model_powerlaw	10
nn_sum	11
reset_params	12
reso	13
sa_onrasters	13
sean	14
search_crop	16
sensitivity_analysis	16
set_global_scales	17
set_parameters	18
set_reso	18
sp_rast	19
supported_metrics	20
tiff_torast	20

ccri_diff	<i>Calculate difference map</i>
-----------	---------------------------------

Description

This function produces a map of difference b/w mean and sum indexes in rank of cropland harvested area fraction.

Usage

```
ccri_diff(rast, x, y, global, geoscale, res = reso())
```

Arguments

rast	A raster object for mean index raster difference
x	A raster object for cropland harvest
y	A raster object for cropland harvest
global	logical. TRUE if global analysis is required, FALSE otherwise. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	vector. geographical scale
res	numeric. map resolution

ccri_mean	<i>Calculate mean of raster objects</i>
-----------	---

Description

Wrapper for [terra::mean\(\)](#). Calculates mean of list of rasters.

Usage

```
ccri_mean(indexes, global = TRUE, geoscale = NULL, plt = TRUE)
```

Arguments

indexes	list of rasters. See details.
global	logical. TRUE if global analysis is required, FALSE otherwise. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	vector. geographical scale
plt	TRUE if need to plot mean map, FALSE otherwise and geoscale.

ccri_variance	<i>Calculate variance of CCRI</i>
---------------	-----------------------------------

Description

This function produces a map of variance of CCRI based on input parameters

Usage

```
ccri_variance(indexes, rast, global, geoscale, res = reso())
```

Arguments

indexes	list of rasters. See details.
rast	A raster object. It will be used in calculating variance.
global	logical. TRUE if global analysis is required, FALSE otherwise. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	vector. geographical scale
res	numeric. map resolution

connectivity	<i>Calculate and plot maps</i>
--------------	--------------------------------

Description

Calculate mean, variance and difference. The result is produced in form of maps plotted with predefined settings. Currently, the settings for plot cannot be customized. Default value is TRUE for all logical arguments

Usage

```
connectivity(
  indexes,
  global = TRUE,
  geoscale,
  res = reso(),
  pmean = TRUE,
  pvar = TRUE,
  pdiff = TRUE
)
```

Arguments

indexes	list of rasters. See details.
global	logical. TRUE if global analysis is required, FALSE otherwise. When TRUE, geoscale is ignored. Default is TRUE.
geoscale	vector. geographical scale
res	numeric. map resolution
pmean	TRUE if map of mean should be plotted, FALSE otherwise.
pvar	TRUE if variance map should be plotted, FALSE otherwise
pdiff	TRUE if difference map should be plotted, FALSE otherwise

Details

indexes are actually risk resulting from operations on crop's raster and parameters provided in either parameters.yaml or [sean\(\)](#).

It will save all the opted plots using - pmean, pvar and pdiff. File will be saved in [getwd\(\)](#). If [interactive\(\)](#) is TRUE, then plots can be seen in active plot window. E.g. Rstudio

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland Connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, \@url<https://doi.org/10.1093/biosci/>

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, \@url<https://CRAN.R-project.org/package=terra>

cropharvest_rast	<i>Get raster object for crop</i>
------------------	-----------------------------------

Description

Get cropland information in a form of raster object from data source for crop

Usage

```
cropharvest_rast(crop_name, data_source)
```

Arguments

crop_name	Name of the crop
data_source	Data source for cropland information

Value

Raster object

Examples

```
## Not run:
cropharvest_rast("avocado", "monfreda")

## End(Not run)
```

crops_rast	<i>Get sum of rasters for individual crops</i>
------------	--

Description

Takes crop names and returns raster object which is sum of raster of individual crops. Currently, only supports crops listed in [geodata::monfredaCrops\(\)](#), [geodata::spamCrops\(\)](#) If crop is present in multiple sources, then their mean is calculated.

Usage

```
crops_rast(crop_names)
```

Arguments

crop_names A named list of source along with crop names

Value

SpatRaster. Raster object which is sum of all the individual crop rasters

Examples

```
## Not run:
crops_rast(list(monfreda = c("wheat", "barley"), mapspam = c("wheat", "potato")))

## End(Not run)
```

dist_methods	<i>Distance methods supported</i>
--------------	-----------------------------------

Description

Contains supported strategies to calculate distance between two points. Use of one the methods in [sean\(\)](#) or [sensitivity_analysis\(\)](#).

Usage

```
dist_methods()
```

Value

vector

geoscale_param	<i>Get geographical scales from the parameters</i>
----------------	--

Description

This function returns a list of geographical scales set in global and custom extent in `parameters.yaml`. If `global` is `TRUE`, the `CustomExt` is ignored.

Usage

```
geoscale_param()
```

Value

A list of geographical scales

get_parameters	<i>Get Parameters</i>
----------------	-----------------------

Description

Retrieves the parameters and copies the parameter file to the specified output path.

Usage

```
get_parameters(out_path = getwd(), iwindow = FALSE)
```

Arguments

out_path	character. The output path where the parameter file will be copied. Default is current working directory getwd()
iwindow	logical. If <code>TRUE</code> , prompts the user to select the output directory using a file chooser window. Default is <code>FALSE</code>

Details

Using configuration file is an alternative to [sean\(\)](#)

Value

character. The path to the copied parameter file.

See Also

[set_parameters\(\)](#)

get_param_metrics	<i>Get metrics from parameters</i>
-------------------	------------------------------------

Description

Get metrics and parameters stored in `parameters.yaml`.

Usage

```
get_param_metrics(params = load_parameters())
```

Arguments

`params` R object of [load_parameters\(\)](#). Default is `load_parameters()`.

Value

List of metrics - parameters and values. See usage.

Examples

```
# Get metrics from parameters
get_param_metrics()
get_param_metrics(load_parameters())
```

get_rasters	<i>Get rasters object from parameters</i>
-------------	---

Description

Takes named list of hosts as an input. See host object in [get_parameters\(\)](#) or [load_parameters\(\)](#). This is also a wrapper of [crops_rast\(\)](#). Function creates 2 raster object - one is a sum of all the crops specified under sources and other using the provided raster file. See [tiff_torast\(\)](#)

Usage

```
get_rasters(hosts)
```

Arguments

`hosts` List of hosts and values. It is synonym to Hosts object in parameters

Value

List of SpatRaster.

See Also

[load_parameters\(\)](#), [get_parameters\(\)](#), [tiff_torast\(\)](#), [cropharvest_rast\(\)](#)

Examples

```
# Get default rasters
## Not run:
get_rasters(list(mapspam = c("wheat"), monfreda = c("avocado"), file = "some_raster.tif"))

## End(Not run)
```

get_supported_sources *Get supported sources of crops*

Description

When provided, `cropharvest_rast()` will look for cropland data in this specific source.

Usage

```
get_supported_sources()
```

Value

return vector of supported sources. Also used as a lookup to find get raster object.

Examples

```
# Get currently supported sources
get_supported_sources()
```

global_scales *Global geographical extent*

Description

See geographical extents used in global analysis. Returns eastern and western hemisphere extents. Each extent is in the form of `c(Xmin, Xmax, Ymin, Ymax)`.

Usage

```
global_scales()
```

See Also

```
set\_global\_scales\(\)
```

load_parameters	<i>Load Parameters from YAML File</i>
-----------------	---------------------------------------

Description

This function loads parameters from a YAML file and stores them in an object.

Usage

```
load_parameters(filepath = .get_helper_filepath(.kparameters_file_type))
```

Arguments

filepath	Path to the YAML file containing the parameters. By default, it takes the value of ".kparameters_file_type" which is set to "parameters.yaml".
----------	--

Value

object with parameters and values

Examples

```
# Load parameters from default file
load_parameters()
```

model_powerlaw	<i>Calculate risk index using inbuilt models.</i>
----------------	---

Description

- `model_powerlaw()` calculates risk index using power law.
- `model_neg_exp()` calculates risk index using negative exponential.

Usage

```
model_powerlaw(
  beta,
  link_threshold,
  distance_matrix = the$distance_matrix,
  thresholded_crop_values,
  adj_mat = NULL,
  crop_raster,
  crop_cells_above_threshold,
  metrics = the$parameters_config$`CCRI parameters`$NetworkMetrics$InversePowerLaw
)

model_neg_exp(
  gamma_val,
  link_threshold,
```

```

distance_matrix = the$distance_matrix,
thresholded_crop_values,
adj_mat = NULL,
crop_raster,
crop_cells_above_threshold,
metrics = the$parameters_config$`CCRI parameters`$NetworkMetrics$InversePowerLaw
)

```

Arguments

beta	A list of beta values. DispersalParameterBeta in parameters.yaml.
link_threshold	A threshold value for link.
distance_matrix	distance matrix, generated during sean() .
thresholded_crop_values	crop values above threshold.
adj_mat	Adjacency matrix(optional) representing un-directed graph network. If this is provided, then gamma_val, distance_matrix, link_threshold and thresholded_crop_values are ignored. These ignored parameters are used to generate adjacency matrix internally. This is the only way to use custom adjacency matrix.
crop_raster	A raster object for cropland harvest.
crop_cells_above_threshold	crop cells above threshold. Only contains cells and not the the values.
metrics	A list 2 vectors - metrics and weights.
gamma_val	A list of beta values. DispersalParameterGamma in parameters.yaml.

Details

Network metrics should be passed as a list of vectors e.g. `list(metrics = c("betweenness"), weights = c(100))`. Default values are fetched from parameters.yaml and arguments uses the same structure.

Value

risk index

nn_sum	<i>Calculation on network matrix.</i>
--------	---------------------------------------

Description

These are basically an abstraction of functions under the [igraph](#) package. The functions included in this abstraction are:

- `nn_sum()`: Calculates the sum of nearest neighbors [igraph::graph.knn\(\)](#).
- `node_strength()`: Calculates the sum of edge weights of adjacent nodes [igraph::graph.strength\(\)](#).
- `betweenness()`: Calculates the vertex and edge betweenness based on the number of geodesics [igraph::betweenness\(\)](#).
- `ev()`: Calculates the eigenvector centrality of positions within the network [igraph::evcent\(\)](#).

- `closeness()`: measures how many steps is required to access every other vertex from a given vertex [igraph::closeness\(\)](#).
- `degree()`: number of adjacent edges [igraph::degree\(\)](#).
- `pagerank()`: page rank score for vertices [igraph::page_rank\(\)](#).

Usage

```
nn_sum(crop_dm, we)

node_strength(crop_dm, we)

betweenness(crop_dm, we)

ev(crop_dm, we)

degree(crop_dm, we)

closeness(crop_dm, we)

pagerank(crop_dm, we)
```

Arguments

<code>crop_dm</code>	Distance matrix. In the internal workflow, the distance matrix comes is a result of operations within sean() and risk functions.
<code>we</code>	Weight in percentage.

Value

Matrix with the mean value based on the assigned weight.

See Also

Other metrics: [supported_metrics\(\)](#)

<code>reset_params</code>	<i>Reset parameters.yaml</i>
---------------------------	------------------------------

Description

Resets the values in the `parameters.yaml` file to the default initial values.

Usage

```
reset_params()
```

Examples

```
## Not run:
reset_params()

## End(Not run)
```

reso	<i>Get resolution value</i>
------	-----------------------------

Description

Resolution stored in parameter .yaml. If not present it will result default value.

Usage

```
reso()
```

See Also

[set_reso\(\)](#)

sa_onrasters	<i>Run sensitivity analysis</i>
--------------	---------------------------------

Description

Same as [sensitivity_analysis\(\)](#) but it takes raster object and other parameters as an input.

Usage

```
sa_onrasters(
  rast,
  global = TRUE,
  geoscale,
  link_thresholds,
  host_density_thresholds,
  agg_methods = c("sum", "mean"),
  dist_method = "geodesic",
  res = reso(),
  maps = TRUE
)
```

Arguments

rast	Raster object which will be used in analysis.
global	Logical. TRUE if global analysis, FALSE otherwise. Default is TRUE
geoscale	Vector. Geographical coordinates in the form of c(Xmin, Xmax, Ymin, Ymax)
link_thresholds	vector. link threshold values
host_density_thresholds	vector. host density threshold values
agg_methods	vector. Aggregation methods
dist_method	character. One of the values from dist_methods()
res	numeric. resolution at which operations will run. Default is reso()
maps	logical. TRUE if maps are to be plotted, FALSE otherwise

Details

When `global = TRUE`, `geo_scale` is ignored. Instead uses scales from `global_scales()`.

Value

A list of calculated CCRI indices after operations. An index is generated for each combination of paramters. One combination is equivalent to `sean()` function.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland Connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, \@urlhttps://doi.org/10.1093/biosci/

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, \@urlhttps://CRAN.R-project.org/package=terra

See Also

Use `get_rasters()` to obtain raster object.

Examples

```
## Not run:
rr <- get_rasters(list(monfreda = c("avocado")))
sa_onrasters(rr[[1]],
             global = FALSE,
             geoscale = c(-115, -75, 5, 32),
             c(0.0001, 0.00004),
             c(0.0001, 0.00005),
             c("sum", "mean"),
             res = 24)
sa_onrasters(rr[[1]],
             global = TRUE,
             link_thresholds = c(0.000001),
             host_density_thresholds = c(0.00015),
             agg_methods = c("sum"),
             res = 24)

## End(Not run)
```

sean

Calculate sensitivity analysis on cropland harvested area fraction

Description

This function calculates sensitivity analysis on cropland harvested area fraction based on provided parameters. Some parameters are only accessible from `paramters.yaml` and uses value from here

Usage

```
sean(
  rast,
  global = TRUE,
  geoscale,
  agg_methods = c("sum", "mean"),
  dist_method = "geodesic",
  link_threshold = 0,
  host_density_threshold = 0,
  res = reso(),
  maps = TRUE
)
```

Arguments

<code>rast</code>	Raster object which will be used in analysis.
<code>global</code>	Logical. TRUE if global analysis, FALSE otherwise. Default is TRUE
<code>geoscale</code>	Vector. Geographical coordinates in the form of <code>c(Xmin, Xmax, Ymin, Ymax)</code>
<code>agg_methods</code>	vector. Aggregation methods
<code>dist_method</code>	character. One of the values from dist_methods()
<code>link_threshold</code>	numeric. A threshold value for link
<code>host_density_threshold</code>	A host density threshold value
<code>res</code>	numeric. resolution at which operations will run. Default is reso()
<code>maps</code>	logical. TRUE if maps are to be plotted, FALSE otherwise

Details

When `global = TRUE`, `geoscale` is ignored and [global_scales\(\)](#) is used

Value

A list of calculated CCRI values using negative exponential

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland Connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, \@url<https://doi.org/10.1093/biosci/>

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, \@url<https://CRAN.R-project.org/package=terra>

See Also

Uses [connectivity\(\)](#)

Examples

```
## Not run:
avocado <- cropharvest_rast("avocado", "monfreda")
risk_indexes <- sean(avocado)

## End(Not run)
```

search_crop	<i>Search for crop</i>
-------------	------------------------

Description

It returns the dataset sources in which crop data is available. It's a wrapper around [geodata::spamCrops\(\)](#) and [geodata::monfredaCrops\(\)](#)

Usage

```
search_crop(name)
```

Arguments

name	name of crop
------	--------------

See Also

[get_supported_sources\(\)](#)

Examples

```
search_crop("coffee")
search_crop("wheat")
## Not run:
search_crop("jackfruit")

## End(Not run)
```

sensitivity_analysis	<i>Calculate sensitivity analysis on parameters</i>
----------------------	---

Description

This function runs sensitivity analysis on parameters based on parameters provided through [set_parameters\(\)](#). It can be used as an entry point for CCRI. By default, it runs analysis on global scales [global_scales\(\)](#). After analysis is complete, it will suppress maps for outcomes if `maps = FALSE` or [interactive\(\)](#) is `FALSE`.

Usage

```
sensitivity_analysis(maps = TRUE, alert = TRUE)
```


Arguments

maps	logical. TRUE if maps are to be plotted, FALSE otherwise
alert	logical. TRUE if beep sound is to be played, FALSE otherwise

Value

logical. TRUE if analysis is completed, FALSE otherwise. Errors are not handled.

References

Yanru Xing, John F Hernandez Nopsa, Kelsey F Andersen, Jorge L Andrade-Piedra, Fenton D Beed, Guy Blomme, Mónica Carvajal-Yepes, Danny L Coyne, Wilmer J Cuellar, Gregory A Forbes, Jan F Kreuze, Jürgen Kroschel, P Lava Kumar, James P Legg, Monica Parker, Elmar Schulte-Geldermann, Kalpana Sharma, Karen A Garrett, *Global Cropland Connectivity: A Risk Factor for Invasion and Saturation by Emerging Pathogens and Pests*, BioScience, Volume 70, Issue 9, September 2020, Pages 744–758, \url<https://doi.org/10.1093/biosci/>

Hijmans R (2023). *terra: Spatial Data Analysis*. R package version 1.7-46, \url<https://CRAN.R-project.org/package=terra>

See Also

[sa_onrasters\(\)](#) [sean\(\)](#) [global_scales\(\)](#) [get_parameters\(\)](#) [set_parameters\(\)](#) [connectivity\(\)](#)

Examples

```
## Not run:
# Run analysis on specified parameters.yaml
sensitivity_analysis()
sensitivity_analysis(FALSE, FALSE)
sensitivity_analysis(TRUE, FALSE)

## End(Not run)
```

set_global_scales	<i>Set global geographical extent</i>
-------------------	---------------------------------------

Description

Set the geographical extents used in global analysis. Each extent should be in the form of c(Xmin, Xmax, Ymin, Ymax)

Usage

```
set_global_scales(value)
```

Arguments

value	list. Named list of eastern and western hemisphere extents. See usage.
-------	--

See Also

[global_scales\(\)](#) [terra::ext\(\)](#)

Examples

```
## Not run:
set_global_scales(list(east = c(-24, 180, -58, 60), west = c(-140, -34, -58, 60)))

## End(Not run)
```

set_parameters	<i>Set Parameters</i>
----------------	-----------------------

Description

This function allows you to set the parameters by replacing the existing parameters file with a new one. Use [get_parameters\(\)](#) to modify the parameter values.

Usage

```
set_parameters(new_params, iwindow = FALSE)
```

Arguments

new_params	The path to the new parameters file.
iwindow	Logical indicating whether to prompt the user to select the new parameters file using a file selection window. Defaults to FALSE.

Value

None

set_reso	<i>Set resolution value</i>
----------	-----------------------------

Description

Set resolution to be used in analysis. It doesn't modify the parameters.yaml but instead a currently loaded instance of it. Must be greater than 0 and less than or equal to 48.

Usage

```
set_reso(value)
```

Arguments

value	numeric. Resolution value.
-------	----------------------------

Examples

```
## Not run:
set_reso(24)

## End(Not run)
```

sp_rast	<i>raster for mapspam crop.</i>
---------	---------------------------------

Description

get raster for crop in mapspam dataset

Usage

```
sp_rast(crp)
```

Arguments

crp character. name of a crop. Case-insensitive.

Details

See `geodata::spamCrops()` for supported crops.

Value

spatRaster

References

www.mapspam.com/data International Food Policy Research Institute, 2020. Spatially-Disaggregated Crop Production Statistics Data in Africa South of the Sahara for 2017. <https://doi.org/10.7910/DVN/FSSKBW>, Harvard Dataverse, V2

See Also

`geodata::spamCrops()` `search_crop()`

Examples

```
## Not run:  
sp_rast("rice")  
  
## End(Not run)
```

supported_metrics	Returns metrics currently supported in the analysis.
-------------------	--

Description

Returns metrics currently supported in the analysis.

Usage

```
supported_metrics()
```

Value

vector of supported metrics.

See Also

Other metrics: [nn_sum\(\)](#)

Examples

```
supported_metrics()
```

tiff_torast	Get raster object from tif file
-------------	---------------------------------

Description

This is a wrapper of [terra::rast\(\)](#) and generates a raster object if provided with a TIF file.

Usage

```
tiff_torast(path_to_tif)
```

Arguments

path_to_tif TIF file

Value

SpatRaster.

Examples

```
## Not run:
# Generate raster for usage
fp <- .get_helper_filepath("avocado")
tiff_torast(fp)
tiff_torast("avocado_HarvestedAreaFraction.tif")

## End(Not run)
```