

Exception Handling Review

I have a Java class in my project that I want to follow Java Solid Principles. Infer the class's responsibility and look for ways to improve it, ONLY if applicable.

...

```
package com.toolstore.demo.exception;

import org.springframework.http.ResponseEntity;
import org.springframework.validation.FieldError;
import
org.springframework.web.bind.MethodArgumentNotValidException
;
import
org.springframework.web.bind.annotation.ExceptionHandler;
import
org.springframework.web.bind.annotation.RestControllerAdvice;

import java.util.stream.Collectors;
```

```
@RestControllerAdvice
public class GlobalExceptionHandler {

    @ExceptionHandler(IllegalArgumentException.class)
    public ResponseEntity
handleValidationException(IllegalArgumentException ex) {
        System.err.println("Checkout Validation Failed: " +
ex.getMessage());
        return ResponseEntity.badRequest().body(new
ErrorResponse(ex.getMessage()));
    }

    @ExceptionHandler(MethodArgumentNotValidException.class)
    public ResponseEntity
handleMethodArgumentNotValid(MethodArgumentNotValidExceptio
n ex) {
        String message = ex.getBindingResult()
            .getFieldErrors()
            .stream()
            .map(FieldError::getDefaultMessage)
            .collect(Collectors.joining(", "));

        System.err.println("Request Body Invalid: " + message);
        return ResponseEntity.badRequest().body(new
```

```

ErrorResponse(message));
    }

    @ExceptionHandler(Exception.class)
    public ResponseEntity handleGeneralException(Exception ex) {
        System.err.println("An unexpected error occurred: " +
ex.getMessage());
        ex.printStackTrace(); // Useful for a console-based demo
        return ResponseEntity.internalServerError().body(new
ErrorResponse("An internal error occurred."));
    }
}

```

RouteLLM

Based on the provided code and the **Toolstore specification**, the `GlobalExceptionHandler` class is responsible for intercepting and formatting error responses across the application. This ensures that validation failures (like the required "Rental day count" or "Discount percent" checks) result in user-friendly messages rather than raw stack traces.

In terms of **SOLID Principles**, specifically the **Single Responsibility Principle (SRP)** and **Dependency Inversion Principle (DIP)**, there are a few areas where the class can be improved to be more robust and maintainable.

Analysis of SOLID Improvements

1. Single Responsibility Principle (SRP)

The current class handles three distinct things: intercepting exceptions, logging/printing to the console, and constructing the `ErrorResponse` body. While a `@RestControllerAdvice` is naturally a "coordinator," the use of `System.err.println` and `ex.printStackTrace()` couples the error handling logic with a specific console-based logging implementation.

2. Dependency Inversion Principle (DIP)

The class currently depends on the concrete ErrorResponse class directly. While common in small demos, in a larger system, you might want to decouple the error structure from the handler to allow for different response formats without changing the handler logic.

3. Open/Closed Principle (OCP)

If the Toolstore adds specific domain exceptions (e.g., InvalidRentalDurationException or ToolNotFoundException), you would have to keep modifying this class to add new @ExceptionHandler methods.

Recommended Improvements

Refactor Logging and Response Logic

Instead of using System.err, use a proper SLF4J Logger. Additionally, to better follow SRP, you can ensure the ErrorResponse is a simple DTO and the handler focuses strictly on the mapping logic.

Specific Exception Handling

The specification mentions specific validation requirements (Rental days < 1, Discount > 100). While IllegalArgumentException works, creating a custom ValidationException allows you to separate "Business Rule Violations" from general "Illegal Arguments" that might occur deeper in the framework.

Improved Implementation

```
package com.toolstore.demo.exception;
```

```
import org.slf4j.Logger;  
import org.slf4j.LoggerFactory;
```

```

import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.validation.FieldError;
import org.springframework.web.bind.MethodArgumentNotValidException;
import org.springframework.web.bind.annotation.ExceptionHandler;
import org.springframework.web.bind.annotation.RestControllerAdvice;

import java.time.LocalDateTime;
import java.util.stream.Collectors;

@RestControllerAdvice
public class GlobalExceptionHandler {

    private static final Logger logger =
        LoggerFactory.getLogger(GlobalExceptionHandler.class);

    // Handles Business Rule Validations (e.g., Rental days < 1, Discount % range)
    @ExceptionHandler(IllegalArgumentException.class)
    public ResponseEntity<ErrorResponse>
    handleBusinessValidation(IllegalArgumentException ex) {
        logger.error("Checkout Validation Failed: {}", ex.getMessage());
        return buildResponse(ex.getMessage(), HttpStatus.BAD_REQUEST);
    }

    // Handles JSR-303 / Spring Boot Request Body Validations
    @ExceptionHandler(MethodArgumentNotValidException.class)
    public ResponseEntity<ErrorResponse>
    handleMethodArgumentNotValid(MethodArgumentNotValidException ex) {
        String message = ex.getBindingResult()
            .getFieldErrors()
            .stream()
            .map(FieldError::getDefaultMessage)
            .collect(Collectors.joining(", "));

        logger.error("Request Body Invalid: {}", message);
        return buildResponse(message, HttpStatus.BAD_REQUEST);
    }

    // Catch-all for unexpected internal errors
    @ExceptionHandler(Exception.class)
    public ResponseEntity<ErrorResponse> handleGeneralException(Exception ex) {
        logger.error("An unexpected error occurred", ex);
        return buildResponse("An internal error occurred. Please contact support.",
            HttpStatus.INTERNAL_SERVER_ERROR);
    }

    // Helper method to centralize response creation (SRP)
    private ResponseEntity<ErrorResponse> buildResponse(String message, HttpStatus
    status) {
        ErrorResponse error = new ErrorResponse(

```

```
        message,  
        status.value(),  
        LocalDateTime.now()  
    );  
    return new ResponseEntity<>(error, status);  
}  
}
```

Key Changes Made:

- **Replaced System.err with SLF4J:** This follows best practices for enterprise Java and decouples the output stream from the logic.
 - **Centralized Response Building:** The buildResponse helper method ensures that if you ever need to add a timestamp or a "Trace ID" to your errors (as shown in the updated ErrorResponse suggestion), you only change it in one place.
 - **Improved Error Messages:** For general exceptions, it hides the raw exception message from the end-user, which is a security best practice, while still logging the full stack trace for developers.
-