

ADMINISTRATOR MANUAL: INSTALLATION AND CONFIGURATION

This volume is intended for the System Administrator (SysAdmin). The proper functioning of the Creation Terminal depends on a precise configuration of ports, absolute paths, and the correct categorization of models in the database.

SQL

MODULE I: DEPLOYMENT AND BASE CONFIGURATION (CORE)

The system features an auto-shielding mechanism upon startup that protects vital configurations and manages the server's Onboarding process.

1.1 The config.php File and Global Variables

During the initial startup, if the system does not detect a config.php file, it will automatically clone it from config.sample.php to prevent fatal critical errors (Error 500). The communication arteries are defined within this file:

- **APP_MODE:** Defines the environment (servidor [server] or local). In local mode, the system auto-assigns the session to the first administrator user and prevents login blocks.
- **LLM Connection (Ollama):** IP (127.0.0.1) and Port (11434). It is vital that Ollama is running and accepting cross-origin requests if it is hosted on another machine.
- **GPU Connection (ComfyUI):** IP, Port (8188), and the ComfyUI API key.
- **COMFY_MODELS_DIR:** The absolute physical path (e.g., F:/ComfyUI/ComfyUI/models). **Crucial:** The Civitai downloader relies on this path to know exactly where to save the files.

1.2 The Onboarding Assistant

If the models database (modelos_ia) is empty upon startup, the interface blocks user access and launches the Onboarding Modal for the administrator:

SQL

- **Network Diagnostics:** It performs a silent ping to both the Ollama and ComfyUI ports. If both return a green response, it unlocks the installation options.
- **Core Installation:** Allows downloading the base LLM brain (llama3 via Ollama) and the reference graphic model (Juggernaut X SDXL via Civitai).

1.3 Licensing System (Lemon Squeezy) and Offline Mode

The system verifies the license key stored in the usuarios table against the Lemon Squeezy API on every session startup.

SQL

- **Offline Fallback:** If the server loses internet connection (3-second timeout), the system gives the "benefit of the doubt" and maintains the PRO privileges of the local session to avoid disrupting studio workflow.

- **Revocation:** If Lemon Squeezy responds that the license has been canceled, refunded, or is invalid, the user is automatically downgraded to the Free version.

MODULE II: MODEL MANAGER (DB AND CIVITAI)

For security reasons, the Terminal does not read models directly from the folders, but rather through the `modelos_ia` table. This allows assigning unique parameters and access levels to each file.

SQL

2.1 Native Civitai Downloader

The administrator does not need to open the Windows file explorer. From the web manager, you can paste a Civitai download URL.

- **Automatic Routing:** By selecting whether it is a Checkpoint, UNET, or LoRA, the system routes the downloaded `.safetensors` file to its corresponding folder within `COMFY_MODELS_DIR`.
- **Automatic Registration:** Upon completing the download, the model is directly registered in the database and is ready to use without reloading the server.

SQL

2.2 The `modelos_ia` Table and Parameterization

Every model registered in the database has vital attributes:

SQL

- **Category and Engine:** Defines which interface tab it will appear in (SDXL, SD15, Video, Flux/Natural, Ollama).

SQL

- **ES_UNBUNDLED:** A boolean toggle (`es_unbundled`). If active, it tells the system that this file must be loaded through a UNETLoader (like FLUX or Wan) instead of the classic CheckpointLoaderSimple.

SQL

- **Default Parameters:** You can set `default_steps`, `default_cfg`, `default_sampler`, and `default_scheduler`. When this model is selected in the interface, the user's sliders and dropdowns will mutate (with a blue flash) to adjust to these optimal values.

SQL

 **THE SYS_REFINER MODEL:** For tools like ADetailer to work with heavy models (such as FLUX, Qwen, or DiTs), it is mandatory that at least one model exists in the database with its category set exactly to `sys_refiner`. This will be the model (usually a lightweight SD1.5 or SDXL) that the AI loads in the background to redraw faces.

SQL

MODULE III: THE LOGICAL BRAIN AND PROMPTS

The `personalidades_prompts` table manages all the systemic behavior of the LLM and the graphic style presets.

SQL

3.1 Types of Prompts and Personalities

The `tipo` (type) field in the database defines where and how each record is injected:

SQL

- **core_architect / vision_analyst:** The core instructions ("System Prompts") that tell Llama 3 how to behave when translating ideas into English or analyzing images.
- **chat_personality / chat_default:** Allows creating new "Roles" for the Chat tab (e.g., Screenwriter, Programmer).
- **seed_image / seed_video:** The phrases injected when the user clicks the Dice (Surprise) button.
- **estilo_sdxl, estilo_flux, estilo_video:** Injects modifiers (parameterized in JSON or objects) directly into the positive and negative boxes when the user selects an interface Preset.

3.2 Wildcard Engine

The system loads `.txt` files located on the server. If the user types `__clothing__` in the prompt, the backend will look for the `clothing.txt` file, pick a random line, and replace the variable before sending it to the GPU.

MODULE IV: OTA UPDATES AND MAINTENANCE

For distributed systems or remote servers, Garty's Architect features an integrated Over-The-Air (OTA) update system that avoids the need for FTP or command-line Git.

4.1 Checking and Downloading (GitHub)

The system silently checks the `version.json` file in the main GitHub repository. If it detects a higher version than the `APP_VERSION` variable declared in `config.php`, it enables the update button.

- It downloads a ZIP file from the repository and saves it as a temporary file (`temp_update.zip`).

4.2 Blinded Decompression

The update system iterates through the ZIP file by file but features a titanium shield (Blacklist) that prevents the overwriting of client data:

- Completely ignores the extraction of `config.php`.
- Blocks the overwriting of `.sqlite` and `.db` databases.
- Ignores any changes in the `/data/` and `/galeria/` directories, protecting all user-generated images, audio, and history.

4.3 Hot Language Manager

The administrator panel allows editing translation variables without touching the source code.

- It reads the `/lang/` folder and allows creating or modifying `.php` files (like `en.php` or `es.php`) directly from an integrated web editor.
- It saves an `idiomas_meta.json` file to map ISO codes (e.g., `ca`) to visual names for the end-user menu (e.g., `Català`).