

MATLAB Queuing Library

Juan Felipe Imbett Jiménez

October 31, 2013

1 Installation

The installation of the library is quite easy. Download the .zip file and locate it in the MATLAB root directory. Each .m file must be in your workspace, otherwise MATLAB wont understand the callback.

2 Getting started

The MATLAB Queuing Library consists of the following .m files

- jacksonNetwork.m Jackson's networks modelling.
- mmqueue.m Single queue modelling, with Poisson arrivals and Exponential service times.
- pjs.m Subroutine that calculates $P(j \geq s)$ for $M/M/s/GD/\infty/\infty$

3 mmqueue.m

This file calculates the values of L, L_q, L_s, W, W_q, W_s for a queue with exponentially distributed inter arrival times and service times. The command is the following:

$$[L, L_q, L_s, W, W_q, W_s] = mmqueue(s, \lambda, \mu, c) \quad (1)$$

Where s is the number of servers, λ is the arrival rate, μ is the service rate and c is the capacity. If the system has an infinite capacity $c = -1$. The following example shows the routine:

- System: $M/M/1/GD/5/\infty$
- $\lambda = 5$
- $\mu = 4$

The code in MATLAB is the following:

```

1
2      %Example of a M/M/1/GD/5/infty
3
4 -   clc; %Clears the console
5 -   lambda=5;
6 -   mu=4;
7 -   s=1;
8 -   c=5;
9 -   [L, Lq, Ls, W, Wq, Ws] = mmqueue( s, lambda, mu, c );
10

```

L	3.1317
Lq	2.2205
Ls	0.9112
W	0.8592
Wq	0.6092
Ws	0.2500

4 jacksonNetwork.m

This file calculates L, L_q, L_s, W, W_q, W_s for a Jackson's Network. If any assumption is violated the routine handles an error. The command is the following:

$$[L, L_q, L_s, W, W_q, W_s] = jacksonNetwork(\gamma, P, s, \mu) \quad (2)$$

Where γ is a row vector with the external arrival rates, P is the transition probability between stations, s is a row vector with the number of servers in each station, if the number of servers is infinite then $s = -1$, and μ is a row vector with service rates in each station. Consider the following example of a Jackson's network:

- 3 stations
- $\gamma = [2, 3, 0]$
- $P_{1,3} = 1, P_{2,1} = \frac{1}{2}, P_{2,3} = \frac{1}{2}, P_{3,2} = \frac{1}{2}$
- $s = [1, 2, \infty]$
- $\mu = [10, 15, 2]$

The code in MATLAB is the following:

```

1
2      %Example of a Jackson's Network
3
4 -   clc; %Clears the console
5 -   P=[0 0 1; 0.5 0 0.5; 0 0.7 0];
6 -   gamma=[2 3 0];
7 -   servers=[1 2 -1];
8 -   mu=[10 15 2];
9 -   [ L, Lq, Ls, W, Wq, Ws ] = jacksonNetwork( gamma, P , servers, mu);

```

L	23.6182
Lq	13.3738
Ls	10.2444
W	4.7236
Wq	2.6748
Ws	2.0489