

IGVF CRISPR Jamboree 2024: MuData Structure (R)

Gene Katsevich

February 23, 2024

Let us walk through the input and output format specifications, from the perspective of R, using a subset of the Gasperini et al (2019) dataset as an example.

```
library(MuData)
library(SummarizedExperiment)

inference_data_path <- "/mnt/shared/inference"
```

1 Required input fields

We start with an example of the minimal MuData object required for perturb-seq inference.

```
mudata_input_fp <- paste0(inference_data_path,
                           "/gasperini_inference_input_minimal.h5mu")
input_minimal <- readH5MU(mudata_input_fp)
input_minimal

## A MultiAssayExperiment object of 2 listed
## experiments with user-defined names and respective classes.
## Containing an ExperimentList class object of length 2:
## [1] gene: SummarizedExperiment with 112 rows and 9704 columns
## [2] guide: SummarizedExperiment with 55 rows and 9704 columns
## Functionality:
## experiments() - obtain the ExperimentList instance
## colData() - the primary/phenotype DataFrame
## sampleMap() - the sample coordination DataFrame
## `$$`, `[`, `[[]` - extract colData columns, subset, or experiment
## *Format() - convert into a long or wide DataFrame
## assays() - convert ExperimentList to a SimpleList of matrices
## exportClass() - save data to flat files
```

The minimal MuData object for perturb-seq inference contains two modalities: **gene** and **guide**.

1.1 gene modality

The minimal **gene** modality needs to just have one assay, whose name is the empty string, containing the RNA UMI counts:

```
input_minimal[['gene']]

## class: SummarizedExperiment
## dim: 112 9704
## metadata(0):
## assays(1): ''
```

```
## rownames(112): ENSG00000008853 ENSG00000104679 ... ENSG00000198899
## ENSG00000228253
## rowData names(0):
## colnames(9704): GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3 ... GGATTACCATGTTGAC-1_2A_4_SI-GA-G5
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2
## colData names(0):
```

To bring it more in line with the typical `SummarizedExperiment`, we can rename the assay as `counts`:

```
assayNames(input_minimal[['gene']]) <- 'counts'
input_minimal[['gene']]
```

```
## class: SummarizedExperiment
## dim: 112 9704
## metadata(0):
## assays(1): counts
## rownames(112): ENSG00000008853 ENSG00000104679 ... ENSG00000198899
## ENSG00000228253
## rowData names(0):
## colnames(9704): GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3 ... GGATTACCATGTTGAC-1_2A_4_SI-GA-G5
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2
## colData names(0):
```

```
assay(input_minimal[['gene']], 'counts')[1:2,1:2]
```

```
## 2 x 2 sparse Matrix of class "dgCMatrix"
## GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## ENSG00000008853 .
## ENSG00000104679 2
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3
## ENSG00000008853 .
## ENSG00000104679 .
```

1.2 guide modality

After renaming the first assay of the `guide` modality, this modality must have assays `counts` and `guide_assignment` containing the gRNA UMI counts and binary gRNA assignments, respectively:

```
assayNames(input_minimal[['guide']])[1] <- 'counts'
input_minimal[['guide']]
```

```
## class: SummarizedExperiment
## dim: 55 9704
## metadata(2): capture_method moi
## assays(2): counts guide_assignment
## rownames(55): ATGTAGAAGGAGACACCGGG GCGCAGAGGCGGATGTAGAG ...
## AATCCTCTAATGGACGAAGA ATATTCAGCAGCTAAAGCAT
## rowData names(2): targeting intended_target_name
## colnames(9704): GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3 ... GGATTACCATGTTGAC-1_2A_4_SI-GA-G5
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2
## colData names(0):
```

We can view a couple rows and columns of each:

```
cell_ids <- c("GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2",
             "GGTGAAGCACCAGGCT-1_1A_6_SI-GA-E7")
grna_ids <- c("GCCCTGCTACCCACTTACAG",
             "ATGTAGAAGGAGACACCGGG")
```

```
assay(input_minimal[['guide']], 'counts')[grna_ids, cell_ids]
```

```
## 2 x 2 sparse Matrix of class "dgCMatix"
##               GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## GCCCTGCTACCCACTTACAG                      9
## ATGTAGAAGGAGACACCGGG                      .
##               GGTGAAGCACCAGGCT-1_1A_6_SI-GA-E7
## GCCCTGCTACCCACTTACAG                      .
## ATGTAGAAGGAGACACCGGG                     18
```

```
assay(input_minimal[['guide']], 'guide_assignment')[grna_ids, cell_ids]
```

```
## 2 x 2 sparse Matrix of class "dgCMatix"
##               GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2
## GCCCTGCTACCCACTTACAG                      1
## ATGTAGAAGGAGACACCGGG                      .
##               GGTGAAGCACCAGGCT-1_1A_6_SI-GA-E7
## GCCCTGCTACCCACTTACAG                      .
## ATGTAGAAGGAGACACCGGG                      1
```

In addition to the guide UMI counts and assignments, the **guide** modality must contain certain metadata information. This includes a `rowData()` data frame containing at least the binary variable **targeting** (TRUE if the guide targets a genomic element of interest or FALSE if it is safe- or non-targeting) and the string **intended_target_name** (the name of the genomic element targeted by the guide).

```
rowData(input_minimal[['guide']])[c(1, 2, 21, 22, 31, 32),]
```

```
## DataFrame with 6 rows and 2 columns
##               targeting intended_target_name
##               <character>      <character>
## ATGTAGAAGGAGACACCGGG      TRUE      ENSG00000012660
## GCGCAGAGGCGGATGTAGAG      TRUE      ENSG00000012660
## ACACCCTCATTAGAACCCAG      TRUE      candidate_enh_1
## TTAAGAGCCTCGGTTCCCCT      TRUE      candidate_enh_1
## GACCTCCTGTGATCAGGTGG      FALSE      non-targeting
## ATTGGTATCCGTATAAGCAG      FALSE      non-targeting
```

Note that the **targeting** column is a string rather than a Boolean due to type compatibility issues involving R, Python, and HDF5. It can be cast to a Boolean if desired.

Finally, the guide modality must contain `metadata()` fields called **moi** (low or high) and **capture_method** ("CROP-seq" or "direct capture"):

```
metadata(input_minimal[['guide']])
```

```
## $capture_method
## [1] "CROP-seq"
##
## $moi
## [1] "high"
```

1.3 Global metadata

The input MuData object is also required to have a global `metadata` field named `pairs_to_test`, which is a data frame containing the pairs of elements (specified via `intended_target_name`) and genes (specified via `gene_id`) for which the inference is to be performed.

```
metadata(input_minimal)$pairs_to_test |> as.data.frame() |> head()
```

```
##           gene_id intended_target_name
## 1 ENSG00000187109      ENSG00000187109
## 2 ENSG00000114850      ENSG00000114850
## 3 ENSG00000134851      ENSG00000134851
## 4 ENSG00000163866      ENSG00000163866
## 5 ENSG00000181610      ENSG00000181610
## 6 ENSG00000113552      ENSG00000113552
```

2 Optional input fields

Next we consider optional fields that can be included in the input MuData object.

```
mudata_input_fp <- paste0(inference_data_path,
                           "/gasperini_inference_input.h5mu")
input_optional = readH5MU(mudata_input_fp)
input_optional
```

```
## A MultiAssayExperiment object of 2 listed
## experiments with user-defined names and respective classes.
## Containing an ExperimentList class object of length 2:
## [1] gene: SummarizedExperiment with 112 rows and 9704 columns
## [2] guide: SummarizedExperiment with 55 rows and 9704 columns
## Functionality:
## experiments() - obtain the ExperimentList instance
## colData() - the primary/phenotype DataFrame
## sampleMap() - the sample coordination DataFrame
## `$`, `[`, `[[]` - extract colData columns, subset, or experiment
## *Format() - convert into a long or wide DataFrame
## assays() - convert ExperimentList to a SimpleList of matrices
## exportClass() - save data to flat files
```

2.1 gene modality

The MuData object may include cellwise covariates for the `gene` modality in `colData()`, such as number of genes with nonzero UMI counts (`num_expressed_genes`) and total RNA UMIs (`total_gene_umis`):

```
colData(input_optional[['gene']])
```

```
## DataFrame with 9704 rows and 2 columns
##           num_expressed_genes total_gene_umis
##                               <integer>      <numeric>
## GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2          41          280
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3          35          192
## CCCAATCTCCTCAATT-1_1B_1_SI-GA-F2          41          781
## CGCGGTACACTGTCCG-1_1A_2_SI-GA-E3          37          189
## GGACGTCTCATGTCTT-1_1B_8_SI-GA-F9          32          262
## ...                               ...           ...
## CGCTATCTCTATCGCC-1_2A_4_SI-GA-G5          23          203
```

```
## TCACAAGCAGCCTTGG-1_2A_6_SI-GA-G7          30          173
## GCTGCAGGTGAAGGCT-1_2B_6_SI-GA-H7          37          428
## GGATTACCATGTTGAC-1_2A_4_SI-GA-G5          47          658
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2         23          166
```

The MuData object may include per-gene metadata in `rowData()`, such as the HGNC gene symbol (`symbol`), the gene chromosome (`chr`), start (`gene_start`), and end (`gene_end`) coordinates:

```
rowData(input_optional[['gene']])

## DataFrame with 112 rows and 4 columns
##              symbol   gene_chr gene_start gene_end
##              <character> <character> <numeric> <numeric>
## ENSG00000008853   RHOTB2      chr8    22844930 22844931
## ENSG00000104679    R3HCC1      chr8    23145421 23145422
## ENSG00000104689   TNFRSF10A     chr8    23082573 23082574
## ENSG00000120889   TNFRSF10B     chr8    22926533 22926534
## ENSG00000120896    SORBS3      chr8    22409208 22409209
## ...              ...          ...      ...      ...
## ENSG00000114850    SSR3        chr3    156271913 156271914
## ENSG00000072274    TFRC        chr3    195808960 195808961
## ENSG00000134851    TMEM165     chr4     56262124 56262125
## ENSG00000198899                NaN        NaN
## ENSG00000228253                NaN        NaN
```

2.2 guide modality

The MuData object may include cellwise covariates for the `guide` modality in `colData()`, such as number of guides with nonzero UMI counts (`num_expressed_guides`) and total guide UMIs (`total_guide_umis`):

```
colData(input_optional[['guide']])

## DataFrame with 9704 rows and 2 columns
##              num_expressed_guides total_guide_umis
##              <integer>          <numeric>
## GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2          1          9
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3          1         18
## CCAATCTCCTCAATT-1_1B_1_SI-GA-F2          1         24
## CGCGGTACACTGTCGG-1_1A_2_SI-GA-E3          1         26
## GGACGTCTCATGTCTT-1_1B_8_SI-GA-F9          1         12
## ...              ...              ...
## CGCTATCTCTATCGCC-1_2A_4_SI-GA-G5          1          5
## TCACAAGCAGCCTTGG-1_2A_6_SI-GA-G7          1         39
## GCTGCAGGTGAAGGCT-1_2B_6_SI-GA-H7          1         21
## GGATTACCATGTTGAC-1_2A_4_SI-GA-G5          1         73
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2          1         12
```

The MuData object may include per-guide metadata in `rowData()` in addition to the required `targeting` and `intended_target_name` fields, such as the chromosome (`intended_target_chr`), start (`intended_target_start`), and end (`intended_target_end`) of the targeted element:

```
rowData(input_optional[['guide']])[c(1, 2, 21, 22, 31, 32),]

## DataFrame with 6 rows and 5 columns
##              targeting intended_target_name intended_target_chr
##              <character>          <character>          <character>
## ATGTAGAAGGAGACACCGG      TRUE      ENSG00000012660          chr6
```

```
## GCGCAGAGGCGGATGTAGAG      TRUE      ENSG00000012660      chr6
## ACACCCTCATTAGAACCCAG      TRUE      candidate_enh_1      chr8
## TTAAGAGCCTCGGTTCCCCT      TRUE      candidate_enh_1      chr8
## GACCTCCTGTGATCAGGTGG      FALSE      non-targeting
## ATTGGTATCCGTATAAGCAG      FALSE      non-targeting
##                               intended_target_start intended_target_end
##                               <numeric>          <numeric>
## ATGTAGAAGGAGACACCGGG      53213723      53213738
## GCGCAGAGGCGGATGTAGAG      53213738      53213754
## ACACCCTCATTAGAACCCAG      23366136      23366564
## TTAAGAGCCTCGGTTCCCCT      23366564      23366992
## GACCTCCTGTGATCAGGTGG      -9          -9
## ATTGGTATCCGTATAAGCAG      -9          -9
```

2.3 Global metadata

Optionally, the MuData input object can contain a global `colData()` containing cell-level information that is not specific to modality, such as batch information. Here is what it looks like for the Gasperini data:

```
colData(input_optional)
```

```
## DataFrame with 9704 rows and 3 columns
##                               prep_batch  within_batch_chip
##                               <character>    <character>
## GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2 prep_batch_1 within_batch_chip_B
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3 prep_batch_1 within_batch_chip_A
## CCCAATCTCCTCAATT-1_1B_1_SI-GA-F2 prep_batch_1 within_batch_chip_B
## CGCGGTACACTGTGCG-1_1A_2_SI-GA-E3 prep_batch_1 within_batch_chip_A
## GGACGTCTCATGTCTT-1_1B_8_SI-GA-F9 prep_batch_1 within_batch_chip_B
## ...                               ...
## CGCTATCTCTATCGCC-1_2A_4_SI-GA-G5 prep_batch_2 within_batch_chip_A
## TCACAAGCAGCCTTGG-1_2A_6_SI-GA-G7 prep_batch_2 within_batch_chip_A
## GCTGCAGGTGAAGGCT-1_2B_6_SI-GA-H7 prep_batch_2 within_batch_chip_B
## GGATTACCATGTTGAC-1_2A_4_SI-GA-G5 prep_batch_2 within_batch_chip_A
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2 prep_batch_2 within_batch_chip_A
##                               within_chip_lane
##                               <character>
## GCTTGAATCGAATGCT-1_1B_1_SI-GA-F2 within_chip_lane_1
## AGCTTGATCGAGAGCA-1_1A_2_SI-GA-E3 within_chip_lane_2
## CCCAATCTCCTCAATT-1_1B_1_SI-GA-F2 within_chip_lane_1
## CGCGGTACACTGTGCG-1_1A_2_SI-GA-E3 within_chip_lane_2
## GGACGTCTCATGTCTT-1_1B_8_SI-GA-F9 within_chip_lane_8
## ...                               ...
## CGCTATCTCTATCGCC-1_2A_4_SI-GA-G5 within_chip_lane_4
## TCACAAGCAGCCTTGG-1_2A_6_SI-GA-G7 within_chip_lane_6
## GCTGCAGGTGAAGGCT-1_2B_6_SI-GA-H7 within_chip_lane_6
## GGATTACCATGTTGAC-1_2A_4_SI-GA-G5 within_chip_lane_4
## GTGCTTCTCGGATGTT-1_2A_1_SI-GA-G2 within_chip_lane_1
```

2.4 Pairs to test

Optionally, the `pairs_to_test` field of the global metadata can have a third column: `pair_type`:

```
metadata(input_optional)$pairs_to_test |> as.data.frame() |> head()
```

```
##           gene_id intended_target_name      pair_type
```

```
## 1 ENSG00000187109      ENSG00000187109 positive_control
## 2 ENSG00000114850      ENSG00000114850 positive_control
## 3 ENSG00000134851      ENSG00000134851 positive_control
## 4 ENSG00000163866      ENSG00000163866 positive_control
## 5 ENSG00000181610      ENSG00000181610 positive_control
## 6 ENSG00000113552      ENSG00000113552 positive_control
```

This optional column classifies pairs based on whether they are intended to be positive controls (an association is known to exist), negative controls (an association is known not to exist), or discovery pairs (pairs where it is unknown whether an association exists). This information need not be used by the inference module, but it is useful for downstream analysis.

3 Output fields

The output should be the same MuData object as the input, with the addition of a `test_results` field to the global metadata:

```
mudata_output_fp <- paste0(inference_data_path,
                             "/gasperini_inference_output.h5mu")
output_optional <- readH5MU(mudata_output_fp)
output_optional
```

```
## A MultiAssayExperiment object of 2 listed
## experiments with user-defined names and respective classes.
## Containing an ExperimentList class object of length 2:
## [1] gene: SummarizedExperiment with 112 rows and 9704 columns
## [2] guide: SummarizedExperiment with 55 rows and 9704 columns
## Functionality:
## experiments() - obtain the ExperimentList instance
## colData() - the primary/phenotype DataFrame
## sampleMap() - the sample coordination DataFrame
## `$`, `[`, `[[]` - extract colData columns, subset, or experiment
## *Format() - convert into a long or wide DataFrame
## assays() - convert ExperimentList to a SimpleList of matrices
## exportClass() - save data to flat files
```

```
metadata(output_optional)$test_results |> as.data.frame() |> head()
```

```
##      gene_id intended_target_name  log2_fc  p_value  pair_type
## 1 ENSG00000187109      ENSG00000187109 -0.7743672 3.217223e-85 positive_control
## 2 ENSG00000114850      ENSG00000114850 -1.8495718 2.414163e-79 positive_control
## 3 ENSG00000134851      ENSG00000134851 -0.8938597 4.309833e-50 positive_control
## 4 ENSG00000163866      ENSG00000163866 -1.2236996 4.704066e-49 positive_control
## 5 ENSG00000181610      ENSG00000181610 -1.3142850 3.766690e-42 positive_control
## 6 ENSG00000113552      ENSG00000113552 -1.6785978 2.554175e-39 positive_control
```

This is a data frame containing the same columns as the `pairs_to_test` data frame, plus at least one column containing a measure of the association for each pair. These columns can be `p_value`, `log2_fc`, `posterior_probability`, or any other measure of association.