



Windows PowerShell Interface Description

VERSION: 15.0

UPDATED: JUNE 2017

Copyright Notices

Copyright © 2002-2017 KEMP Technologies, Inc.. All rights reserved.. KEMP Technologies and the KEMP Technologies logo are registered trademarks of KEMP Technologies, Inc..

KEMP Technologies, Inc. reserves all ownership rights for the LoadMaster product line including software and documentation. The use of the LoadMaster Exchange appliance is subject to the license agreement. Information in this guide may be modified at any time without prior notice.

Microsoft Windows is a registered trademarks of Microsoft Corporation in the United States and other countries. All other trademarks and service marks are the property of their respective owners.

Limitations: This document and all of its contents are provided as-is. KEMP Technologies has made efforts to ensure that the information presented herein are correct, but makes no warranty, express or implied, about the accuracy of this information. If any material errors or inaccuracies should occur in this document, KEMP Technologies will, if feasible, furnish appropriate correctional notices which Users will accept as the sole and exclusive remedy at law or in equity. Users of the information in this document acknowledge that KEMP Technologies cannot be held liable for any loss, injury or damage of any kind, present or prospective, including without limitation any direct, special, incidental or consequential damages (including without limitation lost profits and loss of damage to goodwill) whether suffered by recipient or third party or from any action or inaction whether or not negligent, in the compiling or in delivering or communicating or publishing this document.

Any Internet Protocol (IP) addresses, phone numbers or other data that may resemble actual contact information used in this document are not intended to be actual addresses, phone numbers or contact information. Any examples, command display output, network topology diagrams, and other figures included in this document are shown for illustrative purposes only. Any use of actual addressing or contact information in illustrative content is unintentional and coincidental.

Portions of this software are; copyright (c) 2004-2006 Frank Denis. All rights reserved; copyright (c) 2002 Michael Shalayeff. All rights reserved; copyright (c) 2003 Ryan McBride. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE ABOVE COPYRIGHT HOLDERS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of the above copyright holders..

Portions of the LoadMaster software are copyright (C) 1989, 1991 Free Software Foundation, Inc. -51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA- and KEMP Technologies Inc. is in full compliance of the GNU license requirements, Version 2, June 1991. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Portions of this software are Copyright (C) 1988, Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms are permitted provided that the above copyright notice and this paragraph are duplicated in all such forms and that any documentation, advertising materials, and other materials related to such distribution and use acknowledge that the software was developed by the University of California, Berkeley. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Portions of this software are Copyright (C) 1998, Massachusetts Institute of Technology

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Portions of this software are Copyright (C) 1995-2004, Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Portions of this software are Copyright (C) 2003, Internet Systems Consortium

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Used, under license, U.S. Patent Nos. 6,473,802, 6,374,300, 8,392,563, 8,103,770, 7,831,712, 7,606,912, 7,346,695, 7,287,084 and 6,970,933.

Table of Contents

1	Introduction	5
1.1	Document Purpose	5
1.2	Intended Audience.....	5
1.3	Prerequisites	5
2	Windows PowerShell	6
2.1	Installing the KEMP PowerShell Module.....	6
2.2	Importing the Certificate	7
2.3	Using the Get-Help Command	8
2.4	Authenticating to the LoadMaster.....	8
2.4.1	Configure Certificate-Based Authentication	9
2.5	Object Structure.....	22
2.5.1	Errors.....	24
2.6	Initially Configure a LoadMaster Using PowerShell API Commands.....	25
2.6.1	Licensing Cloud LoadMasters.....	25
2.6.2	Initial Configuration Commands List.....	26
2.6.3	Accept the EULAs	27
2.6.4	Retrieve the Available Licenses (optional).....	28
2.6.5	License the LoadMaster	32
2.6.6	Set the Initial Password for the LoadMaster	34
2.6.7	Retrieve the License Details (optional)	35
2.6.8	Update a LoadMaster License.....	36
2.7	Code Snippet Examples.....	36
2.7.1	Online Licensing	36
2.7.2	Initialize the LoadMaster Connection Parameters	39
2.7.3	Enable the API	39
2.8	Known Issues with Beta PowerShell Wrapper	40
	References	41
	Document History	42

1 Introduction

KEMP Technologies products optimize web and application infrastructure as defined by high-availability, high-performance, flexible scalability, security and ease of management. They minimize the total cost-of-ownership for web infrastructure, while enabling flexible and comprehensive deployment options.

1.1 Document Purpose

This document provides some information on how to import the KEMP PowerShell module, how to enable the API interface on the LoadMaster and how to use the **Get-Help** command to retrieve help text relating to the various commands and parameters that can be used.

1.2 Intended Audience

This document is intended to help anyone who wishes to configure or interface to the KEMP LoadMaster using Windows PowerShell commands.

1.3 Prerequisites

For the PowerShell API to work with the LoadMaster, the following prerequisites must be met:

- Either TLS1.1 or TLS1.2 must be enabled in the LoadMaster WUI Settings. These are enabled by default. SSLv3 and TLS1.0 are unsupported with the PowerShell API. To set the **Supported TLS Protocols**, go to **Certificates & Security > Admin WUI Access** and select the check boxes provided.
- The API interface must be enabled on the LoadMaster. To enable it – go to **Certificates & Security > Remote Access** and tick the **Enable API Interface** check box.
- PowerShell version 5 or above is recommended.

2 Windows PowerShell

Windows PowerShell is Microsoft's command-line shell and scripting language based on a .NET framework. Windows PowerShell allows administrators to automate tasks and manage all applications from a central source.

The KEMP PowerShell module allows administrators to configure the KEMP LoadMaster from the Microsoft PowerShell command line.

2.1 Installing the KEMP PowerShell Module

Download the KEMP PowerShell module from the KEMP Documentation page, <https://kemptechnologies.com/loadmaster-documentation/>. Unzip the files.

The module contains the following files within the Kemp.LoadBalancer.Powershell folder:

- Kemp.LoadBalancer.Powershell.psd1
- Kemp.LoadBalancer.Powershell.psm1
- Kemp.LoadBalancer.Powershell-Help.xml

Before installing the KEMP PowerShell module, please ensure that you have Microsoft PowerShell version 3.0 installed.

Copy the **Kemp.LoadBalancer.Powershell** folder to the relevant folder.

Install the module in a folder that is available in PSModulePath (\$Env:PSModulePath).

If PSModulePath does not contain the module folder value, add the module path to the in PSModulePath environment variable. The module path can be for the current user only or for all users. Recommended values are:

- **\$home\Documents\WindowsPowerShell\Modules** for the current User
- **\$Env:ProgramFiles\WindowsPowerShell\Modules** for All Users

For example, install the KEMP PowerShell module for the current user only:

```
# Save the current value of PSModulePath
$mpath = [Environment]::GetEnvironmentVariable("PSModulePath")

# Add the new path to the $mpath variable
$ mpath +=
";$home\Documents\WindowsPowerShell\Modules\Kemp.LoadBalancer.Powershell"

# Add the paths in $currValue to the PSModulePath value.
[Environment]::SetEnvironmentVariable("PSModulePath", $currValue)
```

Import the module to start using it:

```
Import-Module Kemp.LoadBalancer.PowerShell
```

```
Get-Module Kemp.LoadBalancer.PowerShell
```

ModuleType	Version	Name	ExportedCommands
Script	7.2.39.0	Kemp.LoadBalancer.PowerShell	{Add-BondedInterface,
A...			

For the PowerShell commands to work, the API interface must be enabled on the LoadMaster. To enable it using the Web User Interface (WUI), go to **Certificates & Security > Remote Access** and select **Enable API Interface**.

You can test the connection to the load balancer by using the **Test-LmServerConnection** command, for example:

```
Test-LmServerConnection -ComputerName 10.11.0.60 -Port 443 -Verbose
```

To retrieve a list of available commands, run the following command:

```
Get-Command -Module Kemp.LoadBalancer.PowerShell
```

To retrieve the build number of the PowerShell module, run the following command:

```
(Get-Module Kemp.LoadBalancer.PowerShell).ReleaseNotes
```

This command only works on PowerShell version 5 and above.

2.2 Importing the Certificate

As of LoadMaster version 7.2.36 the PowerShell module is signed. Depending on your execution policy, you may need to import the KEMP PowerShell certificate to allow execution. When you download the module from the KEMP website to obtain the following files:

- Kemp.LoadBalancer.PowerShell-Help.xml
- Kemp.LoadBalancer.PowerShell.psd1
- Kemp.LoadBalancer.PowerShell.psm1
- kemp-cert.cer
- symantec-ca.cer
- symantec-int.cer

Perform the following steps:

1. Double-click the **symantec-ca.cer** file and install it in **Trusted Root Certification Authorities**.
2. Double the **symantec-int.cer** file and install it in **Trusted Root Certification Authorities**.

3. Confirm the installation by clicking **OK** when requested.
4. Double click the **kemp-cert.cer** and install it in **Trusted Publishers**.
5. Set the execution policy to **AllSigned**. For example, Set-ExecutionPolicy –ExecutionPolicy AllSigned –Scope CurrentUser.

Alternatively, you could adjust your execution policy to one that is less restrictive.

2.3 Using the Get-Help Command

To retrieve help text for a particular command, run the **Get-Help** command, followed by a command name, for example:

Get-Help Set-VirtualService

Different parameters can be specified to retrieve more detailed help text:

- **-Detailed**: Provides further detailed help, including a list of parameters and their descriptions.
- **-Examples**: Provides an example command and example output.
- **-Full**: Provides all of the help text for the specified command.

For example:

Get-Help Set-VirtualService –Full

2.4 Authenticating to the LoadMaster

To run PowerShell API commands, you need to establish authentication with the LoadMaster. There are two ways to establish authentication:

- Using credentials; a LoadMaster username (**Credential**) and password
- Using certificate-based authentication

Whichever option you use, you can either specify the parameters when running individual commands, or using the **Initialize-LmConnectionParameters** command.

You can also globally set the KEMP LoadMaster IP address that you are directing the commands to by using the **Initialize-Lm** command, for example:

Initialize-Lm -Address 10.11.0.60 -LBPort 443 -Credential bal -Verbose

You can either enter a username for the load balancer or provide a PSCredential object. When you enter a username, a prompt appears asking for the password. You can override the globally-provided LoadBalancer address and User Name on each individual command by using the **LoadBalancer** or **Credential** parameter within the command.

Similarly, you can specify the details to use certificate-based authentication using the **Initialize-LmConnectionParameters** command. For further information on the various steps involved to configure certificate-based authentication, refer to the below section.


2.4.1 Configure Certificate-Based Authentication

Follow the steps in the sections below to configure certificate-based authentication.

2.4.1.1 Enable Session Management

You must enable **Session Management** before you can enable client certificate authentication. To enable Session Management, follow the steps below:

1. In the main menu of the LoadMaster WUI, navigate to **System Configuration > Miscellaneous Options > WUI Settings**.



A screenshot of the 'WUI Session Management' settings page. It features a title bar 'WUI Session Management' and a single checkbox labeled 'Enable Session Management' which is currently unchecked.

Figure 2-1: Enable Session Management


2. Select the **Enable Session Management** check box.

Once this check box is selected, the user is required to log in to continue using the LoadMaster.

3. Configure any other settings as needed.

2.4.1.2 Create a User (If Needed)

1. It is not possible to use certificate-based authentication with the **bal** user. However, you can create a non-**bal** user and grant it **All Permissions**, or whatever permissions you want. If you do not already have another user created, you can add one by following these steps: In the main menu of the LoadMaster WUI, expand **System Configuration > System Administration** and click **User Management**.



A screenshot of the 'Add User' form. It has a title bar 'Add User'. Below it, there are two text input fields: 'User' containing 'ExampleUser' and 'Password' containing seven dots. To the right of the password field is a checkbox labeled 'No Local Password' which is unchecked. At the bottom right is a blue button labeled 'Add User'.

Figure 2-2: Add User

2. At the bottom of the screen, enter a username in the **User** text box.
3. At this point, you can either set a **Password** for the new user, or select the **No Local Password** check box.

For further information on the **No Local Password** option, and on certificate authentication in general, refer to the **User Management, Feature Description**.

4. Click **Add User**.

2.4.1.3 Enable Client Certificate Authentication on the LoadMaster

A number of different login methods are available to enable. For steps on how to set the **Admin Login Method**, along with a description of each of the available methods, refer to the steps below:

1. In the main menu of the LoadMaster WUI, expand **Certificates & Security** and click **Remote Access**.

The screenshot shows the 'Administrator Access' configuration page in the LoadMaster WUI. It includes the following settings:

- Allow Remote SSH Access:** Checked. Using: All Networks. Port: 22. [Set Port]
- SSH Pre-Auth Banner:** [Text input field] [Set Pre-Auth Message]
- Allow Web Administrative Access:** Checked. Using: eth0: 10.154.11.100. Port: 443.
- Admin Default Gateway:** [Text input field] [Set Administrative Access]
- Allow Multi Interface Access:** Unchecked.
- Enable API Interface:** Checked.
- Admin Login Method:** Password or Client certificate (dropdown menu).
- Enable Software FIPS 140-2 level 1 Mode:** [Enable Software FIPS mode]
- Allow Update Checks:** Checked.

Figure 2-3: Admin Login Method

2. Select the relevant **Admin Login Method**.

Using local certificates will only work with API authentication. Because of this, it might be best to select the **Password or Client certificate** option. This will allow API access using the client certificate and WUI access using the username/password.

The following login methods are available:

- **Password Only Access (default):** This option provides access using the username and password only – there is no access using client certificates.
- **Password or Client certificate:** The user can log in either using the username/password or using a valid client certificate. If a valid client certificate is in place, the username and password is not required.

The LoadMaster asks the client for a certificate. If a client certificate is available, the LoadMaster checks for a match. The LoadMaster checks if the certificate is a match with one of the local certificates, or checks if the Subject Alternative Name (SAN) or Common Name (CN) of the certificate is a match. The SAN is used in preference to the CN when performing a match. If there is a match, the user is granted access to the LoadMaster. This works both using the API and user interface.

An invalid certificate will not allow access.

If no client certificate is supplied, the LoadMaster will expect that a username and password is supplied (for the API) or will ask the user to enter a password using the standard WUI login page.

- **Client certificate required:** Access is only allowed using the use of a client certificate. It is not possible to log in using the username and password. SSH access is not affected by this (only the **bal** user can log in using SSH).
- **Client certificate required (Verify via OCSP):** This is the same as the **Client certificate required** option, but the client certificate is verified using an OCSP service. You must configure the OCSP Server Settings for this to work. For further information on the OCSP Server Settings, refer to the **DoD Common Access Card Authentication, Feature Description**.

Some points to note regarding the client certificate methods are below:

- The **bal** user does not have a client certificate. Therefore, it is not possible to log into the LoadMaster as **bal** using the **Client certificate required** methods. However, a non-**bal** user can be created and granted **All Permissions**. This will allow the same functionality as the **bal** user.
- There is no log out option for users that are logged in to the WUI using client certificates, as it is not possible to log out (if the user did log out the next access would automatically log them back in again). The session terminates when the page is closed, or when the browser is restarted.

2.4.1.4 *Generate and Download the Client Certificate*

To generate a local certificate, follow the steps below:

Users with **User Administration** permissions are able to manage local certificates for themselves and other users.

1. In the main menu of the LoadMaster WUI, navigate to **System Configuration > System Administration > User Management**.

Local Users		
User	Permissions	Operation
ExampleUser	All Permissions	<div>ModifyDelete</div>

Figure 2-4: Modify user

2. Click **Modify** on the relevant user.




The 'Local Certificate' interface features a title bar and a horizontal separator. Below the separator, there are three rows of controls. The first row contains the text 'Download Certificate' followed by a 'Download' button. The second row contains 'Generate Certificate', a 'Generate' button, and a 'Passphrase' text input field with a masked password '.....'. The third row contains 'Delete Certificate' followed by a 'Delete' button.

Figure 2-5: Generate certificate

3. Enter a **Passphrase** and click **Generate**.


Entering a passphrase is optional. If a passphrase is entered it gets used to encrypt the private key.



A standard Windows message box titled '10.154.11.170 says:'. The main text reads 'New Certificate generated'. Below this is a checkbox labeled 'Prevent this page from creating additional dialogs.' which is currently unchecked. An 'OK' button is located in the bottom right corner.

Figure 2-6: New Certificate generated

4. Click **OK** to the pop-up message that appears.



This 'Local Certificate' interface is identical to Figure 2-5, but the 'Generate' button is replaced by a 'Regenerate' button. The 'Passphrase' text input field is now empty.

Figure 2-7: Download the certificate

5. Click **Download**.

You can also regenerate from this screen.

2.4.1.5 Create the PFX File

When you generate a certificate, as described in the section above, the LoadMaster creates a .pem file. For certificate-based authentication to work with PowerShell, a .pfx file is required.

You can convert the .pem file to .pfx any way you like. For the purposes of this document, we have provided steps on how to do it using OpenSSL. If you are using Windows, you may need to install OpenSSL to run these steps.

To create a .pfx file using, follow the steps below:

1. Open the .pem certificate.
2. Copy from the start of the -----BEGIN CERTIFICATE----- section to the end of the -----END CERTIFICATE----- section.
3. Paste this text into a new file.
4. Save the file as **<CerFileName>.cer**.
5. Go to the .pem certificate file again.
6. Copy from the start of the -----BEGIN RSA PRIVATE KEY----- section to the end of the -----END RSA PRIVATE KEY----- section.
7. Paste this text into a new file.
8. Save the file as **<KeyFileName>.key**.
9. Use the **openssl** command to create the .pfx file:
openssl pkcs12 -export -out <NewFileName>.pfx -inkey <KeyFilename>.key -in <CerFileName>.cer
10. Import the certificate to the web browser.

2.4.1.6 Import the PFX File into the Microsoft Management Console (if using Windows)

If you are using Windows, follow the steps below to import the .pfx file into the Microsoft Management Console:




Figure 2-8: Search for mmc.exe

1. Click **Start** and type **mmc.exe**.
2. Click **mmc.exe** to open the Microsoft Management Console.
3. Click **File** and select **Add/Remove Snap-in**.




Figure 2-9: Certificates

4. Select **Certificates** on the left and click **Add**.




Figure 2-10: My user account

5. Ensure that **My user account** is selected and click **Finish**.
6. Click **OK**.




Figure 2-11: Certificates

7. Double-click **Certificates – Current User**.




Figure 2-12: Personal

8. Double-click **Personal**.




Figure 2-13: Certificates

9. Double-click **Certificates**.
10. Right-click on any white space in the middle panel, select **All Tasks** and click **Import**.




Figure 2-14: Next

11. Click **Next**.




Figure 2-15: Browse

12. Click **Browse**.
13. Browse to the location of the .pfx file to be imported.




Figure 2-16: All Files

14. Select **All Files** in the drop-down menu in the bottom-right.
15. Double-click the .pfx file.




Figure 2-17: Enter Password

16. Enter the **Password** (if necessary).
17. Click **Next**.




Figure 2-18: Certificate store

18. Click **Browse** and select the **Personal** certificate store.
19. Click **Next**.




Figure 2-19: Finish

20. Review the settings and click **Finish**.

2.4.1.7 Specify the Certificate Details in the API

After configuring all of the options as outlined in the above sections, you need to specify the details of the certificate to run the API commands successfully. You can either do this using the **Initialize-Lm** command or in individual commands when they are run. The two parameters related to certificate-based authentication are:

- **SubjectCN:** This parameter is mandatory if you want to use certificate-based authentication. This is the certificate Common Name (CN). This is the username of the LoadMaster user that the certificate was generated for. If you do not specify the **CertificateStoreLocation**, the certificate is searched for in the **<CurrentUser>/My** location.
- **CertificateStoreLocation:** This parameter is optional. If you do not use it, the cmdlet searches for the certificate in the **<CurrentUser>/My** location (default). If the **CertificateStoreLocation** parameter is set, the API searches for the certificate in the specified location, for example **Cert:\<CurrentUser>\TrustedPeople**

2.5 Object Structure

As of the 7.2.39.0.334 version of the KEMP PowerShell wrapper, all the commands (except **Test-LmServerConnection**) return a PowerShell object with the following structure:

The **Test-LmServerConnection** command returns **True** if the LoadMaster is reachable by the API, **False** if not.

- **ReturnCode** (integer)
- **Response** (string)
- **Data** (PowerShell object, if any)

As a result of the new object structure, the current KEMP PowerShell wrapper is not compatible with scripts written based on an older version of the KEMP PowerShell wrapper (before July 2017).

The possible values for the **ReturnCode** field are:

- 200: The command completed successfully
- 4xx/500: The command ended with an error. The error code depends on the error type.

The possible values for the **Response** field are:

- Command successfully executed
- Description of the error when the command fails, for example **Unknown parameter value Imversion**.

The **Data** field contains the response, if any. The structure of this field depends on the command. The elements of this field can be accessed using the “dot” notation. If the command fails, this field is empty.

Example 1: Retrieve the installed LoadMaster firmware version:

```
$lma = Get-LmParameter -Param version -LoadBalancer 172.21.59.189 -  
SubjectCN user1  
$lma | Format-List
```

```
ReturnCode : 200  
Response   : Command successfully executed.  
Data       : @{version=7.2.39.0.DEV-PRIVATE-user1}
```

```
$lma.Data.version  
7.2.39.0.DEV-PRIVATE-user1
```

Example 2: Retrieve the available licenses for a specific Order ID:

```
$licDet = Get-LicenseType -KempId jbloggs@kemptechnologies.com -  
Password ExamplePassword -LoadBalancer 172.21.59.85 -Credential  
$lm85BalCreds -OrderId Example20170517
```

```
$licDet | Format-List
```

ReturnCode : 200

Response : Command successfully executed.

Data : @{{License=System.Object[]}}

\$licDet.Data.License

id : 0632b88b577c71591798268bcd4e01132f082309

name : VLM-5000 ESP GEO with Basic 2 Years

available : 1

description : VLM-5000 ESP GEO with Basic 2 Years

tethered : False

LicenseStatus : Permanent License

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

id : fc488d991cffb7a5958625427d6bfb0b3edc008e

name : VLM-5000 WAF GEO with Basic 3 Years

available : 1

description : VLM-5000 WAF GEO with Basic 3 Years

tethered : False

LicenseStatus : Permanent License

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

name : VLM-5000 with Enterprise Plus subscription

available : 1

tethered : 0

id : 3eb92178611573946b422cf8d0df69d04c07fede

LicenseStatus : Temp License

description : VLM-5000 with Enterprise Plus subscription

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

The benefits of the structure of the command answers are:

- ### 2.5.1 Errors

```

ERROR: Can't find a certificate with "invalidcertificate" as CN in the default
Cert:\CurrentUser\My store.
At C:\Users\FabrizioCarpin\work\Powershell\branches\PD-
8213\Kemp.LoadBalancer.Powershell\Kemp.LoadBalancer.Powershell.psml:273 char:5
+ ~~~~~~
+ ~~~~~~
+ CategoryInfo          : OperationStopped: (ERROR: Can't fi...tUser\My
store.:String) [], RuntimeException
+ FullyQualifiedErrorId : ERROR: Can't find a certificate with
"invalidcertificate" as CN in the default Cert:\CurrentUser\My store.

```


When deploying a pay-per-use LoadMaster, you can use the `Set-LicenseInitialPassword` command to configure the administrator password. The LoadMaster is ready to use after that point.

2.6.2 Initial Configuration Commands List

The initial configuration commands are listed below:

- EULA:
 - Read-LicenseEULA (mandatory)
 - Confirm-LicenseEULA (mandatory)
 - Confirm-LicenseEULA2 (mandatory)

These EULA commands must be run in the above order.

- License type:
 - Get-LicenseType (optional)
 - Get-AslLicenseType (optional)

These commands are optional when completing the licensing process. The **Get-LicenseType** command contacts the KEMP Licensing Server. The **Get-AslLicenseType** must be used with a KEMP 360 Central Activation Server instance that is acting as a “local licensing server”.

- Licensing:
 - Request-LicenseOnline
 - Request-LicenseOffline
 - Request-LicenseOnPremise

To install the license on the LoadMaster, one of the above commands must be used:

- The online command is used when the LoadMaster can reach the KEMP licensing server.
- Otherwise, the offline command must be used. If using offline licensing, you must have the “BLOB” licensing text that KEMP sent in an email.
- The Request-LicenseOnPremise command is used to license a LoadMaster using a KEMP 360 Central acting as a “local licensing server”.

- Set password:
 - Set-LicenseInitialPassword (mandatory)

This command must be used to set the LoadMaster administrator (**bal**) password.

- Get license details:
 - Get-LicenseInfo (optional)

To license a LoadMaster, you must acknowledge the EULA licenses. This step involves three commands and they must be run in the following order:

- For example:

\$reula

\$reula.Data.Eula

The **MagicString** parameter must be used as input for the **Confirm-LicenseEULA** command. The **Type** parameter is optional. The default value for the **Type** parameter is **Trial**. The **Free** value must only be used for the Free LoadMaster.

```
$ceula = Confirm-LicenseEULA -Magic $reula.Data.Eula.MagicString `
                                     -LoadBalancer 172.21.59.85
-Credential $lm85BaICreds
```

```
$ceula
```

ReturnCode	Response	Data
200	Command successfully executed	@{Eu1a2=}

```
$ceula.Data.Eu1a2
```

MagicString	Eu1a2
46181257-2f09-4094-a9cd-6af02f352180	...

The last step is to run the **Confirm-LicenseEULA2** command. The **MagicString** parameter is from the **Confirm-LicenseEULA** output. The command is used to specify whether to use the Call Home feature. If it is enabled, the LoadMaster regularly contacts the KEMP Licensing Server to check for updates and other information. Specify the value (**yes/no**) as desired.

```
$ceula2 = Confirm-LicenseEULA2 -Magic $ceula.Data.Eu1a2.MagicString -
Accept yes -
-LoadBalancer 172.21.59.85 -
Credential $lm85BalCreds
```

```
$ceula2
```

ReturnCode	Response	Data
200	Command successfully executed.	

2.6.4 Retrieve the Available Licenses (optional)

Before running the command to license the LoadMaster (**Request-LicenseOnline/Request-LicenseOffline**) it is possible to retrieve the available license(s) for a specific KEMP ID from the KEMP Licensing Server using the **Get-LicenseType** command.

The parameters for this command are:

- KempId (mandatory)
- Password (mandatory)
- OrderId (optional)

The output of the command (when successful) has the following structure:

```
ReturnCode : 200
Response   : Command successfully executed.
Data       : @{License=}
```

The field **Data.License** contains details about the the license(s) and it always includes the temporary license option. For example:

\$licDet.Data.License

```
id           : 0632b88b577c71591798268bcd4e01132f082309
name         : VLM-5000 ESP GEO with Basic 2 Years
available    : 1
description  : VLM-5000 ESP GEO with Basic 2 Years
tethered     : False
```

LicenseStatus : Permanent License

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

```
id           : fc488d991cffb7a5958625427d6bfb0b3edc008e
name         : VLM-5000 WAF GEO with Basic 3 Years
available    : 1
description  : VLM-5000 WAF GEO with Basic 3 Years
tethered     : False
```

LicenseStatus : Permanent License

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

```
name         : VLM-5000 with Enterprise Plus subscription
available    : 1
tethered     : 0
```

```
id           : 3eb92178611573946b422cf8d0df69d04c07fede
```

LicenseStatus : Temp License

```
description  : VLM-5000 with Enterprise Plus subscription
```

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

In this example, the customer purchased two licenses. The third entry is the temporary license.

If the KEMP ID does not exist, the command returns the string “License type information not available”.

2.6.4.1 Example without Specifying an Order ID

Without an Order ID, the command only returns the temporary license details:

```
$licDet = Get-LicenseType -KempId jbloggs@kemptechnologies.com -
Password supersecretpasswd `
                                     -LoadBalancer 172.21.59.85
-Credential $lm85BalCreds
```

```
$licDet
ReturnCode Response                               Data
-----
200 Command successfully executed. @{License=System.Object[]}
```

```
$licDet.Data.License
```

```
name          : VLM-5000 with Enterprise Plus subscription
available     : 1
tethered      : 0
id            : 3eb92178611573946b422cf8d0df69d04c07fede
LicenseStatus : Temp License
description    : VLM-5000 with Enterprise Plus subscription
BuyMoreAt     : https://www.kemptechnologies.com/buy-me-
now?KEMPID=jbloggs@kemptechnologies.com
```

2.6.4.2 Example with a Valid Order ID

If a valid Order ID is provided, the command returns an array of licenses containing the purchased license(s) and the temporary license details:

```
$licDet = Get-LicenseType -KempId gigio@gigetto.com -Password
supersecretpasswd `
                                     -LoadBalancer 172.21.59.85 -Credential
$lm85BalCreds -OrderId Example20170517
```

```
$licDet | Format-List
```

```
ReturnCode : 200
Response    : Command successfully executed.
Data        : @{License=System.Object[]}
```

```
$licDet.Data.License
```

```
id           : 0632b88b577c71591798268bcd4e01132f082309
name         : VLM-5000 ESP GEO with Basic 2 Years
available    : 1
description  : VLM-5000 ESP GEO with Basic 2 Years
tethered     : False
LicenseStatus : Permanent License
BuyMoreAt    : https://www.kemptechnologies.com/buy-me-
now?KEMPID=jbloggs@kemptechnologies.com
```

```
id           : fc488d991cffb7a5958625427d6bfb0b3edc008e
name         : VLM-5000 WAF GEO with Basic 3 Years
available    : 1
description  : VLM-5000 WAF GEO with Basic 3 Years
tethered     : False
LicenseStatus : Permanent License
BuyMoreAt    : https://www.kemptechnologies.com/buy-me-now?KEMPID=
jbloggs@kemptechnologies.com
```

```
name         : VLM-5000 with Enterprise Plus subscription
available    : 1
tethered     : 0
id           : 3eb92178611573946b422cf8d0df69d04c07fede
LicenseStatus : Temp License
description  : VLM-5000 with Enterprise Plus subscription
BuyMoreAt    : https://www.kemptechnologies.com/buy-me-now?KEMPID=
jbloggs@kemptechnologies.com
```

The answer is an array and you can retrieve each element of the array by using the usual array syntax, for example, to get the first element of the array:

```
$licDet.Data.License[0]
```

```
id           : 0632b88b577c71591798268bcd4e01132f082309
name         : VLM-5000 ESP GEO with Basic 2 Years
available    : 1
description  : VLM-5000 ESP GEO with Basic 2 Years
tethered     : False
LicenseStatus : Permanent License
```

BuyMoreAt : <https://www.kemptechnologies.com/buy-me-now?KEMPID=jbloggs@kemptechnologies.com>

2.6.4.3 Example with an Invalid (Undefined) KEMP ID

An example with an invalid (or non-existing) KEMP ID is below:

```
$err = Get-LicenseType -KempId invalid@invalid.co.uk -Password  
bla2017bla ` -LoadBalancer 172.21.59.85 -  
Credential $lm85Ba1Creds
```

ReturnCode : 200

Response : Command successfully executed.

Data : @{Licenses=License type information not available}

\$err.Data.Licenses

License type information not available

2.6.4.4 Retrieve License Types when using Activation Server Functionality

If you are licensing the LoadMaster using a KEMP 360 Central Activation Server, a similar command (**Get-AslLicenseType**) is used to retrieve the available licenses. The parameters for this command are:

- aslipaddress (mandatory): IP address of the KEMP 360 Central Activation Server instance
- aslport (mandatory): The KEMP 360 Central Activation Server listening port
- aslname (optional): The KEMP 360 Central Activation Server Fully Qualified Domain Name (FQDN)

2.6.5 License the LoadMaster

The commands to license the LoadMaster (initially license the LoadMaster for the first time, not updating an existing LoadMaster license) are **Request-LicenseOnline** and **Request-LicenseOffline**.

To use the **Request-LicenseOnline** command, the LoadMaster must be able to connect to the KEMP Licensing Server. If this is not possible, the **Request-LicenseOffline** command can be used.

The **Request-LicenseOnPremise** command is used to license a LoadMaster using a KEMP 360 Central as a “Local Licensing Server”.

The **Request-LicenseOnline** command interface contains the **OrderId** and **LicenseTypeId** parameters. When you purchase a product from KEMP, KEMP provide you with the **OrderId**. The

OrderId is a unique string that is a pointer to the record that details what was purchased. The **OrderId** is a container – there may be multiple license types for one **OrderId**. The **LicenseTypeId** is the “license ID” that can be retrieved using the **Get-LicenseType** command, as shown in the above examples.

If you specify the **OrderId** but not the **LicenseTypeId**, the first license in the list matching the specified Order ID is used. This is the first license defined (the oldest) for that order ID.

If you specify both the **OrderId** and **LicenseTypeId**, the specific license matching both the Order ID and License Type ID is used.

If you do not specify either an **OrderId** or **LicenseTypeId**, a temporary license is applied.

If you specify a **LicenseTypeId** but not an **OrderId**, an error message is returned. This is an invalid combination – the Order ID must also be specified if using the License Type ID.

The following table summarizes the above text:

OrderId (not mandatory)	LicenseTypeId (not mandatory)	License Given to the LoadMaster
Used	Not used	First license in the list matching the specified Order ID
Used	Used (value from Get-LicenseType)	The specific license matching the Order ID and License Type ID
Not used	Not used	Temporary license
Not used	Used (value from Get-LicenseType)	Invalid combination (error is returned). The Order ID must also be specified.

Table 2-1: OrderId/LicenseTypeId combinations

2.6.5.1 Online Licensing Example

The below example uses online licensing and requests a specific license (both the **OrderId** and **LicenseTypeId** must be used):

```
$lictype = Get-LicenseType -KempId jbloggs@kemptechnologies.com -
Password supersecretpassword `
                    -LoadBalancer 172.21.59.85 -Credential $lm85Ba1Creds
-OrderId marvel20170511-01
```

```
$lictype | Format-List
```

```
ReturnCode : 200
```

```
Response   : Command successfully executed.
```

```
Data       : @{{License=System.Object[]}}
```

```
$lic = Request-LicenseOnline -LoadBalancer 172.21.59.85 -Credential
$lm85BalCreds `
                                -KempId jbloggs@kemptechnologies.com -
Password supersecretpassword `
                                -LicenseTypeId $lictype.Data.License[0].id
-OrderId marvel20170511-01
```

```
$lic | Format-List
```

```
ReturnCode : 200
Response   : Command successfully executed.
Data       :
```

2.6.5.2 Offline Licensing Example

An example using the offline licensing method is below:

```
$offline_lic = Request-LicenseOffline -Path .\blob-85.blob -
LoadBalancer 172.21.59.85
```

```
$offline_lic
```

```
ReturnCode Response                               Data
-----
200 Command successfully executed.
```

2.6.6 Set the Initial Password for the LoadMaster

After licensing, you must set the administrator password before you can start using the LoadMaster. Use the **Set-LicenseInitialPassword** command to do this, for example:

```
$setp = Set-LicenseInitialPassword -Passwd balsupersecretpassword -
LoadBalancer 172.21.59.85 `
-Credential $lm85BalCreds
```

```
$setp | Format-List
```

```
ReturnCode : 200
Response   : Command successfully executed.
```

Data :

2.6.7 Retrieve the License Details (optional)

You can use the **Get-LicenseInfo** command to retrieve the LoadMaster license details.

```
$license_details = Get-LicenseInfo -LoadBalancer 172.21.59.85 -  
Credential $lm85BalCreds
```

```
$license_details
```

ReturnCode	Response	Data
-----	-----	----
	200	Command successfully executed. @{LicenseInfo=}

```
$license_details.Data.LicenseInfo
```

```
uuid           : 941b6d65-1758-40a3-8a89-a9b45a8a8512  
ActivationDate  : Wed May 17 16:47:46 UTC 2017  
LicensedUntil  : unlimited  
SupportLevel   : Basic 2 years  
SupportUntil   : Fri May 17 04:00:00 UTC 2019  
LicenseType    : VLM-5000 ESP GEO  
LicenseStatus  : Single Perm  
ApplianceModel : VLM-5000 ESP GEO  
MaxVS          : 0  
MaxRS          : 0  
Bandwidth      : 5000  
TpsLimit       : 10000  
HA             : no  
FirstHA        : no  
ModSecurity    : yes  
AFE            : yes  
ViewAFE        : yes  
ESP            : yes  
IPSEC          : 2  
SingleCPU      : no  
VLM            : yes  
VlmPlatform    : VMWARE  
SKU            : VLM_OVF_64
```

```
FreeLicense      : no
Temporary       : no
ASL             : no
MandatoryTether : no
MultipleConnect : no
```

2.6.8 Update a LoadMaster License

The LoadMaster license can be updated using the **Update-LicenseOnline** or **Update-LicenseOffline** command.

Here is an example using the online command:

```
$licupdate = Update-LicenseOnline -KempId fabrizio@eagle.com -Password
kempkemp `
                                     -LoadBalancer 172.21.59.85
-Credential $lm85Ba1Creds
```

```
$licupdate
```

ReturnCode	Response	Data
-----	-----	----
	200 Command successfully executed.	

You can check the updated license by running the **Get-LicenseInfo** command.

2.7 Code Snippet Examples

Refer to the sections below for some code snippet examples.

2.7.1 Online Licensing

The following prerequisites are assumed:

- A KEMP LoadMaster with an IP address has been deployed and is ready to be set up
- A valid KEMP ID and password exists to get the license from the KEMP Licensing Server

(1) CREATE THE CREDENTIALS

```
$passwd = ConvertTo-SecureString "<<your password>>" -AsPlainText -
Force
$creds = New-Object System.Management.Automation.PSCredential("ba1",
$passwd)
$LMIP = <<LoadMaster IP address>>
$KEMPID = <<Customer KEMP ID>>
```

```
$KEMPPASSWD = <<Customer KEMP PASSWORD>>
```

```
# (2) Virtual Service and Real Server details (for more details about  
the configuration parameters see the official KEMP documentation:  
https://kemptechnologies.com/loadmaster-documentation/)
```

```
$VSIP = <<Virtual Service IP>>
```

```
$VSPOINT = <<Virtual Service Port>>
```

```
$VSPROTOCOL = <<Virtual Service Protocol (tcp/udp)>>
```

```
$RSIP = <<Real Server IP>>
```

```
$RSPORT = <<Real Server Port>>
```

```
# (3) GET the EULA
```

```
$reula = Read-LicenseEULA -LoadBalancer $LMIP -Credential $creds
```

```
if ($reula.ReturnCode -ne 200) {
```

```
    # ERROR: exit
```

```
    return $reula
```

```
}
```

```
# (4) CONFIRM the EULA (mandatory)
```

```
$ceula = Confirm-LicenseEULA -Magic $reula.Data.Eula.MagicString `
```

```
-LoadBalancer $LMIP -
```

```
Credential $creds
```

```
if ($ceula.ReturnCode -ne 200) {
```

```
    # ERROR: exit
```

```
    return $ceula
```

```
}
```

```
# (5) CONFIRM/NOT CONFIRM the EULA2 (your choice)
```

```
#$accept = "yes"
```

```
$accept = "no"
```

```
$ceula2 = Confirm-LicenseEULA2 -Magic $ceula.Data.Eula2.MagicString -  
Accept $accept `
```

```
-LoadBalancer $LMIP -
```

```
Credential $creds
```

```
if ($ceula2.ReturnCode -ne 200) {
```

```
    # ERROR: exit
```

```
    return $ceula2
```

```
}
```

```
# (6) LICENSE the machine
$lic = Request-LicenseOnline -LoadBalancer $LMIP -Credential $creds `
                                     -KempId $KEMPID -
Password $KEMPPASSWD
if ($lic.ReturnCode -ne 200) {
    # ERROR: exit
    return $lic
}

# (7) SET the Initial Password
$setp = Set-LicenseInitialPassword -Passwd $passwd -LoadBalancer $LMIP `
                                     -
Credential $creds
if ($setp .ReturnCode -ne 200) {
    # ERROR: exit
    return $setp
}

# (8) CREATE a Virtual Service
$vs = New-AdcVirtualService -VirtualService $VSIP -VSPort $VSPORT `
                             -VSProtocol $VSPROTOCOL -LoadBalancer $LMIP -
Credential $creds
if ($vs.ReturnCode -ne 200) {
    # ERROR: exit
    return $vs
}

# (9) CREATE a Real Server
$rs = New-AdcRealServer -VirtualService $VSIP -VSPort $VSPORT -
VSProtocol $VSPROTOCOL `
                             -RealServer $RSIP -
RealServerPort $RSPORT `
                             -LoadBalancer $LMIP -
Credential $creds
if ($rs.ReturnCode -ne 200) {
    # ERROR: exit
    return $rs
}
```

2.7.2 Initialize the LoadMaster Connection Parameters

In the above examples, the required parameters, **LoadBalancer** and **Credential**, can be initialized before running the commands with the **Initialize-LmConnectionParameters** command. If you do this, it is not necessary to specify these parameters in each command.

For example:

```
$lma = Initialize-LmConnectionParameters -Address $LMIP -Credential $creds
$lma | Format-List
```

```
ReturnCode : 200
Response    : Command successfully executed.
Data        : @{{Connection=; Login=}}
```

After the initialization, for example, the command to create a vs will become:

```
$vs = New-AdcVirtualService -VirtualService $VSIP -VSPort $VSPORT `
                                     -VSProtocol
$VSProtocol
if ($vs.ReturnCode -ne 200) {
    # ERROR: exit
    return $vs
}
```

2.7.3 Enable the API

You can enable the API using the command **Enable-SecAPIAccess**. The LoadMaster must be licensed for this command to work.

```
$eapi = Enable-SecAPIAccess -LoadBalancer $LMIP -Credential $creds

$eapi | Format-List
```

```
ReturnCode : 200
Response    : The API is enabled
Data        :
```

If you license a LoadMaster using the API, the API is automatically enabled.

2.8 Known Issues with Beta PowerShell Wrapper

The 7.2.39.0.334 version of the KEMP PowerShell wrapper has the following known issues:

ID number	Known Issue
PD-9539	The New-GeoCluster command fails if you try to add an already existing cluster.
PD-9480	GEO custom locations do not restore correctly.
PD-9507	The New-SdnController fails in a specific scenario: if you create an SDN controller or multiple SDN controllers and delete all the SDN controllers, you cannot add a new SDN controller.
PD-9525	In the Set-GeoFQDN command, the parameter SiteFailureDelay is specified in minutes but the returned value is in seconds.
PD-9523	A 200 success message is returned when the Get-GeoFQDN or Get-GeoCluster command is run for a non-existing FQDN/cluster.

Table 2-2: Known Issues

References

Unless otherwise specified, the following documents can be found at <http://kemptechnologies.com/documentation>.

WUI, Configuration Guide

KEMP LoadMaster, Product Overview

User Management, Feature Description

DoD Common Access Card Authentication, Feature Description

Document History

Date	Change	Reason for Change	Version	Resp.
Sep 2015	Release updates	Updates for 7.1-30	5.0	LB
Oct 2015	Minor updates	Updated header and footer	6.0	LB
Nov 2015	Minor updates	Enhancements made	7.0	LB
Dec 2015	Release updates	Updates for 7.1-32	8.0	LB
Jan 2016	Minor updates	Enhancements made	9.0	LB
Mar 2016	Minor updates	Enhancements made	10.0	LB
July 2016	Major updates	Help text moved into module	11.0	LB
Oct 2016	Release updates	Updates for 7.2.36	12.0	LB
Jan 2017	Release updates	Updates for 7.2.37	13.0	POC
Mar 2017	Release updates	Updates for 7.2.38	14.0	LB
June 2017	Release updates	Updates for 7.2.39	15.0	LB