N-Channel JFETs

PRODUCT SUMMARY				
Part Number	$V_{GS(off)}$ (V)	$V_{(BR)GSS}$ Min (V)	g_{fs} Min (mS)	I_{DSS} Min (mA)
2N4416	−≤6	−30	4.5	5
2N4416A	−2.5 to −6	−35	4.5	5
SST4416	−≤6	−30	4.5	5

FEATURES

- Excellent High-Frequency Gain: 2N4416/A, Gps 13 dB (typ) @ 400 MHz
- Very Low Noise: 3 dB (typ) @ 400 MHz
- Very Low Distortion
- High AC/DC Switch Off-Isolation

BENEFITS

- Wideband High Gain
- Very High System Sensitivity
- High Quality of Amplification
- High-Speed Switching Capability
- High Low-Level Signal Amplification

APPLICATIONS

- High-Frequency Amplifier/Mixer
- Oscillator
- Sample-and-Hold
- Very Low Capacitance Switches

DESCRIPTION

The 2N4416/2N4416A/SST4416 n-channel JFETs are designed to provide high-performance amplification at high frequencies.

The TO-206AF (TO-72) hermetically-sealed package is available with full military processing (see Military Information.) The TO-236 (SOT-23) package provides a low-cost option and is available with tape-and-reel options (see Packaging Information). For similar products in the TO-226AA (TO-92) package, see the J304/305 data sheet.

TO-206AF
(TO-72)



Top View

2N4416
2N4416A

TO-236
(SOT-23)



Top View

SST4416 (H1)*

*Marking Code for TO-236

For applications information see AN104.

ABSOLUTE MAXIMUM RATINGS

Gate-Drain, Gate-Source Voltage :
(2N/SST4416) . . . . . –30 V
(2N4416A) . . . . . –35 V
Gate Current . . . . . 10 mA
Lead Temperature . . . . . 300 °C
Storage Temperature : (2N Prefix) . . . . . –65 to 200 °C
(SST Prefix) . . . . . –65 to 150°C
Operating Junction Temperature . . . . . –55 to 150 °C
Power Dissipation : (2N Prefix)[a] . . . . . 300 mW
(SST Prefix)[b] . . . . . 350 mW

Notes
a. Derate 2.4 mW/°C above 25°C
b. Derate 2.8 mW/°C above 25°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

SPECIFICATIONS (T_A = 25°C UNLESS NOTED)

Parameter	Symbol	Test Conditions	Typ[a]	Limits 2N4416 Min	2N4416 Max	2N4416A Min	2N4416A Max	SST4416 Min	SST4416 Max	Unit
Static										
Gate-Source Breakdown Voltage	$V_{(BR)GSS}$	I_G = –1 μA , V_{DS} = 0 V	–36	–30		–35		–30		V
Gate-Source Cutoff Voltage	$V_{GS(off)}$	V_{DS} = 15 V, I_D = 1 nA	–3		–6	–2.5	–6		–6	V
Saturation Drain Current[b]	I_{DSS}	V_{DS} = 15 V, V_{GS} = 0 V	10	5	15	5	15	5	15	mA
Gate Reverse Current	I_{GSS}	V_{GS} = –20 V, V_{DS} = 0 V (2N)	–2		–100		–100			pA
		T_A = 150°C	–4		–100		–100			nA
		V_{GS} = –15 V, V_{DS} = 0 V (SST)	–0.002						–1	nA
		T_A = 125°C	–0.6							nA
Gate Operating Current	I_G	V_{DG} = 10 V, I_D = 1 mA	–20							pA
Drain Cutoff Current[c]	$I_{D(off)}$	V_{DS} = 10 V, V_{GS} = –6 V	2							pA
Drain-Source On-Resistance[c]	$r_{DS(on)}$	V_{GS} = 0 V, I_D = 300 μA	150							Ω
Gate-Source Forward Voltage[c]	$V_{GS(F)}$	I_G = 1 mA , V_{DS} = 0 V	0.7							V
Dynamic										
Common-Source Forward Transconductance[b]	g_{fs}	V_{DS} = 15 V, V_{GS} = 0 V f = 1 kHz	6	4.5	7.5	4.5	7.5	4.5	7.5	mS
Common-Source Output Conductance[b]	g_{os}		15		50		50		50	μS
Common-Source Input Capacitance	C_{iss}	V_{DS} = 15 V, V_{GS} = 0 V f = 1 MHz	2.2		4		4			pF
Common-Source Reverse Transfer Capacitance	C_{rss}		0.7		0.8		0.8			pF
Common-Source Output Capacitance	C_{oss}		1		2		2			pF
Equivalent Input Noise Voltage[c]	$\overline{e}_n$	V_{DS} = 10 V, V_{GS} = 0 V f = 1 kHz	6							nV/√Hz

HIGH-FREQUENCY SPECIFICATIONS FOR 2N4416/2N4416A (T_A = 25°C UNLESS NOTED)

Parameter	Symbol	Test Conditions	Limits 100 MHz Min	Limits 100 MHz Max	Limits 400 MHz Min	Limits 400 MHz Max	Unit
Common Source Input Conductance[d]	g_{iss}	V_{DS} = 15 V, V_{GS} = 0 V		100		1,000	µS
Common Source Input Susceptance[d]	b_{iss}			2,500		10,000	
Common Source Output Conductance[d]	g_{oss}			75		100	
Common Source Output Susceptance[d]	b_{oss}			1,000		4,000	
Common Source Forward Transconductance[d]	g_{fs}				4,000		
Common-Source Power Gain[d]	G_{ps}	V_{DS} = 15 V, I_D = 5 mA	18		10		dB
Noise Figure[d]	NF	R_G = 1 kΩ		2		4	

Notes
a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing. NH
b. Pulse test: PW ≤ 300 µs duty cycle ≤ 3%.
c. This parameter not registered with JEDEC.
d. Not a production test.

TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

Drain Current and Transconductance vs. Gate-Source Cutoff Voltage



On-Resistance and Output Conductance vs. Gate-Source Cutoff Voltage



Output Characteristics



Output Characteristics



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

Output Characteristics



Output Characteristics



Transfer Characteristics



Transfer Characteristics



Transconductance vs. Gate-Source Voltage



Transconductance vs. Gate-Source Voltgage



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

On-Resistance vs. Drain Current



Circuit Voltage Gain vs. Drain Current



Common-Source Input Capacitance vs. Gate-Source Voltage



Common-Source Reverse Feedback Capacitance vs. Gate-Source Voltage



Input Admittance



Forward Admittance



TYPICAL CHARACTERISTICS (T_A = 25°C UNLESS OTHERWISE NOTED)

Reverse Admittance



Output Admittance



Gate Leakage Current



Common-Source Forward Transconductance vs. Drain Current



Equivalent Input Noise Voltage vs. Frequency



Output Conductance vs. Drain Current



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see http://www.vishay.com/ppg?70242.

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.