



High Definition Tractography Networks

Eleftherios Garyfallidis^{1,2}


1. University of Cambridge, Cambridge UK

2. MRC Cognition and Brain Sciences Unit, Cambridge UK

Ian Nimmo-Smith²

MRC Cognition and Brain Sciences Unit, Cambridge UK

Background





Diffusion-weighted MR imaging (dMRI) is a non-invasive technique which can reveal important information about the directional organisation of the white matter fibres of the brain.

Tractography is a way to approximate these neuronal pathways using streamlines and connectivity profiles.

Deriving tractography from the raw MR data calls for a wide range of signal processing, medical imaging and machine learning techniques.

Reconstruction

$$\psi_{GQI2} = \mathbf{s} \cdot \mathbf{H}((6D.G \circ \mathbf{b} \circ \mathbf{1}) \cdot G) \lambda^3 / \pi$$



Tracking




Bundle Stats



Diffusion-weighted MR imaging (dMRI) is a non-invasive technique which can reveal important information about the directional organisation of the white matter fibres of the brain.

Across Subjects



Graph Theory

Network theory can be used at all levels of tractography analysis.

A tractography is a network of approximated neuronal fibre pathways.

We have further advanced the methods towards high definitions.

We provide state-of-the-art software for analysing these data sets and a solid ground for further implementation of graph-theoretic approaches.

[1] Garyfallidis et al. (2012) Towards an accurate brain tractography.

