Particle Swarm Optimization Multitensor Fitting.

Michael Paquette*, Eleftherios Garyfallidis*, Samuel St-Jean*, Pierrick Coupé[†], Maxime Descoteaux*

* Université de Sherbrooke, Sherbrooke, Canada

† McGill University, Montreal, Canada

For the purpose of the ISBI HARDI reconstruction challenge 2013 and for the categories DTI and HARDI we reconstructed the data by fitting a multitensor (MT) with particle swarm optimization (PSO) [?].

The goal is to find the optimal parameters so that the MT model, $\sum_{i=0}^{N} f_i e^{-bg^t D_i g}, \text{ fits the measured signal where } D_i \text{ is a rank 2}$ symmetric tensor with volume fraction f_i, g the normalized gradient wavevector and b the corresponding b-value. This is accomplished by minimizing the squared error $\sum_{k=0}^{M} \left(\sum_{i=0}^{N} f_i e^{-b_k g_k^t D_i g_k} - y_k\right)$ for a fixed diffusion signal $y = \{y_k\}_{k=0}^{M}$, number of compartment N and gradient scheme $\{b_k, g_k\}_{k=0}^{M}$

The DW dataset was denoised with the adaptive nonlocal means [?] using a rician noise model. As proposed in [?], each DW images were processed independently.

Hello [?], [?], [?], [?].	••
	••
•••	••
•••	•••
•••	••
•••	
•••	••
•••	••
	••
•••	••
	••
	••
•••	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
	••
This work is supported by	••
This work is supported by	••

...

...

...

...

...