

Recent advances in Diffusion Imaging in Python (Dipy)

Eleftherios Garyfallidis¹, Ariel Rokem², Bagrat Amirbekian³, Stefan van der Walt⁴, Mauro Zucchelli⁵, Jesus-Omar Ocegueda-Gonzalez⁶, Samuel St-Jean⁷, Gabriel Girard⁷, Michael Paquette⁷, Ian Nimmo-Smith⁸, Matthew Brett⁹, and Maxime Descoteaux¹⁰

¹University of Sherbrooke, Sherbrooke, Quebec, Canada, ²Stanford University, CA, United States, ³University of California, San Francisco, CA, United States, ⁴Stellenbosch University, Stellenbosch, South Africa, ⁵University of Verona, Italy, ⁶Centro de Investigacion en Matematicas, Mexico, ⁷University of Sherbrooke, Quebec, Canada, ⁸MRC Cognition & Brain Sciences Unit, Cambridge, United Kingdom, ⁹University of California, Berkeley, CA, United States, ¹⁰University of Sherbrooke, Sherbrooke, Canada

Target Audience/Purpose

This paper is targeted to everyone who uses or develops software for diffusion MRI (dMRI) analysis. The purpose of this abstract is to inform the researchers in dMRI about the recent and new algorithms implemented in Diffusion Imaging in Python (Dipy).

Methods

Diffusion Imaging in Python (Dipy) is a *free and open source* software project for the analysis of data from dMRI experiments. Dipy gathers implementations of many different methods in dMRI, including: diffusion signal pre-processing; reconstruction of diffusion distributions in individual voxels; fiber tractography and streamline post-processing, analysis and visualization. In contrast to many other scientific software projects, Dipy is not being developed by a single research group. Rather, it is an open project that encourages contributions from any scientist/developer through GitHub and open discussions on the project mailing list. Consequently, Dipy today has an international team of contributors, spanning seven academic institutions in five countries and three continents and is still growing. Dipy has a modular structure with the main modules depicted in fig.1. It also has a few hard dependencies shown with yellow colour in the same figure and some optional dependencies shown with orange colour. In Dipy we implement state-of-the-art methods in every level of the processing pipeline. *Pre-processing*: we have implemented novel adaptive denoising methods³, tools to create well distributed spheres (electrostatic repulsion), automatic SNR estimation, brain extraction and simulations (see bottom right figure). *Voxel Reconstruction*: a great range of methods that can be used for any type of q-space acquisition (single-shell, multi-shell and DSI-like). Here we reference briefly some of them: CSD¹, SDT⁴, DSI⁷, DSI Deconvolution⁸, CSA⁵, SHORE⁶, Tensors with least squares, weighted least squares and RESTORE¹⁰. We also support parallelization of reconstructions and peak finding for systems with




Figure 1: Modules and dependencies




Figure 3: Initial (left), centroids (middle), clusters (right)




Figure 4: Local reconstructions

multiple CPUs. *Fiber tracking*: we have implemented a fast deterministic algorithm (EuDX)¹¹ and a modular method for Probabilistic tracking. *Fiber analysis*: we can calculate metrics (e.g. length, curvature) for streamlines and also check if streamlines intersect with ROIs and create connectivity matrices. Furthermore, we have an efficient method to cluster streamlines called Quickbundles⁹ (see fig.2) that can be used to simplify large datasets. *Data Access*: we provide access to publicly available datasets and datasets for simulations. We can also read many different formats (e.g. Nifti1, Trackvis, HDF5).

Results/Discussion/Conclusion

In fig.2 we show the result of QuickBundles applied in the initial streamlines (left) and showing the centroids of the clusters (middle) and the final clusters (right). In fig.3 we show ellipsoids and ODFs for the same ROI of the same dataset with different reconstruction methods implemented in Dipy. In fig.4 we show at the left column the PDF (upper) and ODF (lower) from simulated datasets of a 60 degrees crossing using DSI⁷, and with DSI with deconvolution⁸ on the right column. More examples are available in the project's website². Dipy welcomes everyone to use or contribute in the project and give us feedback and suggestions.

References

- [1] Tournier et al. Non-negativity constrained super-resolved spherical deconvolution, Neuroimage (2007).
- [2] <http://dipy.org>
- [3] Coupe et al. Adaptive multi-resolution non-local means filter, IETIP (2012).
- [4] Descoteaux et al., Deterministic and probabilistic tractography based on complex fibre orientation distributions, IEEE TMI (2009).
- [5] Aganj et al, Reconstruction of the orientation distribution function in single and multiple shell q-ball imaging with the constant solid angle, MRM (2010).
- [6] Merlet et al, Continuous diffusion signal, EAP and ODF estimation via Compressed Sensing in diffusion MRI, MIA (2013).
- [7] Wedeen, Diffusion spectrum imaging of crossing fibers, Neuroimage. (2009)
- [8] Canales-Rodriguez, Deconvolution in diffusion spectrum imaging, Neuroimage 2010.
- [9] Garyfallidis et al., QuickBundles: a method for tractography simplification, Frontiers (2012).
- [10] Chang et al., RESTORE: robust estimation of Tensors, MRM (2005).
- [11] Garyfallidis, PhD thesis, (2012).




Figure 2: Simulations