


Probabilistic Topic Models: Expectation-Maximization Algorithm

ChengXiang “Cheng” Zhai
Department of Computer Science
University of Illinois at Urbana-Champaign

Probabilistic Topic Models: Expectation-Maximization (EM) Algorithm





Estimation of One Topic: $P(w | \theta_d)$

How to set θ_d to maximize $p(d | \Lambda)$?
(all other parameters are known)


d

... text mining...
is... clustering...
we.... Text.. the



If we know which word is from which distribution...

$$p(w_i | \theta_d) = \frac{c(w_i, d')}{\sum_{w' \in V} c(w', d')}$$



Given all the parameters, infer the distribution a word is from...

Is "text" more likely from θ_d or θ_B ?

From θ_d ($z=0$)? *from θ_d .*

$p(\theta_d)p(\text{"text"}|\theta_d)$

From θ_B ($z=1$)? *from θ_B .*

$p(\theta_B)p(\text{"text"}|\theta_B)$

$P(w|\theta_d)$

$p(w|\theta_B)$

θ_d
text 0.04
mining 0.035
association 0.03
clustering 0.005
...
the 0.000001

θ_B
the 0.03
a 0.02
is 0.015
we 0.01
food 0.003
...
text 0.000006

$p(\theta_d)+p(\theta_B)=1$

$P(\theta_d)=0.5$

$P(\theta_B)=0.5$

Topic Choice

$p(z=0 | w = \text{"text"}) =$

$$\frac{p(\theta_d)p(\text{"text"}|\theta_d)}{p(\theta_d)p(\text{"text"}|\theta_d) + p(\theta_B)p(\text{"text"}|\theta_B)}$$

*text/ θ_d > text/ θ_B .
但前面有 prior $p(\theta_d)$
和 $p(\theta_B)$. \therefore 要综合
以上两者*

The Expectation-Maximization (EM) Algorithm

Hidden Variable:

$z \in \{0, 1\}$

	z
the	1
paper	1
presents	1
a	1
text	0
mining	0
algorithm	0
for	1
clustering	0
...	...

- ① Initialize $p(w|\theta_d)$ with random values.
- ② Then iteratively improve it using E-step & M-step.
- ③ Stop when likelihood doesn't change.

$$p^{(n)}(z=0|w) = \frac{p(\theta_d)p^{(n)}(w|\theta_d)}{p(\theta_d)p^{(n)}(w|\theta_d) + p(\theta_B)p(w|\theta_B)}$$

E-step

How likely w is from θ_d

利用 E-step 算出的 z .

$$p^{(n+1)}(w|\theta_d) = \frac{c(w,d)p^{(n)}(z=0|w)}{\sum_{w' \in V} c(w',d)p^{(n)}(z=0|w')}$$

M-step

获得进一步的
子集

将相同组 ($z=\{0\}$) 分别处理.

EM Computation in Action

E-step
$$p^{(n)}(z = 0 | w) = \frac{p(\theta_d)p^{(n)}(w | \theta_d)}{p(\theta_d)p^{(n)}(w | \theta_d) + p(\theta_B)p(w | \theta_B)}$$

M-step
$$p^{(n+1)}(w | \theta_d) = \frac{c(w, d)p^{(n)}(z = 0 | w)}{\sum_{w' \in V} c(w', d)p^{(n)}(z = 0 | w')}$$

Assume
 $p(\theta_d) = p(\theta_B) = 0.5$
 and $p(w | \theta_B)$ is known

Word	#	$p(w \theta_B)$	Iteration 1		Iteration 2		Iteration 3	
			$P(w \theta)$	$p(z=0 w)$	$P(w \theta)$	$P(z=0 w)$	$P(w \theta)$	$P(z=0 w)$
The	4	0.5	0.25	0.33	0.20	0.29	0.18	0.26
Paper	2	0.3	0.25	0.45	0.14	0.32	0.10	0.25
Text	4	0.1	0.25	0.71	0.44	0.81	0.50	0.93
Mining	2	0.1	0.25	0.71	0.22	0.69	0.22	0.69
Log-Likelihood			-16.96		-16.13		-16.02	

Likelihood increasing
 值取值范围是 (0,1) ... $\log < 0$.

"By products": Are they also useful? 7

EM As Hill-Climbing → Converge to Local Maximum

类似于 梯度上升.

Likelihood $p(d|\theta)$

① E-step = computing the lower bound

Original likelihood

Lower bound of likelihood function

next guess $p^{(n+1)}(w|\theta_d)$

current guess $p^{(n)}(w|\theta_d)$

② M-step = maximizing the lower bound

①: 计算 lower bound.

②: 找到 lower bound 最大值

③ 逐步提升.

Summary

- Expectation-Maximization (EM) algorithm
 - General algorithm for computing ML estimate of mixture models
 - Hill-climbing, so can only converge to a local maximum (depending on initial points) 关于梯度下降的理解。
- E-step: “augment” data by predicting values of useful hidden variables 通过预测有用的隐藏变量来简化计算。
- M-step: exploit the “augmented data” to improve estimate of parameters (“improve” is guaranteed in terms of likelihood)
- “Data augmentation” is probabilistic → Split counts of events probabilistically